

# Oracle Database 11g: SQL Fundamentals I

Volume I • Student Guide

D49996GC11

Edition 1.1

April 2009

D59980

**ORACLE**

Oracle Internal & Oracle Academy  
Use Only

## **Authors**

Puja Singh  
Brian Pottle

## **Technical Contributors and Reviewers**

Claire Bennett  
Tom Best  
Purjanti Chang  
Ken Cooper  
László Czinkóczki  
Burt Demchick  
Mark Fleming  
Gerlinde Frenzen  
Nancy Greenberg  
Chaitanya Koratamaddi  
Wendy Lo  
Timothy Mcglue  
Alan Paulson  
Bryan Roberts  
Abhishek Singh  
Lori Tritz  
Michael Versaci  
Lex van der Werff

## **Editors**

Raj Kumar  
Amitha Narayan  
Vijayalakshmi Narasimhan

## **Graphic Designer**

Satish Bettgowda

## **Publishers**

Sujatha Nagendra  
Syed Ali

**Copyright © 2009, Oracle. All rights reserved.**

### **Disclaimer**

This document contains proprietary information and is protected by copyright and other intellectual property laws. You may copy and print this document solely for your own use in an Oracle training course. The document may not be modified or altered in any way. Except where your use constitutes "fair use" under copyright law, you may not use, share, download, upload, copy, print, display, perform, reproduce, publish, license, post, transmit, or distribute this document in whole or in part without the express authorization of Oracle.

The information contained in this document is subject to change without notice. If you find any problems in the document, please report them in writing to: Oracle University, 500 Oracle Parkway, Redwood Shores, California 94065 USA. This document is not warranted to be error-free.

### **Restricted Rights Notice**

If this documentation is delivered to the United States Government or anyone using the documentation on behalf of the United States Government, the following notice is applicable:

#### **U.S. GOVERNMENT RIGHTS**

The U.S. Government's rights to use, modify, reproduce, release, perform, display, or disclose these training materials are restricted by the terms of the applicable Oracle license agreement and/or the applicable U.S. Government contract.

### **Trademark Notice**

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Oracle Internal & Oracle Academy  
Use Only

# Contents

## Preface

### I Introduction

Lesson Objectives	I-2
Lesson Agenda	I-3
Course Objectives	I-4
Course Agenda	I-5
Appendixes Used in the Course	I-7
Lesson Agenda	I-8
Oracle Database 11g: Focus Areas	I-9
Oracle Database 11g	I-10
Oracle Fusion Middleware	I-12
Oracle Enterprise Manager Grid Control 10g	I-13
Oracle BI Publisher	I-14
Lesson Agenda	I-15
Relational and Object Relational Database Management Systems	I-16
Data Storage on Different Media	I-17
Relational Database Concept	I-18
Definition of a Relational Database	I-19
Data Models	I-20
Entity Relationship Model	I-21
Entity Relationship Modeling Conventions	I-23
Relating Multiple Tables	I-25
Relational Database Terminology	I-27
Lesson Agenda	I-29
Using SQL to Query Your Database	I-30
SQL Statements	I-31
Development Environments for SQL	I-32
Lesson Agenda	I-33
The Human Resources (HR) Schema	I-34
Tables Used in the Course	I-35
Lesson Agenda	I-36
Oracle Database 11g Documentation	I-37
Additional Resources	I-38

Summary 1-39  
Practice I: Overview 1-40

## **1 Retrieving Data Using the SQL `SELECT` Statement**

Objectives 1-2  
Lesson Agenda 1-3  
Capabilities of SQL `SELECT` Statements 1-4  
Basic `SELECT` Statement 1-5  
Selecting All Columns 1-6  
Selecting Specific Columns 1-7  
Writing SQL Statements 1-8  
Column Heading Defaults 1-9  
Lesson Agenda 1-10  
Arithmetic Expressions 1-11  
Using Arithmetic Operators 1-12  
Operator Precedence 1-13  
Defining a Null Value 1-14  
Null Values in Arithmetic Expressions 1-15  
Lesson Agenda 1-16  
Defining a Column Alias 1-17  
Using Column Aliases 1-18  
Lesson Agenda 1-19  
Concatenation Operator 1-20  
Literal Character Strings 1-21  
Using Literal Character Strings 1-22  
Alternative Quote (`q`) Operator 1-23  
Duplicate Rows 1-24  
Lesson Agenda 1-25  
Displaying the Table Structure 1-26  
Using the `DESCRIBE` Command 1-27  
Quiz 1-28  
Summary 1-29  
Practice 1: Overview 1-30

## **2 Restricting and Sorting Data**

Objectives 2-2  
Lesson Agenda 2-3  
Limiting Rows Using a Selection 2-4  
Limiting the Rows That Are Selected 2-5  
Using the `WHERE` Clause 2-6

Character Strings and Dates 2-7  
Comparison Operators 2-8  
Using Comparison Operators 2-9  
Range Conditions Using the BETWEEN Operator 2-10  
Membership Condition Using the IN Operator 2-11  
Pattern Matching Using the LIKE Operator 2-12  
Combining Wildcard Characters 2-13  
Using the NULL Conditions 2-14  
Defining Conditions Using the Logical Operators 2-15  
Using the AND Operator 2-16  
Using the OR Operator 2-17  
Using the NOT Operator 2-18  
Lesson Agenda 2-19  
Rules of Precedence 2-20  
Lesson Agenda 2-22  
Using the ORDER BY Clause 2-23  
Sorting 2-24  
Lesson Agenda 2-26  
Substitution Variables 2-27  
Using the Single-Ampersand Substitution Variable 2-29  
Character and Date Values with Substitution Variables 2-31  
Specifying Column Names, Expressions, and Text 2-32  
Using the Double-Ampersand Substitution Variable 2-33  
Lesson Agenda 2-34  
Using the DEFINE Command 2-35  
Using the VERIFY Command 2-36  
Quiz 2-37  
Summary 2-38  
Practice 2: Overview 2-39

### **3 Using Single-Row Functions to Customize Output**

Objectives 3-2  
Lesson Agenda 3-3  
SQL Functions 3-4  
Two Types of SQL Functions 3-5  
Single-Row Functions 3-6  
Lesson Agenda 3-8  
Character Functions 3-9  
Case-Conversion Functions 3-11  
Using Case-Conversion Functions 3-12

Character-Manipulation Functions 3-13  
Using the Character-Manipulation Functions 3-14  
Lesson Agenda 3-15  
Number Functions 3-16  
Using the ROUND Function 3-17  
Using the TRUNC Function 3-18  
Using the MOD Function 3-19  
Lesson Agenda 3-20  
Working with Dates 3-21  
RR Date Format 3-22  
Using the SYSDATE Function 3-24  
Arithmetic with Dates 3-25  
Using Arithmetic Operators with Dates 3-26  
Lesson Agenda 3-27  
Date-Manipulation Functions 3-28  
Using Date Functions 3-29  
Using ROUND and TRUNC Functions with Dates 3-30  
Quiz 3-31  
Summary 3-32  
Practice 3: Overview 3-33

#### **4 Using Conversion Functions and Conditional Expressions**

Objectives 4-2  
Lesson Agenda 4-3  
Conversion Functions 4-4  
Implicit Data Type Conversion 4-5  
Explicit Data Type Conversion 4-7  
Lesson Agenda 4-10  
Using the TO\_CHAR Function with Dates 4-11  
Elements of the Date Format Model 4-12  
Using the TO\_CHAR Function with Dates 4-16  
Using the TO\_CHAR Function with Numbers 4-17  
Using the TO\_NUMBER and TO\_DATE Functions 4-20  
Using the TO\_CHAR and TO\_DATE Function with RR Date Format 4-22  
Lesson Agenda 4-23  
Nesting Functions 4-24  
Lesson Agenda 4-26  
General Functions 4-27  
NVL Function 4-28  
Using the NVL Function 4-29

Using the NVL2 Function 4-30  
Using the NULLIF Function 4-31  
Using the COALESCE Function 4-32  
Lesson Agenda 4-35  
Conditional Expressions 4-36  
CASE Expression 4-37  
Using the CASE Expression 4-38  
DECODE Function 4-39  
Using the DECODE Function 4-40  
Quiz 4-42  
Summary 4-43  
Practice 4: Overview 4-44

## **5 Reporting Aggregated Data Using the Group Functions**

Objectives 5-2  
Lesson Agenda 5-3  
What Are Group Functions? 5-4  
Types of Group Functions 5-5  
Group Functions: Syntax 5-6  
Using the AVG and SUM Functions 5-7  
Using the MIN and MAX Functions 5-8  
Using the COUNT Function 5-9  
Using the DISTINCT Keyword 5-10  
Group Functions and Null Values 5-11  
Lesson Agenda 5-12  
Creating Groups of Data 5-13  
Creating Groups of Data: GROUP BY Clause Syntax 5-14  
Using the GROUP BY Clause 5-15  
Grouping by More than One Column 5-17  
Using the GROUP BY Clause on Multiple Columns 5-18  
Illegal Queries Using Group Functions 5-19  
Restricting Group Results 5-21  
Restricting Group Results with the HAVING Clause 5-22  
Using the HAVING Clause 5-23  
Lesson Agenda 5-25  
Nesting Group Functions 5-26  
Quiz 5-27  
Summary 5-28  
Practice 5: Overview 5-29

## **6 Displaying Data from Multiple Tables**

Objectives 6-2

Lesson Agenda 6-3

Obtaining Data from Multiple Tables 6-4

Types of Joins 6-5

Joining Tables Using SQL:1999 Syntax 6-6

Qualifying Ambiguous Column Names 6-7

Lesson Agenda 6-8

Creating Natural Joins 6-9

Retrieving Records with Natural Joins 6-10

Creating Joins with the USING Clause 6-11

Joining Column Names 6-12

Retrieving Records with the USING Clause 6-13

Using Table Aliases with the USING Clause 6-14

Creating Joins with the ON Clause 6-15

Retrieving Records with the ON Clause 6-16

Creating Three-Way Joins with the ON Clause 6-17

Applying Additional Conditions to a Join 6-18

Lesson Agenda 6-19

Joining a Table to Itself 6-20

Self-Joins Using the ON Clause 6-21

Lesson Agenda 6-22

Nonequijoins 6-23

Retrieving Records with Nonequijoins 6-24

Lesson Agenda 6-25

Returning Records with No Direct Match Using OUTER Joins 6-26

INNER Versus OUTER Joins 6-27

LEFT OUTER JOIN 6-28

RIGHT OUTER JOIN 6-29

FULL OUTER JOIN 6-30

Lesson Agenda 6-31

Cartesian Products 6-32

Generating a Cartesian Product 6-33

Creating Cross Joins 6-34

Quiz 6-35

Summary 6-36

Practice 6: Overview 6-37

## **7 Using Subqueries to Solve Queries**

- Objectives 7-2
- Lesson Agenda 7-3
- Using a Subquery to Solve a Problem 7-4
- Subquery Syntax 7-5
- Using a Subquery 7-6
- Guidelines for Using Subqueries 7-7
- Types of Subqueries 7-8
- Lesson Agenda 7-9
- Single-Row Subqueries 7-10
- Executing Single-Row Subqueries 7-11
- Using Group Functions in a Subquery 7-12
- The `HAVING` Clause with Subqueries 7-13
- What Is Wrong with This Statement? 7-14
- No Rows Returned by the Inner Query 7-15
- Lesson Agenda 7-16
- Multiple-Row Subqueries 7-17
- Using the `ANY` Operator in Multiple-Row Subqueries 7-18
- Using the `ALL` Operator in Multiple-Row Subqueries 7-19
- Lesson Agenda 7-20
- Null Values in a Subquery 7-21
- Quiz 7-23
- Summary 7-24
- Practice 7: Overview 7-25

## **8 Using the Set Operators**

- Objectives 8-2
- Lesson Agenda 8-3
- Set Operators 8-4
- Set Operator Guidelines 8-5
- The Oracle Server and Set Operators 8-6
- Lesson Agenda 8-7
- Tables Used in This Lesson 8-8
- Lesson Agenda 8-12
- `UNION` Operator 8-13
- Using the `UNION` Operator 8-14
- `UNION ALL` Operator 8-16
- Using the `UNION ALL` Operator 8-17
- Lesson Agenda 8-18
- `INTERSECT` Operator 8-19

Using the `INTERSECT` Operator 8-20  
Lesson Agenda 8-21  
`MINUS` Operator 8-22  
Using the `MINUS` Operator 8-23  
Lesson Agenda 8-24  
Matching the `SELECT` Statements 8-25  
Matching the `SELECT` Statement: Example 8-26  
Lesson Agenda 8-27  
Using the `ORDER BY` Clause in Set Operations 8-28  
Quiz 8-29  
Summary 8-30  
Practice 8: Overview 8-31

## **9 Manipulating Data**

Objectives 9-2  
Lesson Agenda 9-3  
Data Manipulation Language 9-4  
Adding a New Row to a Table 9-5  
`INSERT` Statement Syntax 9-6  
Inserting New Rows 9-7  
Inserting Rows with Null Values 9-8  
Inserting Special Values 9-9  
Inserting Specific Date and Time Values 9-10  
Creating a Script 9-11  
Copying Rows from Another Table 9-12  
Lesson Agenda 9-13  
Changing Data in a Table 9-14  
`UPDATE` Statement Syntax 9-15  
Updating Rows in a Table 9-16  
Updating Two Columns with a Subquery 9-17  
Updating Rows Based on Another Table 9-18  
Lesson Agenda 9-19  
Removing a Row from a Table 9-20  
`DELETE` Statement 9-21  
Deleting Rows from a Table 9-22  
Deleting Rows Based on Another Table 9-23  
`TRUNCATE` Statement 9-24  
Lesson Agenda 9-25  
Database Transactions 9-26  
Database Transactions: Start and End 9-27

Advantages of COMMIT and ROLLBACK Statements	9-28
Explicit Transaction Control Statements	9-29
Rolling Back Changes to a Marker	9-30
Implicit Transaction Processing	9-31
State of the Data Before COMMIT or ROLLBACK	9-33
State of the Data After COMMIT	9-34
Committing Data	9-35
State of the Data After ROLLBACK	9-36
State of the Data After ROLLBACK: Example	9-37
Statement-Level Rollback	9-38
Lesson Agenda	9-39
Read Consistency	9-40
Implementing Read Consistency	9-41
Lesson Agenda	9-42
FOR UPDATE Clause in a SELECT Statement	9-43
FOR UPDATE Clause: Examples	9-44
Quiz	9-46
Summary	9-47
Practice 9: Overview	9-48

## **10 Using DDL Statements to Create and Manage Tables**

Objectives	10-2
Lesson Agenda	10-3
Database Objects	10-4
Naming Rules	10-5
Lesson Agenda	10-6
CREATE TABLE Statement	10-7
Referencing Another User's Tables	10-8
DEFAULT Option	10-9
Creating Tables	10-10
Lesson Agenda	10-11
Data Types	10-12
Datetime Data Types	10-14
Lesson Agenda	10-15
Including Constraints	10-16
Constraint Guidelines	10-17
Defining Constraints	10-18
NOT NULL Constraint	10-20
UNIQUE Constraint	10-21
PRIMARY KEY Constraint	10-23

FOREIGN KEY Constraint 10-24  
FOREIGN KEY Constraint: Keywords 10-26  
CHECK Constraint 10-27  
CREATE TABLE: Example 10-28  
Violating Constraints 10-29  
Lesson Agenda 10-31  
Creating a Table Using a Subquery 10-32  
Lesson Agenda 10-34  
ALTER TABLE Statement 10-35  
Read-Only Tables 10-36  
Lesson Agenda 10-37  
Dropping a Table 10-38  
Quiz 10-39  
Summary 10-40  
Practice 10: Overview 10-41

## **11 Creating Other Schema Objects**

Objectives 11-2  
Lesson Agenda 11-3  
Database Objects 11-4  
What Is a View? 11-5  
Advantages of Views 11-6  
Simple Views and Complex Views 11-7  
Creating a View 11-8  
Retrieving Data from a View 11-11  
Modifying a View 11-12  
Creating a Complex View 11-13  
Rules for Performing DML Operations on a View 11-14  
Using the WITH CHECK OPTION Clause 11-17  
Denying DML Operations 11-18  
Removing a View 11-20  
Practice 11: Overview of Part 1 11-21  
Lesson Agenda 11-22  
Sequences 11-23  
CREATE SEQUENCE Statement: Syntax 11-25  
Creating a Sequence 11-26  
NEXTVAL and CURRVAL Pseudocolumns 11-27  
Using a Sequence 11-29  
Caching Sequence Values 11-30  
Modifying a Sequence 11-31

Guidelines for Modifying a Sequence	11-32
Lesson Agenda	11-33
Indexes	11-34
How Are Indexes Created?	11-36
Creating an Index	11-37
Index Creation Guidelines	11-38
Removing an Index	11-39
Lesson Agenda	11-40
Synonyms	11-41
Creating a Synonym for an Object	11-42
Creating and Removing Synonyms	11-43
Quiz	11-44
Summary	11-45
Practice 11: Overview of Part 2	11-46

## **Appendix A: Practice Solutions**

## **Appendix B: Table Descriptions**

## **Appendix C: Oracle Join Syntax**

Objectives	C-2
Obtaining Data from Multiple Tables	C-3
Cartesian Products	C-4
Generating a Cartesian Product	C-5
Types of Oracle-Proprietary Joins	C-6
Joining Tables Using Oracle Syntax	C-7
Qualifying Ambiguous Column Names	C-8
Equijoins	C-9
Retrieving Records with Equijoins	C-10
Retrieving Records with Equijoins: Example	C-11
Additional Search Conditions Using the AND Operator	C-12
Joining More than Two Tables	C-13
Nonequijoins	C-14
Retrieving Records with Nonequijoins	C-15
Returning Records with No Direct Match with Outer Joins	C-16
Outer Joins: Syntax	C-17
Using Outer Joins	C-18
Outer Join: Another Example	C-19
Joining a Table to Itself	C-20
Self-Join: Example	C-21

Summary C-22  
Practice C: Overview C-23

## **Appendix D: Using SQL\*Plus**

Objectives D-2  
SQL and SQL\*Plus Interaction D-3  
SQL Statements Versus SQL\*Plus Commands D-4  
Overview of SQL\*Plus D-5  
Logging In to SQL\*Plus D-6  
Displaying Table Structure D-8  
SQL\*Plus Editing Commands D-10  
Using LIST, n, and APPEND D-12  
Using the CHANGE Command D-13  
SQL\*Plus File Commands D-14  
Using the SAVE, START, and EDIT Commands D-15  
SERVEROUTPUT Command D-17  
Using the SQL\*Plus SPOOL Command D-18  
Using the AUTOTRACE Command D-19  
Summary D-20

## **Appendix E: Using SQL Developer**

Objectives E-2  
What Is Oracle SQL Developer? E-3  
Specifications of SQL Developer E-4  
Installing SQL Developer E-5  
SQL Developer 1.2 Interface E-6  
Creating a Database Connection E-7  
Browsing Database Objects E-10  
Creating a Schema Object E-11  
Creating a New Table: Example E-12  
Using the SQL Worksheet E-13  
Executing SQL Statements E-16  
Saving SQL Scripts E-17  
Executing Saved Script Files: Method 1 E-18  
Executing Saved Script Files: Method 2 E-19  
Executing SQL Statements E-20  
Formatting the SQL Code E-21  
Using Snippets E-22  
Using Snippets: Example E-23  
Using SQL\*Plus E-24

Debugging Procedures and Functions	E-25
Database Reporting	E-26
Creating a User-Defined Report	E-27
Search Engines and External Tools	E-28
Setting Preferences	E-29
Specifications of SQL Developer 1.5.3	E-30
Installing SQL Developer 1.5.3	E-31
SQL Developer 1.5.3 Interface	E-32
Summary	E-34

## **Index**

## **Additional Practices**

## **Additional Practices: Solutions**

Oracle Internal & Oracle Academy  
Use Only

Oracle Internal & Oracle Academy  
Use Only

---

# Preface

---

Oracle Internal & Oracle Academy  
Use Only



**Profile****Before You Begin This Course**

Before you begin this course, you should be able to use a graphical user interface (GUI). The prerequisite is a familiarity with data processing concepts and techniques.

**How This Course Is Organized**

*Oracle Database 11g: SQL Fundamentals I* is an instructor-led course featuring lectures and hands-on exercises. Online demonstrations and written practice sessions reinforce the concepts and skills that are introduced.

Oracle Internal & Oracle Academy  
Use Only

## Related Publications

### Oracle Publications

Title	Part Number
<i>Oracle® Database Reference 11g Release 1 (11.1)</i>	B28320-01
<i>Oracle® Database SQL Language Reference 11g Release 1 (11.1)</i>	B28286-01
<i>Oracle® Database Concepts 11g Release 1 (11.1)</i>	B28318-01
<i>Oracle® Database SQL Developer User's Guide Release 1.2</i>	E10406-01

### Additional Publications

- System release bulletins
- Installation and user's guides
- *read.me* files
- International Oracle User's Group (IOUG) articles
- *Oracle Magazine*

Oracle Internal & Oracle Academy  
Use Only

## Typographic Conventions

What follows are two lists of typographical conventions that are used specifically within text or within code.

### Typographic Conventions Within Text

Convention	Object or Term	Example
Uppercase	Commands, functions, column names, table names, PL/SQL objects, schemas	Use the <code>SELECT</code> command to view information stored in the <code>LAST_NAME</code> column of the <code>EMPLOYEES</code> table.
Lowercase, italic	Filenames, syntax variables, usernames, passwords	<b>where:</b> <i>role</i> is the name of the role to be created.
Initial cap	Trigger and button names	Assign a When-Validate-Item trigger to the ORD block.  Choose Cancel.
Italic	Books, names of courses and manuals, and emphasized words or phrases	For more information on the subject see <i>Oracle SQL Reference Manual</i>  <i>Do not</i> save changes to the database.
Quotation marks	Lesson module titles referenced within a course	This subject is covered in Lesson 3, “Working with Objects.”

## Typographic Conventions (continued)

### Typographic Conventions Within Code

Convention	Object or Term	Example
Uppercase	Commands, functions	<code>SELECT employee_id FROM employees;</code>
Lowercase, italic	Syntax variables	<code>CREATE ROLE <i>role</i>;</code>
Initial cap	Forms triggers	<code>Form module: ORD Trigger level: S_ITEM.QUANTITY item Trigger name: When-Validate-Item . . .</code>
Lowercase	Column names, table names, filenames, PL/SQL objects	<code>. . . OG_ACTIVATE_LAYER (OG_GET_LAYER ('prod_pie_layer')) . . .  SELECT last_name FROM employees;</code>
Bold	Text that must be entered by a user	<code>CREATE USER <b>scott</b> IDENTIFIED BY <b>tiger</b>;</code>

# I Introduction

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Lesson Objectives

After completing this lesson, you should be able to do the following:

- Understand the goals of the course
- List the features of Oracle Database 11g
- Discuss the theoretical and physical aspects of a relational database
- Describe Oracle server's implementation of RDBMS and object relational database management system (ORDBMS)
- Identify the development environments that can be used for this course
- Describe the database and schema used in this course

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

In this lesson, you gain an understanding of the relational database management system (RDBMS) and the object relational database management system (ORDBMS). You are also introduced to Oracle SQL Developer and SQL\*Plus as development environments used for executing SQL statements, and for formatting and reporting purposes.

## Lesson Agenda

- Course objectives, agenda, and appendixes used in the course
- Overview of Oracle Database 11g and related products
- Overview of relational database management concepts and terminologies
- Introduction to SQL and its development environments
- The HR schema and the tables used in this course
- Oracle Database 11g documentation and additional resources

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Course Objectives

After completing this course, you should be able to:

- Identify the major components of Oracle Database 11g
- Retrieve row and column data from tables with the `SELECT` statement
- Create reports of sorted and restricted data
- Employ SQL functions to generate and retrieve customized data
- Run complex queries to retrieve data from multiple tables
- Run data manipulation language (DML) statements to update data in Oracle Database 11g
- Run data definition language (DDL) statements to create and manage schema objects

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Course Objectives

This course offers you an introduction to Oracle Database 11g database technology. In this class, you learn the basic concepts of relational databases and the powerful SQL programming language. This course provides the essential SQL skills that enable you to write queries against single and multiple tables, manipulate data in tables, create database objects, and query metadata.

# Course Agenda

- Day 1:
  - Introduction
  - Retrieving Data Using the SQL `SELECT` Statement
  - Restricting and Sorting Data
  - Using Single-Row Functions to Customize Output
  - Using Conversion Functions and Conditional Expressions
- Day 2:
  - Reporting Aggregated Data Using the Group Functions
  - Displaying Data from Multiple Tables
  - Using Subqueries to Solve Queries
  - Using the Set Operators

ORACLE

Copyright © 2009, Oracle. All rights reserved.

# Course Agenda

- Day 3:
  - Manipulating Data
  - Using DDL Statements to Create and Manage Tables
  - Creating Other Schema Objects

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Appendixes Used in the Course

- Appendix A: Practice Solutions
- Appendix B: Table Descriptions
- Appendix C: Oracle Join Syntax
- Appendix D: Using SQL\*Plus
- Appendix E: Using SQL Developer
- Additional Practices
- Additional Practices Solutions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Lesson Agenda

- Course objectives, course agenda, and appendixes used in this course
- Overview of Oracle Database 11g and related products
- Overview of relational database management concepts and terminologies
- Introduction to SQL and its development environments
- The HR schema and the tables used in this course
- Oracle Database 11g documentation and additional resources

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Oracle Database 11g: Focus Areas



Infrastructure  
Grids

Information  
Management

Application  
Development

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Oracle Database 11g: Focus Areas

Oracle Database 11g offers extensive features across the following focus areas:

- **Infrastructure Grids:** The Infrastructure Grid technology of Oracle enables pooling of low-cost servers and storage to form systems that deliver the highest quality of service in terms of manageability, high availability, and performance. Oracle Database 11g consolidates and extends the benefits of grid computing. Apart from taking full advantage of grid computing, Oracle Database 11g has unique change assurance features to manage changes in a controlled and cost effective manner.
- **Information Management:** Oracle Database 11g extends the existing information management capabilities in content management, information integration, and information life cycle management areas. Oracle provides content management of advanced data types such as Extensible Markup Language (XML), text, spatial, multimedia, medical imaging, and semantic technologies.
- **Application Development:** Oracle Database 11g has capabilities to use and manage all the major application development environments such as PL/SQL, Java/JDBC, .NET and Windows, PHP, SQL Developer, and Application Express.

# Oracle Database 11g



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Oracle Database 11g

Organizations need to support multiple terabytes of information for users who demand fast and secure access to business applications round-the-clock. The database systems must be reliable and must be able to recover quickly in the event of any kind of failure. Oracle Database 11g is designed along the following feature areas to help organizations manage infrastructure grids easily and deliver high-quality service:

- **Manageability:** By using some of the change assurance, management automation, and fault diagnostics features, the database administrators (DBAs) can increase their productivity, reduce costs, minimize errors, and maximize quality of service. Some of the useful features that promote better management are Database Replay facility, the SQL Performance Analyzer, and the Automatic SQL Tuning facility.
- **High availability:** By using the high availability features, you can reduce the risk of down time and data loss. These features improves online operations and enable faster database upgrades.

# Oracle Database 11g



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Oracle Database 11g (continued)

- **Performance:** By using capabilities such as SecureFiles, compression for online transaction processing (OLTP), Real Application Clusters (RAC) optimizations, Result Caches and so on, you can greatly improve the performance of your database. Oracle Database 11g enables organizations to manage large, scalable transactional and data warehousing systems that deliver fast data access using low-cost modular storage.
- **Security:** Oracle Database 11g helps organizations protect their information with unique secure configurations, data encryption and masking, and sophisticated auditing capabilities. It delivers a secure and scalable platform for reliable and fast access to all types of information by using the industry-standard interfaces.
- **Information integration:** Oracle Database 11g has many features to better integrate data throughout the enterprise. It also supports advanced information life cycle management capabilities. This helps you manage the changing data in your database.

# Oracle Fusion Middleware

Portfolio of leading, standards-based, and customer-proven software products that spans a range of tools and services from J2EE and developer tools, through integration services, business intelligence, collaboration, and content management



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Oracle Fusion Middleware

Oracle Fusion Middleware is a comprehensive and well-integrated family of products that offers complete support for development, deployment, and management of Service-Oriented Architecture (SOA). SOA facilitates the development of modular business services that can be easily integrated and reused, thereby reducing development and maintenance costs, and providing higher quality of services. Oracle Fusion Middleware's pluggable architecture enables you to leverage your investments in any existing application, system, or technology. Its unbreakable core technology minimizes the disruption caused by planned or unplanned outages.

Some of the products from the Oracle Fusion Middleware family include:

- **Enterprise Application Server:** Application Server
- **Integration and Process Management:** BPEL Process Manager, Oracle Business Process Analysis Suite
- **Development Tools:** Oracle Application Development Framework, JDeveloper, SOA Suite
- **Business Intelligence:** Oracle Business Activity Monitoring, Oracle Data Integrator
- **Systems Management:** Enterprise Manager
- **Identity Management:** Oracle Identity Management
- **Content Management:** Oracle Content Database Suite
- **User Interaction:** Portal, WebCenter

## Oracle Enterprise Manager Grid Control 10g

- Efficient Oracle Fusion Middleware management
- Simplifying application and infrastructure life cycle management
- Improved database administration and application management capabilities



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Oracle Enterprise Manager Grid Control 10g

Spanning applications, middleware, and database management, Oracle Enterprise Manager Grid Control 10g delivers integrated enterprise management for Oracle and non-Oracle systems.

Oracle Enterprise Manager Grid Control 10g features advanced Oracle Fusion Middleware management capabilities for the services that business applications rely upon, including SOA, Business Activity Monitoring, and Identity Management.

- **Wide-ranging management functionality** for your applications including service-level management, application performance management, configuration management, and change automation
- **Built-in grid automation capabilities** means that information technology responds proactively to fluctuating demand and implements new services more quickly so that businesses can thrive.
- **In-depth diagnostics and readily available remediation** across a range of applications including custom-built applications, Oracle E-Business Suite, PeopleSoft, Siebel, Oracle Fusion Middleware, Oracle Database, and underlying infrastructure
- **Extensive life cycle management capabilities** extends grid computing by providing solutions for the entire application and infrastructure life cycle, including test, stage, and production through operations. It has simplified patch management with synchronized patching, additional operating system support, and conflict detection features.

# Oracle BI Publisher

- Provides a central architecture for authoring, managing, and delivering information in secure and multiple formats
- Reduces complexity and time to develop, test, and deploy all kinds of reports
  - Financial Reports, Invoices, Sales or Purchase orders, XML, and EDI/EFT(eText documents)
- Enables flexible customizations
  - For example, a Microsoft Word document report can be generated in multiple formats such as PDF, HTML, Excel, RTF, and so on.



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Oracle BI Publisher

Oracle Database 11g also includes Oracle BI Publisher—the enterprise reporting solution from Oracle. Oracle BI Publisher (formerly known as XML Publisher) offers the most efficient and scalable reporting solution available for complex, distributed environments.

Oracle BI Publisher reduces the high costs associated with the development, customization, and maintenance of business documents, while increasing the efficiency of reports management. By using a set of familiar desktop tools, users can create and maintain their own report formats based on data queries created by the IT staff or developers.

Oracle BI Publisher report formats can be designed using Microsoft Word or Adobe Acrobat—tools that most users are already familiar with. Oracle BI Publisher also enables you to bring in data from multiple data sources into a single output document. You can deliver reports via printer, email, or fax. You can publish your report to a portal. You can even allow users to collaboratively edit and manage reports on the Web-based Distributed Authoring and Versioning (WebDav) Web servers.

## Lesson Agenda

- Course objectives, course agenda, and appendixes used in this course
- Overview of Oracle Database 11g and related products
- **Overview of relational database management concepts and terminologies**
- Introduction to SQL and its development environments
- The HR schema and the tables used in this course
- Oracle Database 11g documentation and additional resources

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Relational and Object Relational Database Management Systems

- Relational model and object relational model
- User-defined data types and objects
- Fully compatible with relational database
- Supports multimedia and large objects
- High-quality database server features



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Relational and Object Relational Database Management Systems


The Oracle server supports both the relational and the object relational database models.

The Oracle server extends the data-modeling capabilities to support an object relational database model that provides object-oriented programming, complex data types, complex business objects, and full compatibility with the relational world.

It includes several features for improved performance and functionality of the OLTP applications, such as better sharing of run-time data structures, larger buffer caches, and deferrable constraints. Data warehouse applications benefit from enhancements such as parallel execution of insert, update, and delete operations; partitioning; and parallel-aware query optimization. The Oracle model supports client/server and Web-based applications that are distributed and multitiered.

For more information about the relational and object relational model, see the *Oracle Database Concepts 11g Release 1 (11.1)* manual.

## Data Storage on Different Media



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Data Storage on Different Media

Every organization has some information needs. A library keeps a list of members, books, due dates, and fines. A company needs to save information about its employees, departments, and salaries. These pieces of information are called *data*.

Organizations can store data in various media and in different formats, such as a hard copy document in a filing cabinet, or data stored in electronic spreadsheets, or in databases.

A *database* is an organized collection of information.

To manage databases, you need a database management system (DBMS). A DBMS is a program that stores, retrieves, and modifies data in databases on request. There are four main types of databases: *hierarchical*, *network*, *relational*, and (most recently) *object relational*.

# Relational Database Concept

- Dr. E. F. Codd proposed the relational model for database systems in 1970.
- It is the basis for the relational database management system (RDBMS).
- The relational model consists of the following:
  - Collection of objects or relations
  - Set of operators to act on the relations
  - Data integrity for accuracy and consistency

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Relational Database Concept

The principles of the relational model were first outlined by Dr. E. F. Codd in a June 1970 paper titled “A Relational Model of Data for Large Shared Data Banks.” In this paper, Dr. Codd proposed the relational model for database systems.

The common models used at that time were hierarchical and network, or even simple flat-file data structures. Relational database management systems (RDBMS) soon became very popular, especially for their ease of use and flexibility in structure. In addition, a number of innovative vendors, such as Oracle, supplemented the RDBMS with a suite of powerful, application development and user-interface products, thereby providing a total solution.


### Components of the Relational Model

- Collections of objects or relations that store the data
- A set of operators that can act on the relations to produce other relations
- Data integrity for accuracy and consistency

For more information, see *An Introduction to Database Systems, Eighth Edition* (Addison-Wesley: 2004), written by Chris Date.

## Definition of a Relational Database

A relational database is a collection of relations or two-dimensional tables.



ORACLE


Copyright © 2009, Oracle. All rights reserved.

### Definition of a Relational Database

A relational database uses relations or two-dimensional tables to store information.

For example, you might want to store information about all the employees in your company. In a relational database, you create several tables to store different pieces of information about your employees, such as an employee table, a department table, and a salary table.

# Data Models



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Data Models

Models are the cornerstone of design. Engineers build a model of a car to work out any details before putting it into production. In the same manner, system designers develop models to explore ideas and improve the understanding of database design.

### Purpose of Models


Models help communicate the concepts that are in people's minds. They can be used to do the following:

- Communicate
- Categorize
- Describe
- Specify
- Investigate
- Evolve
- Analyze
- Imitate

The objective is to produce a model that fits a multitude of these uses, can be understood by an end user, and contains sufficient detail for a developer to build a database system.

# Entity Relationship Model

- Create an entity relationship diagram from business specifications or narratives:



- Scenario:
  - “. . . Assign one or more employees to a department . . .”
  - “. . . Some departments do not yet have assigned employees . . .”

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Entity Relationship Model

In an effective system, data is divided into discrete categories or entities. An entity relationship (ER) model is an illustration of the various entities in a business and the relationships among them. An ER model is derived from business specifications or narratives and built during the analysis phase of the system development life cycle. ER models separate the information required by a business from the activities performed within the business. Although businesses can change their activities, the type of information tends to remain constant. Therefore, the data structures also tend to be constant.

## Entity Relationship Model (continued)

### Benefits of ER Modeling:

- Documents information for the organization in a clear, precise format
- Provides a clear picture of the scope of the information requirement
- Provides an easily understood pictorial map for database design
- Offers an effective framework for integrating multiple applications

### Key Components

- **Entity:** An aspect of significance about which information must be known. Examples are departments, employees, and orders.
- **Attribute:** Something that describes or qualifies an entity. For example, for the employee entity, the attributes would be the employee number, name, job title, hire date, department number, and so on. Each of the attributes is either required or optional. This state is called *optionality*.
- **Relationship:** A named association between entities showing optionality and degree. Examples are employees and departments, and orders and items

Oracle Internal & Oracle Academy  
Use Only


# Entity Relationship Modeling Conventions

## Entity:

- Singular, unique name
- Uppercase
- Soft box
- Synonym in parentheses

## Attribute:

- Singular name
- Lowercase
- Mandatory marked with “\*”
- Optional marked with “o”



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## ER Modeling Conventions

### Entities

To represent an entity in a model, use the following conventions:

- Singular, unique entity name
- Entity name in uppercase
- Soft box
- Optional synonym names in uppercase within parentheses: ( )

### Attributes

To represent an attribute in a model, use the following conventions:

- Singular name in lowercase
- Asterisk (\*) tag for mandatory attributes (that is, values that *must* be known)
- Letter “o” tag for optional attributes (that is, values that *may* be known)

### Relationships

Symbol	Description
Dashed line	Optional element indicating “maybe”
Solid line	Mandatory element indicating “must be”
Crow’s foot	Degree element indicating “one or more”
Single line	Degree element indicating “one and only one”

## ER Modeling Conventions (continued)

### Relationships

Each direction of the relationship contains:

- **A label:** for example, *taught by* or *assigned to*
- **An optionality:** either *must be* or *maybe*
- **A degree:** either *one and only one* or *one or more*

**Note:** The term *cardinality* is a synonym for the term *degree*.

Each source entity {may be | must be} in relation {one and only one | one or more} with the destination entity.

**Note:** The convention is to read clockwise.

### Unique Identifiers


A unique identifier (UID) is any combination of attributes or relationships, or both, that serves to distinguish occurrences of an entity. Each entity occurrence must be uniquely identifiable.

- Tag each attribute that is part of the UID with a hash sign “#”.
- Tag secondary UIDs with a hash sign in parentheses (#).

Oracle Internal & Oracle Academy  
Use Only

## Relating Multiple Tables

- Each row of data in a table is uniquely identified by a primary key.
- You can logically relate data from multiple tables using foreign keys.



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Relating Multiple Tables

Each table contains data that describes exactly one entity. For example, the EMPLOYEES table contains information about employees. Categories of data are listed across the top of each table, and individual cases are listed below. By using a table format, you can readily visualize, understand, and use information.

Because data about different entities is stored in different tables, you may need to combine two or more tables to answer a particular question. For example, you may want to know the location of the department where an employee works. In this scenario, you need information from the EMPLOYEES table (which contains data about employees) and the DEPARTMENTS table (which contains information about departments). With an RDBMS, you can relate the data in one table to the data in another by using the foreign keys. A foreign key is a column (or a set of columns) that refers to a primary key in the same table or another table.

You can use the ability to relate data in one table to data in another to organize information in separate, manageable units. Employee data can be kept logically distinct from the department data by storing it in a separate table.

## Relating Multiple Tables (continued)

### Guidelines for Primary Keys and Foreign Keys

- You cannot use duplicate values in a primary key.
- Primary keys generally cannot be changed.
- Foreign keys are based on data values and are purely logical (not physical) pointers.
- A foreign key value must match an existing primary key value or unique key value, otherwise it must be null.
- A foreign key must reference either a primary key or a unique key column.

Oracle Internal & Oracle Academy  
Use Only

# Relational Database Terminology

2	3	EMPLOYEE_ID	FIRST_NAME	LAST_NAME	SALARY	COMMISSION_PCT	DEPARTMENT_ID	4
		100	Steven	King	24000	(null)	90	
		101	Neena	Kochhar	17000	(null)	90	
		102	Lex	De Haan	17000	(null)	90	
		103	Alexander	Hunold	9000	(null)	60	
		104	Bruce	Ernst	6000	(null)	60	5
		107	Diana	Lorentz	4200	(null)	60	
		124	Kevin	Mourgos	5800	(null)	50	
		141	Trenna	Rajs	3500	(null)	50	6
		142	Curtis	Davies	3100	(null)	50	
		143	Randall	Matos	2600	(null)	50	
		144	Peter	Vargas	2500	(null)	50	
		149	Eleni	Zlotkey	10500	0.2	80	
		174	Ellen	Abel	11000	0.3	80	
		176	Jonathon	Taylor	8600	0.2	80	
		178	Kimberely	Grant	7000	0.15	(null)	
		200	Jennifer	Whalen	4400	(null)	10	
1		201	Michael	Hartstein	13000	(null)	20	
		202	Pat	Fay	6000	(null)	20	
		205	Shelley	Higgins	12000	(null)	110	
		206	William	Gietz	8300	(null)	110	

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Relational Database Terminology

A relational database can contain one or many tables. A *table* is the basic storage structure of an RDBMS. A table holds all the data necessary about something in the real world, such as employees, invoices, or customers.

The slide shows the contents of the *EMPLOYEES* table or *relation*. The numbers indicate the following:

1. A single *row* (or *tuple*) representing all the data required for a particular employee. Each row in a table should be identified by a primary key, which permits no duplicate rows. The order of rows is insignificant; specify the row order when the data is retrieved.
2. A *column* or attribute containing the employee number. The employee number identifies a *unique* employee in the *EMPLOYEES* table. In this example, the employee number column is designated as the *primary key*. A primary key must contain a value and the value must be unique.
3. A column that is not a key value. A column represents one kind of data in a table; in this example, the data is the salaries of all the employees. Column order is insignificant when storing data; specify the column order when the data is retrieved.

## Relational Database Terminology (continued)

4. A column containing the department number, which is also a *foreign key*. A foreign key is a column that defines how tables relate to each other. A foreign key refers to a primary key or a unique key in the same table or in another table. In the example, DEPARTMENT\_ID uniquely identifies a department in the DEPARTMENTS table.
5. A *field* can be found at the intersection of a row and a column. There can be only one value in it.
6. A field may have no value in it. This is called a null value. In the EMPLOYEES table, only those employees who have the role of sales representative have a value in the COMMISSION\_PCT (commission) field.

Oracle Internal & Oracle Academy  
Use Only

## Lesson Agenda

- Course objectives, course agenda, and appendixes used in this course
- Overview of Oracle Database 11g and related products
- Overview of relational database management concepts and terminologies
- **Introduction to SQL and its development environments**
- The HR schema and the tables used in this course
- Oracle Database 11g documentation and additional resources

ORACLE


Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Using SQL to Query Your Database

Structured query language (SQL) is:

- The ANSI standard language for operating relational databases
- Efficient, easy to learn, and use
- Functionally complete (With SQL, you can define, retrieve, and manipulate data in the tables.)



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using SQL to Query Your Database

In a relational database, you do not specify the access route to the tables, and you do not need to know how the data is arranged physically.

To access the database, you execute a structured query language (SQL) statement, which is the American National Standards Institute (ANSI) standard language for operating relational databases. SQL is a set of statements with which all programs and users access data in an Oracle database. Application programs and Oracle tools often allow users access to the database without using SQL directly, but these applications, in turn, must use SQL when executing the user's request.

SQL provides statements for a variety of tasks, including:

- Querying data
- Inserting, updating, and deleting rows in a table
- Creating, replacing, altering, and dropping objects
- Controlling access to the database and its objects
- Guaranteeing database consistency and integrity

SQL unifies all of the preceding tasks in one consistent language and enables you to work with data at a logical level.

# SQL Statements

SELECT INSERT UPDATE DELETE MERGE	Data manipulation language (DML)
CREATE ALTER DROP RENAME TRUNCATE COMMENT	Data definition language (DDL)
GRANT REVOKE	Data control language (DCL)
COMMIT ROLLBACK SAVEPOINT	Transaction control

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## SQL Statements


SQL statements supported by Oracle comply with industry standards. Oracle Corporation ensures future compliance with evolving standards by actively involving key personnel in SQL standards committees. The industry-accepted committees are ANSI and International Standards Organization (ISO). Both ANSI and ISO have accepted SQL as the standard language for relational databases.

Statement	Description
SELECT INSERT UPDATE DELETE MERGE	Retrieves data from the database, enters new rows, changes existing rows, and removes unwanted rows from tables in the database, respectively. Collectively known as <i>data manipulation language (DML)</i>
CREATE ALTER DROP RENAME TRUNCATE COMMENT	Sets up, changes, and removes data structures from tables. Collectively known as <i>data definition language (DDL)</i>
GRANT REVOKE	Provides or removes access rights to both the Oracle database and the structures within it
COMMIT ROLLBACK SAVEPOINT	Manages the changes made by DML statements. Changes to the data can be grouped together into logical transactions

# Development Environments for SQL

There are two development environments for this course:

- Primary tool is Oracle SQL Developer
- SQL\*Plus command line interface may also be used



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Development Environments for SQL

### SQL Developer

This course has been developed using Oracle SQL Developer as the tool for running the SQL statements discussed in the examples in the slide and the practices.

- SQL Developer version 1.2 is shipped with Oracle Database 11g, and is the default tool for this class.
- In addition, SQL Developer version 1.5.3 is also available on the classroom machine, and may be installed for use. At the time of publication for this course, version 1.5.3 was the latest release of SQL Developer.

### SQL\*Plus

The SQL\*Plus environment may also be used to run all SQL commands covered in this course.

### Note

- See Appendix E for information on using SQL Developer, including simple instructions on installing version 1.5.3.
- See Appendix D for information on using SQL\*Plus.

## Lesson Agenda


- Course objectives, course agenda, and appendixes used in this course
- Overview of Oracle Database 11g and related products
- Overview of relational database management concepts and terminologies
- Introduction to SQL and its development environments
- **The HR schema and the tables used in this course**
- Oracle Database 11g documentation and additional resources

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# The Human Resources (HR) Schema



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## The Human Resources (HR) Schema Description

The Human Resources (HR) schema is a part of the Oracle Sample Schemas that can be installed in an Oracle database. The practice sessions in this course use data from the HR schema.

### Table Descriptions

- REGIONS contains rows that represent a region such as America, Asia, and so on.
- COUNTRIES contains rows for countries, each of which is associated with a region.
- LOCATIONS contains the specific address of a specific office, warehouse, or production site of a company in a particular country.
- DEPARTMENTS shows details about the departments in which the employees work. Each department may have a relationship representing the department manager in the EMPLOYEES table.
- EMPLOYEES contains details about each employee working for a department. Some employees may not be assigned to any department.
- JOBS contains the job types that can be held by each employee.
- JOB\_HISTORY contains the job history of the employees. If an employee changes departments within a job or changes jobs within a department, then a new row is inserted into this table with the earlier job information of the employee.

# Tables Used in the Course

## EMPLOYEES

EMPLOYEE_ID	FIRST_NAME	LAST_NAME	SALARY	COMMISSION_PCT	DEPARTMENT_ID	EMAIL	PHONE_NUMBER	HIRE_DATE
100	Steven	King	24000	(null)	90	SKING	515.123.4567	17-JUN-87
101	Neena	Kochhar	17000	(null)	90	NKOCHHAR	515.123.4568	21-SEP-89
102	Lex	De Haan	17000	(null)	90	LDEHAAN	515.123.4569	13-JAN-93
103	Alexander	Hunold	9000	(null)	60	AHUNOLD	590.423.4567	03-JAN-90
104	Bruce	Ernst	6000	(null)	60	BERNST	590.423.4568	21-MAY-91
107	Diana	Lorentz	4200	(null)	60	DLORENTZ	590.423.5567	07-FEB-99
124	Kevin	Mourgos	5800	(null)	50	KMOURGOS	650.123.5234	16-NOV-99
141	Trenna	Rajs	3500	(null)	50	TRAJS	650.121.8009	17-OCT-95
142	Curtis	Davies	3100	(null)	50	CDAVIES	650.121.2994	29-JAN-97
50	RMATOS				50	RMATOS	650.121.2874	15-MAR-98

DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
10	Administration	200	1700
20	Marketing	201	1800
50	Shipping	124	1500
60	IT	103	1400
80	Sales	149	2500
90	Executive	100	1700
110	Accounting	205	1700
190	Contracting	(null)	1700

GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
A	1000	2999
B	3000	5999
C	6000	9999
D	10000	14999
E	15000	24999
F	25000	40000

## DEPARTMENTS

## JOB\_GRADES

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Tables Used in the Course

The following main tables are used in this course:

- EMPLOYEES table: Gives details of all the employees
- DEPARTMENTS table: Gives details of all the departments
- JOB\_GRADES table: Gives details of salaries for various grades

Apart from these tables, you will also use the other tables listed in the previous slide such as the LOCATIONS and the JOB\_HISTORY table.

**Note:** The structure and data for all the tables are provided in Appendix B.

## Lesson Agenda

- Course objectives, course agenda, and appendixes used in this course
- Overview of Oracle Database 11g and related products
- Overview of relational database management concepts and terminologies
- Introduction to SQL and its development environments
- The HR schema and the tables used in this course
- Oracle Database 11g documentation and additional resources

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Oracle Database 11g Documentation

- *Oracle Database New Features Guide 11g, Release 1 (11.1)*
- *Oracle Database Reference 11g, Release 1 (11.1)*
- *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*
- *Oracle Database Concepts 11g, Release 1 (11.1)*
- *Oracle Database SQL Developer User's Guide, Release 1.2*

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Oracle Database 11g Documentation

Navigate to <http://www.oracle.com/pls/db111/homepage> to access the Oracle Database 11g documentation library.

## Additional Resources

For additional information about the Oracle Database 11g, refer to the following:

- *Oracle Database 11g: New Features eStudies*
- *Oracle by Example series (OBE): Oracle Database 11g*
  - [http://www.oracle.com/technology/obe/11gr1\\_db/index.htm](http://www.oracle.com/technology/obe/11gr1_db/index.htm)

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Summary

In this lesson, you should have learned that:

- Oracle Database 11g extends:
  - The benefits of infrastructure grids
  - The existing information management capabilities
  - The capabilities to use the major application development environments such as PL/SQL, Java/JDBC, .NET, XML, and so on
- The database is based on ORDBMS
- Relational databases are composed of relations, managed by relational operations, and governed by data integrity constraints
- With the Oracle server, you can store and manage information by using SQL

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Summary

Relational database management systems are composed of objects or relations. They are managed by operations and governed by data integrity constraints.

Oracle Corporation produces products and services to meet your RDBMS needs. The main products are the following:

- Oracle Database 11g with which you store and manage information by using SQL
- Oracle Fusion Middleware with which you develop, deploy, and manage modular business services that can be integrated and reused
- Oracle Enterprise Manager Grid Control 10g, which you use to manage and automate administrative tasks across sets of systems in a grid environment

### SQL

The Oracle server supports ANSI-standard SQL and contains extensions. SQL is the language that is used to communicate with the server to access, manipulate, and control data.

## Practice I: Overview

This practice covers the following topics:

- Running the Oracle SQL Developer demo
- Starting Oracle SQL Developer, creating a new database connection, and browsing the HR tables

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice I: Overview

In this practice, you perform the following:

- Run through the Oracle SQL Developer demo.
- Use Oracle SQL Developer to examine data objects in the ORA account assigned to you. The ORA accounts contain the HR schema tables.

Note the following location for the lab files:

*D:\labs\SQL1\labs*

If you are asked to save any lab files, save them in this location.

In any practice, there may be exercises that are prefaced with the phrases “If you have time” or “If you want an extra challenge.” Work on these exercises only if you have completed all other exercises within the allocated time and would like a further challenge to your skills.

Perform the practices slowly and precisely. You can experiment with saving and running command files. If you have any questions at any time, ask your instructor.

**Note:** All written practices use Oracle SQL Developer as the development environment. Although it is recommended that you use Oracle SQL Developer, you can also use SQL\*Plus that is available in this course.

## Practice I

This is the first of many practices in this course. The solutions (if you require them) can be found in Appendix A. Practices are intended to cover most of the topics that are presented in the corresponding lesson.

### Run Through the Oracle SQL Developer Demo: Creating a Database Connection

1. Access the demo “Creating a database connection” at:  
[http://st-curriculum.oracle.com/tutorial/SQLDeveloper/html/module2/mod02\\_cp\\_newdbconn.htm](http://st-curriculum.oracle.com/tutorial/SQLDeveloper/html/module2/mod02_cp_newdbconn.htm)

### Starting Oracle SQL Developer

2. Start Oracle SQL Developer using the sqldeveloper desktop icon.

**Note:** When you start SQL Developer for the first time, you need to provide the path to the `java.exe` file. This is already done for you as a part of the classroom setup. In any case, if you are prompted, enter the following path:

D:\app\Administrator\product\11.1.0\client\_1\jdevstudio\jdk\bin

### Creating a New Oracle SQL Developer Database Connection

3. To create a new database connection, in the Connections Navigator, right-click Connections. Select New Connection from the menu. The New/Select Database Connection dialog box appears.
4. Create a database connection using the following information:
  - a. Connection Name: `myconnection`.
  - b. Username: `oraxx` where `xx` is the number of your PC (Ask your instructor to assign you one `ora` account out of the `ora1-ora20` range of accounts.).
  - c. Password: `oraxx`
  - d. Hostname: Enter the host name of the machine where your database server is running.
  - e. Port: 1521
  - f. SID: ORCL
  - g. Ensure that you select the Save Password check box.

## Practice I (continued)

### Testing and Connecting Using the Oracle SQL Developer Database Connection

5. Test the new connection.
6. If the status is Success, connect to the database using this new connection.

### Browsing the Tables in the Connections Navigator

7. In the Connections Navigator, view the objects available to you in the Tables node. Verify that the following tables are present:

COUNTRIES  
DEPARTMENTS  
EMPLOYEES  
JOB\_GRADES  
JOB\_HISTORY  
JOBS  
LOCATIONS  
REGIONS

8. Browse the structure of the EMPLOYEES table.
9. View the data of the DEPARTMENTS table.

### Opening a SQL Worksheet

10. Open a new SQL Worksheet. Examine the shortcut icons available for the SQL Worksheet.

Oracle Internal & Oracle Academy  
Use Only

# 1

## Retrieving Data Using the SQL `SELECT` Statement

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- List the capabilities of SQL `SELECT` statements
- Execute a basic `SELECT` statement

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

To extract data from the database, you need to use the SQL `SELECT` statement. However, you may need to restrict the columns that are displayed. This lesson describes all the SQL statements that are needed to perform these actions. Further, you may want to create `SELECT` statements that can be used more than once.

## Lesson Agenda

- **Basic SELECT statement**
- Arithmetic expressions and NULL values in the SELECT statement
- Column aliases
- Use of concatenation operator, literal character strings, alternative quote operator, and the DISTINCT keyword
- DESCRIBE command

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Capabilities of SQL SELECT Statements

### Projection





Table 1

### Selection





Table 1





Table 1

Join





Table 2

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Capabilities of SQL SELECT Statements

A `SELECT` statement retrieves information from the database. With a `SELECT` statement, you can use the following capabilities:

- **Projection:** Select the columns in a table that are returned by a query. Select as few or as many of the columns as required.
- **Selection:** Select the rows in a table that are returned by a query. Various criteria can be used to restrict the rows that are retrieved.
- **Joining:** Bring together data that is stored in different tables by specifying the link between them. SQL joins are covered in more detail in the lesson titled “Displaying Data from Multiple Tables.”

# Basic SELECT Statement

```
SELECT * | { [DISTINCT] column | expression [alias], ... }  
FROM table;
```

- SELECT identifies the columns to be displayed.
- FROM identifies the table containing those columns.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Basic SELECT Statement

In its simplest form, a SELECT statement must include the following:

- A SELECT clause, which specifies the columns to be displayed
- A FROM clause, which identifies the table containing the columns that are listed in the SELECT clause

In the syntax:

SELECT	is a list of one or more columns
*	selects all columns
DISTINCT	suppresses duplicates
<i>column/expression</i>	selects the named column or the expression
<i>alias</i>	gives the selected columns different headings
FROM <i>table</i>	specifies the table containing the columns

**Note:** Throughout this course, the words *keyword*, *clause*, and *statement* are used as follows:

- A *keyword* refers to an individual SQL element.  
For example, SELECT and FROM are keywords.
- A *clause* is a part of a SQL statement.  
For example, SELECT employee\_id, last\_name, and so on is a clause.
- A *statement* is a combination of two or more clauses.  
For example, SELECT \* FROM employees is a SQL statement.

# Selecting All Columns

```
SELECT *  
FROM departments;
```

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	10	Administration	200	1700
2	20	Marketing	201	1800
3	50	Shipping	124	1500
4	60	IT	103	1400
5	80	Sales	149	2500
6	90	Executive	100	1700
7	110	Accounting	205	1700
8	190	Contracting	(null)	1700

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Selecting All Columns

You can display all columns of data in a table by following the `SELECT` keyword with an asterisk (\*). In the example in the slide, the department table contains four columns: `DEPARTMENT_ID`, `DEPARTMENT_NAME`, `MANAGER_ID`, and `LOCATION_ID`. The table contains eight rows, one for each department.

You can also display all columns in the table by listing all the columns after the `SELECT` keyword. For example, the following SQL statement (like the example in the slide) displays all columns and all rows of the `DEPARTMENTS` table:

```
SELECT department_id, department_name, manager_id, location_id  
FROM departments;
```

**Note:** In SQL Developer, you can enter your SQL statement in a SQL Worksheet and click the “Execute Statement” icon or press [F9] to execute the statement. The output displayed in the Results tabbed page appears as shown in the slide.

## Selecting Specific Columns

```
SELECT department_id, location_id
FROM departments;
```

	DEPARTMENT_ID	LOCATION_ID
1	10	1700
2	20	1800
3	50	1500
4	60	1400
5	80	2500
6	90	1700
7	110	1700
8	190	1700

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Selecting Specific Columns

You can use the `SELECT` statement to display specific columns of the table by specifying the column names, separated by commas. The example in the slide displays all the department numbers and location numbers from the `DEPARTMENTS` table.

In the `SELECT` clause, specify the columns that you want in the order in which you want them to appear in the output. For example, to display location before department number (from left to right), you use the following statement:

```
SELECT location_id, department_id
FROM departments;
```

	LOCATION_ID	DEPARTMENT_ID
1	1700	10
2	1800	20
3	1500	50
4	1400	60

...

## Writing SQL Statements

- SQL statements are not case-sensitive.
- SQL statements can be entered on one or more lines.
- Keywords cannot be abbreviated or split across lines.
- Clauses are usually placed on separate lines.
- Indents are used to enhance readability.
- In SQL Developer, SQL statements can optionally be terminated by a semicolon (;). Semicolons are required when you execute multiple SQL statements.
- In SQL\*Plus, you are required to end each SQL statement with a semicolon (;).

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Writing SQL Statements

By using the following simple rules and guidelines, you can construct valid statements that are both easy to read and edit:

- SQL statements are not case-sensitive (unless indicated).
- SQL statements can be entered on one or many lines.
- Keywords cannot be split across lines or abbreviated.
- Clauses are usually placed on separate lines for readability and ease of editing.
- Indents should be used to make code more readable.
- Keywords typically are entered in uppercase; all other words, such as table names and column names are entered in lowercase.

### Executing SQL Statements

In SQL Developer, click the Run Script icon or press [F5] to run the command or commands in the SQL Worksheet. You can also click the Execute Statement icon or press [F9] to run a SQL statement in the SQL Worksheet. The Execute Statement icon executes the statement at the mouse pointer in the Enter SQL Statement box while the Run Script icon executes all the statements in the Enter SQL Statement box. The Execute Statement icon displays the output of the query on the Results tabbed page while the Run Script icon emulates the SQL\*Plus display and shows the output on the Script Output tabbed page.

In SQL\*Plus, terminate the SQL statement with a semicolon, and then press [Enter] to run the command.

## Column Heading Defaults

- SQL Developer:
  - Default heading alignment: Left-aligned
  - Default heading display: Uppercase
- SQL\*Plus:
  - Character and Date column headings are left-aligned.
  - Number column headings are right-aligned.
  - Default heading display: Uppercase

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Column Heading Defaults

In SQL Developer, column headings are displayed in uppercase and are left-aligned.

```
SELECT last_name, hire_date, salary
FROM employees;
```

	LAST_NAME	HIRE_DATE	SALARY
1	King	17-JUN-87	24000
2	Kochhar	21-SEP-89	17000
3	De Haan	13-JAN-93	17000
4	Hunold	03-JAN-90	9000
5	Ernst	21-MAY-91	6000
6	Lorentz	07-FEB-99	4200
7	Mourgos	16-NOV-99	5800
8	Rajs	17-OCT-95	3500

...

You can override the column heading display with an alias. Column aliases are covered later in this lesson.

## Lesson Agenda

- Basic `SELECT` statement
- Arithmetic expressions and `NULL` values in the `SELECT` statement
- Column Aliases
- Use of concatenation operator, literal character strings, alternative quote operator, and the `DISTINCT` keyword
- `DESCRIBE` command

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Arithmetic Expressions

Create expressions with number and date data by using arithmetic operators.

Operator	Description
+	Add
-	Subtract
*	Multiply
/	Divide

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Arithmetic Expressions

You may need to modify the way in which data is displayed, or you may want to perform calculations, or look at what-if scenarios. All these are possible using arithmetic expressions. An arithmetic expression can contain column names, constant numeric values, and the arithmetic operators.

### Arithmetic Operators

The slide lists the arithmetic operators that are available in SQL. You can use arithmetic operators in any clause of a SQL statement (except the FROM clause).

**Note:** With the DATE and TIMESTAMP data types, you can use the addition and subtraction operators only.

# Using Arithmetic Operators

```
SELECT last_name, salary, salary + 300
FROM employees;
```

	LAST_NAME	SALARY	SALARY+300
1	King	24000	24300
2	Kochhar	17000	17300
3	De Haan	17000	17300
4	Hunold	9000	9300
5	Ernst	6000	6300
6	Lorentz	4200	4500
7	Mourgos	5800	6100
8	Rajs	3500	3800
9	Davies	3100	3400
10	Matos	2600	2900

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using Arithmetic Operators

The example in the slide uses the addition operator to calculate a salary increase of \$300 for all employees. The slide also displays a `SALARY+300` column in the output.

Note that the resultant calculated column, `SALARY+300`, is not a new column in the `EMPLOYEES` table; it is for display only. By default, the name of a new column comes from the calculation that generated it—in this case, `salary+300`.

**Note:** The Oracle server ignores blank spaces before and after the arithmetic operator.

## Operator Precedence

If an arithmetic expression contains more than one operator, multiplication and division are evaluated first. If operators in an expression are of the same priority, then evaluation is done from left to right.

You can use parentheses to force the expression that is enclosed by the parentheses to be evaluated first.

### Rules of Precedence:

- Multiplication and division occur before addition and subtraction.
- Operators of the same priority are evaluated from left to right.
- Parentheses are used to override the default precedence or to clarify the statement.

# Operator Precedence

```
SELECT last_name, salary, 12*salary+100
FROM employees;
```

1

	LAST_NAME	SALARY	12*SALARY+100
1	King	24000	288100
2	Kochhar	17000	204100
3	De Haan	17000	204100

...

```
SELECT last_name, salary, 12*(salary+100)
FROM employees;
```

2

	LAST_NAME	SALARY	12*(SALARY+100)
1	King	24000	289200
2	Kochhar	17000	205200
3	De Haan	17000	205200

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Operator Precedence (continued)

The first example in the slide displays the last name, salary, and annual compensation of employees. It calculates the annual compensation by multiplying the monthly salary with 12, plus a one-time bonus of \$100. Note that multiplication is performed before addition.

**Note:** Use parentheses to reinforce the standard order of precedence and to improve clarity. For example, the expression in the slide can be written as  $(12 * \text{salary}) + 100$  with no change in the result.

## Using Parentheses

You can override the rules of precedence by using parentheses to specify the desired order in which the operators are to be executed.

The second example in the slide displays the last name, salary, and annual compensation of employees. It calculates the annual compensation as follows: adding a monthly bonus of \$100 to the monthly salary, and then multiplying that subtotal with 12. Because of the parentheses, addition takes priority over multiplication.

## Defining a Null Value

- Null is a value that is unavailable, unassigned, unknown, or inapplicable.
- Null is not the same as zero or a blank space.

```
SELECT last_name, job_id, salary, commission_pct  
FROM employees;
```

	LAST_NAME	JOB_ID	SALARY	COMMISSION_PCT
1	King	AD_PRES	24000	(null)
2	Kochhar	AD_VP	17000	(null)
...				
12	Zlotkey	SA_MAN	10500	0.2
13	Abel	SA_REP	11000	0.3
14	Taylor	SA_REP	8600	0.2
...				
19	Higgins	AC_MGR	12000	(null)
20	Gietz	AC_ACCOUNT	8300	(null)

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Defining a Null Value

If a row lacks a data value for a particular column, that value is said to be *null* or to contain a null.

Null is a value that is unavailable, unassigned, unknown, or inapplicable. Null is not the same as zero or a blank space. Zero is a number and blank space is a character.

Columns of any data type can contain nulls. However, some constraints (NOT NULL and PRIMARY KEY) prevent nulls from being used in the column.

In the COMMISSION\_PCT column in the EMPLOYEES table, notice that only a sales manager or sales representative can earn a commission. Other employees are not entitled to earn commissions. A null represents that fact.

**Note:** By default, SQL Developer uses the literal, (null), to identify null values. However, you can set it to something more relevant to you. To do so, select Preferences from the Tools menu. In the Preferences dialog box, expand the Database node. Click Advanced Parameters and on the right pane, for the “Display Null value As,” enter the appropriate value.

# Null Values in Arithmetic Expressions

Arithmetic expressions containing a null value evaluate to null.

```
SELECT last_name, 12*salary*commission_pct  
FROM employees;
```

	LAST_NAME	12*SALARY*COMMISSION_PCT
1	King	(null)
2	Kochhar	(null)
...		
12	Zlotkey	25200
13	Abel	39600
14	Taylor	20640
...		
19	Higgins	(null)
20	Gietz	(null)

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Null Values in Arithmetic Expressions

If any column value in an arithmetic expression is null, the result is null. For example, if you attempt to perform division by zero, you get an error. However, if you divide a number by null, the result is a null or unknown.

In the example in the slide, employee King does not get any commission. Because the `COMMISSION_PCT` column in the arithmetic expression is null, the result is null.

For more information, see the section on “Basic Elements of Oracle SQL” in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

## Lesson Agenda

- Basic `SELECT` statement
- Arithmetic expressions and `NULL` values in the `SELECT` statement
- **Column aliases**
- Use of concatenation operator, literal character strings, alternative quote operator, and the `DISTINCT` keyword
- `DESCRIBE` command

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Defining a Column Alias

A column alias:

- Renames a column heading
- Is useful with calculations
- Immediately follows the column name (There can also be the optional `AS` keyword between the column name and alias.)
- Requires double quotation marks if it contains spaces or special characters, or if it is case-sensitive

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Defining a Column Alias

When displaying the result of a query, SQL Developer normally uses the name of the selected column as the column heading. This heading may not be descriptive and, therefore, may be difficult to understand. You can change a column heading by using a column alias.

Specify the alias after the column in the `SELECT` list using blank space as a separator. By default, alias headings appear in uppercase. If the alias contains spaces or special characters (such as `#` or `$`), or if it is case-sensitive, enclose the alias in double quotation marks (“ ”).

## Using Column Aliases

```
SELECT last_name AS name, commission_pct comm
FROM employees;
```

	NAME	COMM
1	King	(null)
2	Kochhar	(null)
3	De Haan	(null)

...

```
SELECT last_name "Name", salary*12 "Annual Salary"
FROM employees;
```

	Name	Annual Salary
1	King	288000
2	Kochhar	204000
3	De Haan	204000

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using Column Aliases

The first example displays the names and the commission percentages of all the employees. Note that the optional AS keyword has been used before the column alias name. The result of the query is the same whether the AS keyword is used or not. Also, note that the SQL statement has the column aliases, name and comm, in lowercase, whereas the result of the query displays the column headings in uppercase. As mentioned in the previous slide, column headings appear in uppercase by default.

The second example displays the last names and annual salaries of all the employees. Because Annual Salary contains a space, it has been enclosed in double quotation marks. Note that the column heading in the output is exactly the same as the column alias.

## Lesson Agenda

- Basic `SELECT` Statement
- Arithmetic Expressions and `NULL` values in `SELECT` statement
- Column Aliases
- Use of concatenation operator, literal character strings, alternative quote operator, and the `DISTINCT` keyword
- `DESCRIBE` command

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Concatenation Operator

A concatenation operator:

- Links columns or character strings to other columns
- Is represented by two vertical bars (||)
- Creates a resultant column that is a character expression

```
SELECT last_name || job_id AS "Employees"  
FROM employees;
```

Employees	
1	AbelSA_REP
2	DaviesST_CLERK
3	De HaanAD_VP
4	ErnstIT_PROG
5	FayMK_REP

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Concatenation Operator

You can link columns to other columns, arithmetic expressions, or constant values to create a character expression by using the concatenation operator (||). Columns on either side of the operator are combined to make a single output column.

In the example, LAST\_NAME and JOB\_ID are concatenated, and given the alias Employees. Note that the last name of the employee and the job code are combined to make a single output column.

The AS keyword before the alias name makes the SELECT clause easier to read.

### Null Values with the Concatenation Operator

If you concatenate a null value with a character string, the result is a character string. LAST\_NAME || NULL results in LAST\_NAME.

**Note:** You can also concatenate date expressions with other expressions or columns.

## Literal Character Strings

- A literal is a character, a number, or a date that is included in the `SELECT` statement.
- Date and character literal values must be enclosed within single quotation marks.
- Each character string is output once for each row returned.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Literal Character Strings

A literal is a character, a number, or a date that is included in the `SELECT` list. It is not a column name or a column alias. It is printed for each row returned. Literal strings of free-format text can be included in the query result and are treated the same as a column in the `SELECT` list.

Date and character literals *must* be enclosed within single quotation marks ( ' '); number literals need not be enclosed in a similar manner.

# Using Literal Character Strings

```
SELECT last_name || ' is a ' || job_id  
       AS "Employee Details"  
FROM   employees;
```

Employee Details
1 Abel is a SA_REP
2 Davies is a ST_CLERK
3 De Haan is a AD_VP
4 Ernst is a IT_PROG
5 Fay is a MK_REP
...
18 Vargas is a ST_CLERK
19 Whalen is a AD_ASST
20 Zlotkey is a SA_MAN

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using Literal Character Strings

The example in the slide displays the last names and job codes of all employees. The column has the heading Employee Details. Note the spaces between the single quotation marks in the SELECT statement. The spaces improve the readability of the output.

In the following example, the last name and salary for each employee are concatenated with a literal, to give the returned rows more meaning:

```
SELECT last_name || ': 1 Month salary = ' || salary Monthly  
FROM   employees;
```

MONTHLY
1 King: 1 Month salary = 24000
2 Kochhar: 1 Month salary = 17000
3 De Haan: 1 Month salary = 17000
4 Hunold: 1 Month salary = 9000
5 Ernst: 1 Month salary = 6000
6 Lorentz: 1 Month salary = 4200
7 Mourgos: 1 Month salary = 5800
8 Rajs: 1 Month salary = 3500

...

## Alternative Quote (q) Operator

- Specify your own quotation mark delimiter.
- Select any delimiter.
- Increase readability and usability.

```
SELECT department_name || q' [ Department's Manager Id: ] '  
      || manager_id  
      AS "Department and Manager"  
FROM departments;
```

	Department and Manager
1	Administration Department's Manager Id:200
2	Marketing Department's Manager Id:201
3	Shipping Department's Manager Id:124
4	IT Department's Manager Id:103
5	Sales Department's Manager Id:149
6	Executive Department's Manager Id:100
7	Accounting Department's Manager Id:205
8	Contracting Department's Manager Id:

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Alternative Quote (q) Operator

Many SQL statements use character literals in expressions or conditions. If the literal itself contains a single quotation mark, you can use the quote (q) operator and select your own quotation mark delimiter.

You can choose any convenient delimiter, single-byte or multibyte, or any of the following character pairs: [ ], { }, ( ), or <>.

In the example shown, the string contains a single quotation mark, which is normally interpreted as a delimiter of a character string. By using the q operator, however, brackets [] are used as the quotation mark delimiters. The string between the brackets delimiters is interpreted as a literal character string.

# Duplicate Rows

The default display of queries is all rows, including duplicate rows.

```
SELECT department_id  
FROM employees;
```

1

	DEPARTMENT_ID
1	90
2	90
3	90
4	60
5	60

...

```
SELECT DISTINCT department_id  
FROM employees;
```

2

	DEPARTMENT_ID	
1	(null)	
2	90	
3	20	
...	4	110

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Duplicate Rows

Unless you indicate otherwise, SQL displays the results of a query without eliminating the duplicate rows. The first example in the slide displays all the department numbers from the EMPLOYEES table. Note that the department numbers are repeated.

To eliminate duplicate rows in the result, include the DISTINCT keyword in the SELECT clause immediately after the SELECT keyword. In the second example in the slide, the EMPLOYEES table actually contains 20 rows, but there are only seven unique department numbers in the table.

You can specify multiple columns after the DISTINCT qualifier. The DISTINCT qualifier affects all the selected columns, and the result is every distinct combination of the columns.

```
SELECT DISTINCT department_id, job_id  
FROM employees;
```

	DEPARTMENT_ID	JOB_ID
1	110	AC_ACCOUNT
2	90	AD_VP
3	50	ST_CLERK
4	80	SA_REP
5	50	ST_MAN

...

## Lesson Agenda

- Basic `SELECT` statement
- Arithmetic expressions and `NULL` values in the `SELECT` statement
- Column aliases
- Use of concatenation operator, literal character strings, alternative quote operator, and the `DISTINCT` keyword
- `DESCRIBE` command

ORACLE


Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Displaying the Table Structure

- Use the `DESCRIBE` command to display the structure of a table.
- Or, select the table in the Connections tree and use the Columns tab to view the table structure.

```
DESC[RIBE] tablename
```



Column Name	Data Type	Nullable	Data Default	COLUMN ID	Primary Key	COMMENTS
DEPARTMENT_ID	NUMBER(4,0)	No	(null)	1	1	Primary key column of departments table
DEPARTMENT_N...	VARCHAR2(30 BYTE)	No	(null)	2		(null) A not null column that shows name of a
MANAGER_ID	NUMBER(6,0)	Yes	(null)	3		(null) Manager_id of a department. Foreign ke
LOCATION_ID	NUMBER(4,0)	Yes	(null)	4		(null) Location id where a department is locat

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Displaying the Table Structure

In SQL Developer, you can display the structure of a table by using the `DESCRIBE` command. The command displays the column names and the data types, and it shows you whether a column *must* contain data (that is, whether the column has a `NOT NULL` constraint).

In the syntax, *table name* is the name of any existing table, view, or synonym that is accessible to the user.

Using the SQL Developer GUI interface, you can select the table in the Connections tree and use the Columns tab to view the table structure.

**Note:** The `DESCRIBE` command is supported by both SQL\*Plus and SQL Developer.

# Using the DESCRIBE Command

```
DESCRIBE employees
```

```
DESCRIBE employees
Name                               Null    Type
-----
EMPLOYEE_ID                        NOT NULL NUMBER(6)
FIRST_NAME                          VARCHAR2(20)
LAST_NAME                           NOT NULL VARCHAR2(25)
EMAIL                               NOT NULL VARCHAR2(25)
PHONE_NUMBER                        VARCHAR2(20)
HIRE_DATE                           NOT NULL DATE
JOB_ID                              NOT NULL VARCHAR2(10)
SALARY                              NUMBER(8,2)
COMMISSION_PCT                      NUMBER(2,2)
MANAGER_ID                          NUMBER(6)
DEPARTMENT_ID                       NUMBER(4)

11 rows selected
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the DESCRIBE Command

The example in the slide displays information about the structure of the EMPLOYEES table using the DESCRIBE command.

In the resulting display, *Null* indicates that the values for this column may be unknown. NOT NULL indicates that a column must contain data. *Type* displays the data type for a column.

The data types are described in the following table:

Data Type	Description
NUMBER ( <i>p</i> , <i>s</i> )	Number value having a maximum number of digits <i>p</i> , with <i>s</i> digits to the right of the decimal point
VARCHAR2 ( <i>s</i> )	Variable-length character value of maximum size <i>s</i>
DATE	Date and time value between January 1, 4712 B.C. and December 31, A.D. 9999.
CHAR ( <i>s</i> )	Fixed-length character value of size <i>s</i>

## Quiz

Identify the `SELECT` statements that execute successfully.

1.

```
SELECT first_name, last_name, job_id, salary*12
  AS Yearly Sal
FROM   employees;
```

2.

```
SELECT first_name, last_name, job_id, salary*12
  yearly sal
FROM   employees;
```

3.

```
SELECT first_name, last_name, job_id, salary AS
  yearly sal
FROM   employees;
```

4.

```
SELECT first_name+last_name AS name, job_Id,
  salary*12 yearly sal
FROM   employees;
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Answer: 2, 3

## Summary

In this lesson, you should have learned how to:

- Write a `SELECT` statement that:
  - Returns all rows and columns from a table
  - Returns specified columns from a table
  - Uses column aliases to display more descriptive column headings

```
SELECT * | { [DISTINCT] column / expression [alias], ... }  
FROM table;
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Summary

In this lesson, you should have learned how to retrieve data from a database table with the `SELECT` statement.

```
SELECT * | { [DISTINCT] column [alias], ... }  
FROM table;
```

In the syntax:

<code>SELECT</code>	is a list of one or more columns
<code>*</code>	selects all columns
<code>DISTINCT</code>	suppresses duplicates
<code>column / expression</code>	selects the named column or the expression
<code>alias</code>	gives the selected columns different headings
<code>FROM table</code>	specifies the table containing the columns

## Practice 1: Overview

This practice covers the following topics:

- Selecting all data from different tables
- Describing the structure of tables
- Performing arithmetic calculations and specifying column names

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice 1: Overview

In this practice, you write simple `SELECT` queries. The queries cover most of the `SELECT` clauses and operations that you learned in this lesson.

## Practice 1

### Part 1

Test your knowledge:

1. The following SELECT statement executes successfully:

```
SELECT last_name, job_id, salary AS Sal
FROM employees;
```

True/False

2. The following SELECT statement executes successfully:

```
SELECT *
FROM job_grades;
```

True/False

3. There are four coding errors in the following statement. Can you identify them?

```
SELECT      employee_id, last_name
sal x 12   ANNUAL SALARY
FROM        employees;
```

### Part 2

Note the following points before you begin with the practices:

- Save all your lab files at the following location: D:\labs\SQL1\labs
- Enter your SQL statements in a SQL Worksheet. To save a script in SQL Developer, make sure the required SQL worksheet is active and then from the File menu, select Save As or right-click in the SQL Worksheet and select Save file to save your SQL statement as a lab\_<lessonno>\_<stepno>.sql script. When you are modifying an existing script, make sure you use Save As to save it with a different filename.
- To run the query, click the Execute Statement icon in the SQL Worksheet. Alternatively, you can press [F9]. For DML and DDL statements, use the Run Script icon or press [F5].
- After you have executed the query, make sure that you do not enter your next query in the same worksheet. Open a new worksheet.

You have been hired as a SQL programmer for Acme Corporation. Your first task is to create some reports based on data from the Human Resources tables.

4. Your first task is to determine the structure of the DEPARTMENTS table and its contents.

```
DESCRIBE departments
Name                Null          Type
-----
DEPARTMENT_ID      NOT NULL     NUMBER(4)
DEPARTMENT_NAME     NOT NULL     VARCHAR2(30)
MANAGER_ID          NUMBER(6)
LOCATION_ID           NUMBER(4)
4 rows selected
```

## Practice 1 (continued)

### Part 2 (continued)

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	10	Administration	200	1700
2	20	Marketing	201	1800
3	50	Shipping	124	1500
4	60	IT	103	1400
5	80	Sales	149	2500
6	90	Executive	100	1700
7	110	Accounting	205	1700
8	190	Contracting	(null)	1700

```
5. DESCRIBE employees
Name                               Null    Type
-----
EMPLOYEE_ID                       NOT NULL NUMBER(6)
FIRST_NAME                          VARCHAR2(20)
LAST_NAME                           NOT NULL VARCHAR2(25)
EMAIL                               NOT NULL VARCHAR2(25)
PHONE_NUMBER                        VARCHAR2(20)
HIRE_DATE                           NOT NULL DATE
JOB_ID                              NOT NULL VARCHAR2(10)
SALARY                              NUMBER(8,2)
COMMISSION_PCT                      NUMBER(2,2)
MANAGER_ID                          NUMBER(6)
DEPARTMENT_ID                       NUMBER(4)

11 rows selected
```

The HR department wants a query to display the last name, job ID, hire date, and employee ID for each employee, with the employee ID appearing first. Provide an alias `STARTDATE` for the `HIRE_DATE` column. Save your SQL statement to a file named `lab_01_05.sql` so that you can dispatch this file to the HR department.

## Practice 1 (continued)

### Part 2 (continued)

6. Test your query in the lab\_01\_05.sql file to ensure that it runs correctly.

**Note:** After you have executed the query, make sure that you do not enter your next query in the same worksheet. Open a new worksheet.

	EMPLOYEE_ID	LAST_NAME	JOB_ID	STARTDATE
1	100	King	AD_PRES	17-JUN-87
2	101	Kochhar	AD_VP	21-SEP-89
3	102	De Haan	AD_VP	13-JAN-93
4	103	Hunold	IT_PROG	03-JAN-90
5	104	Ernst	IT_PROG	21-MAY-91
6	107	Lorentz	IT_PROG	07-FEB-99
7	124	Mourgos	ST_MAN	16-NOV-99
8	141	Rajs	ST_CLERK	17-OCT-95
9	142	Davies	ST_CLERK	29-JAN-97
10	143	Matos	ST_CLERK	15-MAR-98

...

19	205	Higgins	AC_MGR	07-JUN-94
20	206	Gietz	AC_ACCOUNT	07-JUN-94

7. The HR department wants a query to display all unique job IDs from the EMPLOYEES table.

	JOB_ID
1	AC_ACCOUNT
2	AC_MGR
3	AD_ASST
4	AD_PRES
5	AD_VP
6	IT_PROG
7	MK_MAN
8	MK_REP
9	SA_MAN
10	SA_REP
11	ST_CLERK
12	ST_MAN

## Practice 1 (continued)

### Part 3

If you have time, complete the following exercises:

- The HR department wants more descriptive column headings for its report on employees. Copy the statement from `lab_01_05.sql` to a new SQL Worksheet. Name the column headings `Emp #`, `Employee`, `Job`, and `Hire Date`, respectively. Then run your query again.

	Emp #	Employee	Job	Hire Date
1	100	King	AD_PRES	17-JUN-87
2	101	Kochhar	AD_VP	21-SEP-89
3	102	De Haan	AD_VP	13-JAN-93
4	103	Hunold	IT_PROG	03-JAN-90
5	104	Ernst	IT_PROG	21-MAY-91
6	107	Lorentz	IT_PROG	07-FEB-99
7	124	Mourgos	ST_MAN	16-NOV-99
8	141	Rajs	ST_CLERK	17-OCT-95
9	142	Davies	ST_CLERK	29-JAN-97
10	143	Matos	ST_CLERK	15-MAR-98

...

19	205	Higgins	AC_MGR	07-JUN-94
20	206	Gietz	AC_ACCOUNT	07-JUN-94

- The HR department has requested a report of all employees and their job IDs. Display the last name concatenated with the job ID (separated by a comma and space) and name the column `Employee and Title`.

	Employee and Title
1	Abel, SA_REP
2	Davies, ST_CLERK
3	De Haan, AD_VP
4	Ernst, IT_PROG
5	Fay, MK_REP
6	Gietz, AC_ACCOUNT
7	Grant, SA_REP
8	Hartstein, MK_MAN
9	Higgins, AC_MGR
10	Hunold, IT_PROG

...


19	Whalen, AD_ASST
20	Zlotkey, SA_MAN

## Practice 1 (continued)

### Part 3 (continued)

If you want an extra challenge, complete the following exercise:

10. To familiarize yourself with the data in the EMPLOYEES table, create a query to display all the data from that table. Separate each column output by a comma. Name the column title THE\_OUTPUT.



	THE_OUTPUT
1	100,Steven,King,SKING,515.123.4567,AD_PRES,,17-JUN-87,24000,,90
2	101,Neena,Kochhar,NKOCHHAR,515.123.4568,AD_VP,100,21-SEP-89,17000,,90
3	102,Lex,De Haan,LDEHAAN,515.123.4569,AD_VP,100,13-JAN-93,17000,,90
4	103,Alexander,Hunold,AHUNOLD,590.423.4567,IT_PROG,102,03-JAN-90,9000,,60
5	104,Bruce,Ernst,BERNST,590.423.4568,IT_PROG,103,21-MAY-91,6000,,60
6	107,Diana,Lorentz,DLORENTZ,590.423.5567,IT_PROG,103,07-FEB-99,4200,,60
7	124,Kevin,Mourgos,KMOURGOS,650.123.5234,ST_MAN,100,16-NOV-99,5800,,50
8	141,Trenna,Rajs,TRAJS,650.121.8009,ST_CLERK,124,17-OCT-95,3500,,50
9	142,Curtis,Davies,CDAVIES,650.121.2994,ST_CLERK,124,29-JAN-97,3100,,50
10	143,Randall,Matos,RMATOS,650.121.2874,ST_CLERK,124,15-MAR-98,2600,,50
...	
19	205,Shelley,Higgins,SHIGGINS,515.123.8080,AC_MGR,101,07-JUN-94,12000,,110
20	206,William,Gietz,WGIETZ,515.123.8181,AC_ACCOUNT,205,07-JUN-94,8300,,110



# 2

## Restricting and Sorting Data

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- Limit the rows that are retrieved by a query
- Sort the rows that are retrieved by a query
- Use ampersand substitution to restrict and sort output at run time

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

When retrieving data from the database, you may need to do the following:

- Restrict the rows of data that are displayed
- Specify the order in which the rows are displayed

This lesson explains the SQL statements that you use to perform the actions listed above.

## Lesson Agenda

- Limiting rows with:
  - The `WHERE` clause
  - The comparison conditions using `=`, `<=`, `BETWEEN`, `IN`, `LIKE`, and `NULL` conditions
  - Logical conditions using `AND`, `OR`, and `NOT` operators
- Rules of precedence for operators in an expression
- Sorting rows using the `ORDER BY` clause
- Substitution variables
- `DEFINE` and `VERIFY` commands

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Limiting Rows Using a Selection

## EMPLOYEES

EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	King	AD_PRES	90
2	Kochhar	AD_VP	90
3	De Haan	AD_VP	90
4	Hunold	IT_PROG	60
5	Ernst	IT_PROG	60
6	Lorentz	IT_PROG	60

...

“retrieve all employees in department 90”



EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	King	AD_PRES	90
2	Kochhar	AD_VP	90
3	De Haan	AD_VP	90

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Limiting Rows Using a Selection

In the example in the slide, assume that you want to display all the employees in department 90. The rows with a value of 90 in the DEPARTMENT\_ID column are the only ones that are returned. This method of restriction is the basis of the WHERE clause in SQL.

## Limiting the Rows That Are Selected

- Restrict the rows that are returned by using the `WHERE` clause:

```
SELECT * | { [DISTINCT] column/expression [alias], ... }  
FROM table  
[WHERE condition(s)];
```

- The `WHERE` clause follows the `FROM` clause.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Limiting the Rows That Are Selected

You can restrict the rows that are returned from the query by using the `WHERE` clause. A `WHERE` clause contains a condition that must be met and it directly follows the `FROM` clause. If the condition is true, the row meeting the condition is returned.

In the syntax:

`WHERE` restricts the query to rows that meet a condition

`condition` is composed of column names, expressions, constants, and a comparison operator. A condition specifies a combination of one or more expressions and logical (Boolean) operators, and returns a value of `TRUE`, `FALSE`, or `UNKNOWN`.

The `WHERE` clause can compare values in columns, literal, arithmetic expressions, or functions. It consists of three elements:

- Column name
- Comparison condition
- Column name, constant, or list of values

## Using the WHERE Clause

```
SELECT employee_id, last_name, job_id, department_id
FROM employees
WHERE department_id = 90 ;
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	King	AD_PRES	90
2	Kochhar	AD_VP	90
3	De Haan	AD_VP	90

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the WHERE Clause

In the example, the SELECT statement retrieves the employee ID, last name, job ID, and department number of all employees who are in department 90.

**Note:** You cannot use column alias in the WHERE clause.

## Character Strings and Dates

- Character strings and date values are enclosed with single quotation marks.
- Character values are case-sensitive and date values are format-sensitive.
- The default date display format is DD-MON-RR.

```
SELECT last_name, job_id, department_id
FROM employees
WHERE last_name = 'Whalen' ;
```

```
SELECT last_name
FROM employees
WHERE hire_date = '17-FEB-96' ;
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Character Strings and Dates

Character strings and dates in the WHERE clause must be enclosed with single quotation marks ( ' ' ). Number constants, however, should not be enclosed with single quotation marks.

All character searches are case-sensitive. In the following example, no rows are returned because the EMPLOYEES table stores all the last names in mixed case:

```
SELECT last_name, job_id, department_id
FROM employees
WHERE last_name = 'WHALEN' ;
```

Oracle databases store dates in an internal numeric format, representing the century, year, month, day, hours, minutes, and seconds. The default date display is in the DD-MON-RR format.

**Note:** For details about the RR format and about changing the default date format, see the lesson titled “Using Single-Row Functions to Customize Output.” Also, you learn about the use of single-row functions such as UPPER and LOWER to override the case sensitivity in the same lesson.

# Comparison Operators

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<>	Not equal to
BETWEEN ...AND...	Between two values (inclusive)
IN(set)	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null value

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Comparison Operators

Comparison operators are used in conditions that compare one expression to another value or expression. They are used in the WHERE clause in the following format:

### Syntax

```
... WHERE expr operator value
```

### Example

```
... WHERE hire_date = '01-JAN-95'  
... WHERE salary >= 6000  
... WHERE last_name = 'Smith'
```

An alias cannot be used in the WHERE clause.

**Note:** The symbols != and ^= can also represent the *not equal to* condition.

## Using Comparison Operators

```
SELECT last_name, salary
FROM employees
WHERE salary <= 3000 ;
```

	LAST_NAME	SALARY
1	Matos	2600
2	Vargas	2500

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using Comparison Operators

In the example, the `SELECT` statement retrieves the last name and salary from the `EMPLOYEES` table for any employee whose salary is less than or equal to \$3,000. Note that there is an explicit value supplied to the `WHERE` clause. The explicit value of 3000 is compared to the salary value in the `SALARY` column of the `EMPLOYEES` table.

## Range Conditions Using the BETWEEN Operator

Use the BETWEEN operator to display rows based on a range of values:

```
SELECT last_name, salary
FROM employees
WHERE salary BETWEEN 2500 AND 3500 ;
```

Lower limit      Upper limit

	LAST_NAME	SALARY
1	Rajs	3500
2	Davies	3100
3	Matos	2600
4	Vargas	2500

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Range Conditions Using the BETWEEN Operator

You can display rows based on a range of values using the BETWEEN operator. The range that you specify contains a lower limit and an upper limit.

The SELECT statement in the slide returns rows from the EMPLOYEES table for any employee whose salary is between \$2,500 and \$3,500.

Values that are specified with the BETWEEN operator are inclusive. However, you must specify the lower limit first.

You can also use the BETWEEN operator on character values:

```
SELECT last_name
FROM employees
WHERE last_name BETWEEN 'King' AND 'Smith';
```

	LAST_NAME
1	King
2	Kochhar
3	Lorentz
4	Matos
5	Mourgos
6	Rajs

## Membership Condition Using the IN Operator

Use the IN operator to test for values in a list:

```
SELECT employee_id, last_name, salary, manager_id
FROM   employees
WHERE  manager_id IN (100, 101, 201) ;
```

EMPLOYEE_ID	LAST_NAME	SALARY	MANAGER_ID
1	Kochhar	17000	100
2	De Haan	17000	100
3	Mourgos	5800	100
4	Zlotkey	10500	100
5	Hartstein	13000	100
6	Whalen	4400	101
7	Higgins	12000	101
8	Fay	6000	201

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Membership Condition Using the IN Operator

To test for values in a specified set of values, use the IN operator. The condition defined using the IN operator is also known as the *membership condition*.

The slide example displays employee numbers, last names, salaries, and managers' employee numbers for all the employees whose manager's employee number is 100, 101, or 201.

The IN operator can be used with any data type. The following example returns a row from the EMPLOYEES table, for any employee whose last name is included in the list of names in the WHERE clause:

```
SELECT employee_id, manager_id, department_id
FROM   employees
WHERE  last_name IN ('Hartstein', 'Vargas');
```

If characters or dates are used in the list, they must be enclosed with single quotation marks (' ').

**Note:** The IN operator is internally evaluated by the Oracle server as a set of OR conditions, such as a=value1 or a=value2 or a=value3. Therefore, using the IN operator has no performance benefits and is used only for logical simplicity.

## Pattern Matching Using the LIKE Operator

- Use the LIKE operator to perform wildcard searches of valid search string values.
- Search conditions can contain either literal characters or numbers:
  - % denotes zero or many characters.
  - \_ denotes one character.

```
SELECT first_name
FROM employees
WHERE first_name LIKE 'S%';
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Pattern Matching Using the LIKE Operator

You may not always know the exact value to search for. You can select rows that match a character pattern by using the LIKE operator. The character pattern–matching operation is referred to as a *wildcard* search. Two symbols can be used to construct the search string.

Symbol	Description
%	Represents any sequence of zero or more characters
_	Represents any single character

The SELECT statement in the slide returns the first name from the EMPLOYEES table for any employee whose first name begins with the letter “S.” Note the uppercase “S.” Consequently, names beginning with a lowercase “s” are not returned.

The LIKE operator can be used as a shortcut for some BETWEEN comparisons. The following example displays the last names and hire dates of all employees who joined between January, 1995 and December, 1995:

```
SELECT last_name, hire_date
FROM employees
WHERE hire_date LIKE '%95';
```

## Combining Wildcard Characters

- You can combine the two wildcard characters (% , \_) with literal characters for pattern matching:

```
SELECT last_name  
FROM employees  
WHERE last_name LIKE '_o%' ;
```

	LAST_NAME
1	Kochhar
2	Lorentz
3	Mourgos

- You can use the `ESCAPE` identifier to search for the actual % and \_ symbols.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Combining Wildcard Characters

The % and \_ symbols can be used in any combination with literal characters. The example in the slide displays the names of all employees whose last names have the letter “o” as the second character.

### ESCAPE Identifier

When you need to have an exact match for the actual % and \_ characters, use the `ESCAPE` identifier. This option specifies what the escape character is. If you want to search for strings that contain SA\_, you can use the following SQL statement:

```
SELECT employee_id, last_name, job_id  
FROM employees WHERE job_id LIKE '%SA\_%' ESCAPE '\\';
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID
1	149	Zlotkey	SA_MAN
2	174	Abel	SA_REP
3	176	Taylor	SA_REP
4	178	Grant	SA_REP

The `ESCAPE` identifier identifies the backslash (\) as the escape character. In the SQL statement, the escape character precedes the underscore (\_). This causes the Oracle server to interpret the underscore literally.

## Using the NULL Conditions

Test for nulls with the IS NULL operator.

```
SELECT last_name, manager_id
FROM employees
WHERE manager_id IS NULL ;
```

LAST_NAME	MANAGER_ID
1 King	(null)

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the NULL Conditions

The NULL conditions include the IS NULL condition and the IS NOT NULL condition.

The IS NULL condition tests for nulls. A null value means that the value is unavailable, unassigned, unknown, or inapplicable. Therefore, you cannot test with =, because a null cannot be equal or unequal to any value. The slide example retrieves the last names and managers of all employees who do not have a manager.

Here is another example: To display the last name, job ID, and commission for all employees who are *not* entitled to receive a commission, use the following SQL statement:

```
SELECT last_name, job_id, commission_pct
FROM employees
WHERE commission_pct IS NULL;
```

LAST_NAME	JOB_ID	COMMISSION_PCT
1 King	AD_PRES	(null)
2 Kochhar	AD_VP	(null)

...

15 Higgins	AC_MGR	(null)
16 Gietz	AC_ACCOUNT	(null)

## Defining Conditions Using the Logical Operators

Operator	Meaning
AND	Returns TRUE if <i>both</i> component conditions are true
OR	Returns TRUE if <i>either</i> component condition is true
NOT	Returns TRUE if the condition is false

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Defining Conditions Using the Logical Operators

A logical condition combines the result of two component conditions to produce a single result based on those conditions or it inverts the result of a single condition. A row is returned only if the overall result of the condition is true.

Three logical operators are available in SQL:

- AND
- OR
- NOT

All the examples so far have specified only one condition in the WHERE clause. You can use several conditions in a single WHERE clause using the AND and OR operators.

## Using the AND Operator

AND requires both the component conditions to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM employees
WHERE salary >= 10000
AND job_id LIKE '%MAN%';
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	149 Zlotkey	SA_MAN	10500
2	201 Hartstein	MK_MAN	13000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the AND Operator

In the example, both the component conditions must be true for any record to be selected. Therefore, only those employees who have a job title that contains the string 'MAN' and earn \$10,000 or more are selected.

All character searches are case-sensitive, that is no rows are returned if 'MAN' is not uppercase. Further, character strings must be enclosed with quotation marks.

#### AND Truth Table

The following table shows the results of combining two expressions with AND:

AND	TRUE	FALSE	NULL
TRUE	TRUE	FALSE	NULL
FALSE	FALSE	FALSE	FALSE
NULL	NULL	FALSE	NULL

## Using the OR Operator

OR requires either component condition to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM employees
WHERE salary >= 10000
OR job_id LIKE '%MAN%' ;
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	100	King	AD_PRES	24000
2	101	Kochhar	AD_VP	17000
3	102	De Haan	AD_VP	17000
4	124	Mourgos	ST_MAN	5800
5	149	Zlotkey	SA_MAN	10500
6	174	Abel	SA_REP	11000
7	201	Hartstein	MK_MAN	13000
8	205	Higgins	AC_MGR	12000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the OR Operator

In the example, either component condition can be true for any record to be selected. Therefore, any employee who has a job ID that contains the string 'MAN' or earns \$10,000 or more is selected.

#### OR Truth Table

The following table shows the results of combining two expressions with OR:

OR	TRUE	FALSE	NULL
TRUE	TRUE	TRUE	TRUE
FALSE	TRUE	FALSE	NULL
NULL	TRUE	NULL	NULL

## Using the NOT Operator

```
SELECT last_name, job_id
FROM   employees
WHERE  job_id
       NOT IN ('IT_PROG', 'ST_CLERK', 'SA_REP') ;
```

	LAST_NAME	JOB_ID
1	De Haan	AD_VP
2	Fay	MK_REP
3	Gietz	AC_ACCOUNT
4	Hartstein	MK_MAN
5	Higgins	AC_MGR
6	King	AD_PRES
7	Kochhar	AD_VP
8	Mourgos	ST_MAN
9	Whalen	AD_ASST
10	Zlotkey	SA_MAN

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the NOT Operator

The slide example displays the last name and job ID of all employees whose job ID *is not* IT\_PROG, ST\_CLERK, or SA\_REP.

#### NOT Truth Table

The following table shows the result of applying the NOT operator to a condition:

NOT	TRUE	FALSE	NULL
	FALSE	TRUE	NULL

**Note:** The NOT operator can also be used with other SQL operators, such as BETWEEN, LIKE, and NULL.

```
... WHERE job_id NOT IN ('AC_ACCOUNT', 'AD_VP')
... WHERE salary NOT BETWEEN 10000 AND 15000
... WHERE last_name NOT LIKE '%A%'
... WHERE commission_pct IS NOT NULL
```

## Lesson Agenda

- Limiting rows with:
  - The `WHERE` clause
  - The comparison conditions using `=`, `<=`, `BETWEEN`, `IN`, `LIKE`, and `NULL` operators
  - Logical conditions using `AND`, `OR`, and `NOT` operators
- Rules of precedence for operators in an expression
- Sorting rows using the `ORDER BY` clause
- Substitution variables
- `DEFINE` and `VERIFY` commands

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Rules of Precedence

Operator	Meaning
1	Arithmetic operators
2	Concatenation operator
3	Comparison conditions
4	IS [NOT] NULL, LIKE, [NOT] IN
5	[NOT] BETWEEN
6	Not equal to
7	NOT logical condition
8	AND logical condition
9	OR logical condition

**You can use parentheses to override rules of precedence.**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Rules of Precedence

The rules of precedence determine the order in which expressions are evaluated and calculated. The table in the slide lists the default order of precedence. However, you can override the default order by using parentheses around the expressions that you want to calculate first.

# Rules of Precedence

```
SELECT last_name, job_id, salary
FROM employees
WHERE job_id = 'SA_REP'
OR job_id = 'AD_PRES'
AND salary > 15000;
```

1

	LAST_NAME	JOB_ID	SALARY
1	King	AD_PRES	24000
2	Abel	SA_REP	11000
3	Taylor	SA_REP	8600
4	Grant	SA_REP	7000

```
SELECT last_name, job_id, salary
FROM employees
WHERE (job_id = 'SA_REP'
OR job_id = 'AD_PRES')
AND salary > 15000;
```

2

	LAST_NAME	JOB_ID	SALARY
1	King	AD_PRES	24000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Rules of Precedence (continued)

### 1. Precedence of the AND Operator: Example

In this example, there are two conditions:

- The first condition is that the job ID is AD\_PRES *and* the salary is greater than \$15,000.
- The second condition is that the job ID is SA\_REP.

Therefore, the SELECT statement reads as follows:

“Select the row if an employee is a president *and* earns more than \$15,000, *or* if the employee is a sales representative.”

### 2. Using Parentheses: Example

In this example, there are two conditions:

- The first condition is that the job ID is AD\_PRES *or* SA\_REP.
- The second condition is that the salary is greater than \$15,000.

Therefore, the SELECT statement reads as follows:

“Select the row if an employee is a president *or* a sales representative, *and* if the employee earns more than \$15,000.”

## Lesson Agenda

- Limiting rows with:
  - The `WHERE` clause
  - The comparison conditions using `=`, `<=`, `BETWEEN`, `IN`, `LIKE`, and `NULL` operators
  - Logical conditions using `AND`, `OR`, and `NOT` operators
- Rules of precedence for operators in an expression
- **Sorting rows using the `ORDER BY` clause**
- Substitution variables
- `DEFINE` and `VERIFY` commands

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Using the ORDER BY Clause

- Sort retrieved rows with the ORDER BY clause:
  - ASC: Ascending order, default
  - DESC: Descending order
- The ORDER BY clause comes last in the SELECT statement:

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY hire_date ;
```

	LAST_NAME	JOB_ID	DEPARTMENT_ID	HIRE_DATE
1	King	AD_PRES		90 17-JUN-87
2	Whalen	AD_ASST		10 17-SEP-87
3	Kochhar	AD_VP		90 21-SEP-89
4	Hunold	IT_PROG		60 03-JAN-90
5	Ernst	IT_PROG		60 21-MAY-91
6	De Haan	AD_VP		90 13-JAN-93

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the ORDER BY Clause

The order of rows that are returned in a query result is undefined. The ORDER BY clause can be used to sort the rows. However, if you use the ORDER BY clause, it must be the last clause of the SQL statement. Further, you can specify an expression, an alias, or a column position as the sort condition.

### Syntax

```
SELECT          expr
FROM            table
[WHERE         condition(s)]
[ORDER BY     {column, expr, numeric_position} [ASC|DESC]];
```

In the syntax:

ORDER BY specifies the order in which the retrieved rows are displayed  
ASC orders the rows in ascending order (this is the default order)  
DESC orders the rows in descending order

If the ORDER BY clause is not used, the sort order is undefined, and the Oracle server may not fetch rows in the same order for the same query twice. Use the ORDER BY clause to display the rows in a specific order.

**Note:** Use the keywords NULLS FIRST or NULLS LAST to specify whether returned rows containing null values should appear first or last in the ordering sequence.

# Sorting

- Sorting in descending order:

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY hire_date DESC ;
```

1

- Sorting by column alias:

```
SELECT employee_id, last_name, salary*12 annsal
FROM employees
ORDER BY annsal ;
```

2

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Sorting

The default sort order is ascending:

- Numeric values are displayed with the lowest values first (for example, 1 to 999).
- Date values are displayed with the earliest value first (for example, 01-JAN-92 before 01-JAN-95).
- Character values are displayed in the alphabetical order (for example, “A” first and “Z” last).
- Null values are displayed last for ascending sequences and first for descending sequences.
- You can also sort by a column that is not in the `SELECT` list.

### Examples:

1. To reverse the order in which the rows are displayed, specify the `DESC` keyword after the column name in the `ORDER BY` clause. The slide example sorts the result by the most recently hired employee.
2. You can also use a column alias in the `ORDER BY` clause. The slide example sorts the data by annual salary.

# Sorting

- Sorting by using the column's numeric position:

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY 3;
```

3

- Sorting by multiple columns:

```
SELECT last_name, department_id, salary
FROM employees
ORDER BY department_id, salary DESC;
```

4

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Sorting (continued)

### Examples:

3. You can sort query results by specifying the numeric position of the column in the SELECT clause. The slide example sorts the result by the `department_id` as this column is at the third position in the SELECT clause.
4. You can sort query results by more than one column. The sort limit is the number of columns in the given table. In the ORDER BY clause, specify the columns and separate the column names using commas. If you want to reverse the order of a column, specify DESC after its name.

## Lesson Agenda


- Limiting rows with:
  - The `WHERE` clause
  - The comparison conditions using `=`, `<=`, `BETWEEN`, `IN`, `LIKE`, and `NULL` operators
  - Logical conditions using `AND`, `OR`, and `NOT` operators
- Rules of precedence for operators in an expression
- Sorting rows using the `ORDER BY` clause
- **Substitution variables**
- `DEFINE` and `VERIFY` commands

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Substitution Variables



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Substitution Variables

So far, all the SQL statements were executed with predetermined columns, conditions and their values. Suppose that you want a query that lists the employees with various jobs and not just those whose `job_id` is `SA_REP`. You can edit the `WHERE` clause to provide a different value each time you run the command, but there is also an easier way.

By using a substitution variable in place of the exact values in the `WHERE` clause, you can run the same query for different values.

You can create reports that prompt users to supply their own values to restrict the range of data returned, by using substitution variables. You can embed *substitution variables* in a command file or in a single SQL statement. A variable can be thought of as a container in which values are temporarily stored. When the statement is run, the stored value is substituted.

# Substitution Variables

- Use substitution variables to:
  - Temporarily store values with single-ampersand (&) and double-ampersand (&&) substitution
- Use substitution variables to supplement the following:
  - WHERE conditions
  - ORDER BY clauses
  - Column expressions
  - Table names
  - Entire SELECT statements

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Substitution Variables (continued)

You can use single-ampersand (&) substitution variables to temporarily store values.

You can also predefine variables by using the DEFINE command. DEFINE creates and assigns a value to a variable.

### Restricted Ranges of Data: Examples

- Reporting figures only for the current quarter or specified date range
- Reporting on data relevant only to the user requesting the report
- Displaying personnel only within a given department

### Other Interactive Effects

Interactive effects are not restricted to direct user interaction with the WHERE clause. The same principles can also be used to achieve other goals, such as:


- Obtaining input values from a file rather than from a person
- Passing values from one SQL statement to another

**Note:** Both SQL Developer and SQL\* Plus support substitution variables and the DEFINE/UNDEFINE commands. Neither SQL Developer nor SQL\* Plus support validation checks (except for data type) on user input. If used in scripts that are deployed to users, substitution variables can be subverted for SQL injection attacks.

## Using the Single-Ampersand Substitution Variable

Use a variable prefixed with an ampersand (&) to prompt the user for a value:

```
SELECT employee_id, last_name, salary, department_id
FROM employees
WHERE employee_id = &employee_num ;
```



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the Single-Ampersand Substitution Variable


When running a report, users often want to restrict the data that is returned dynamically. SQL\*Plus or SQL Developer provides this flexibility with user variables. Use an ampersand (&) to identify each variable in your SQL statement. However, you do not need to define the value of each variable.

Notation	Description
<i>&amp;user_variable</i>	Indicates a variable in a SQL statement; if the variable does not exist, SQL*Plus or SQL Developer prompts the user for a value (the new variable is discarded after it is used.)

The example in the slide creates a SQL Developer substitution variable for an employee number. When the statement is executed, SQL Developer prompts the user for an employee number and then displays the employee number, last name, salary, and department number for that employee.

With the single ampersand, the user is prompted every time the command is executed if the variable does not exist.

## Using the Single-Ampersand Substitution Variable



	EMPLOYEE_ID	LAST_NAME	SALARY	DEPARTMENT_ID
1	101	Kochhar	17000	90

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the Single-Ampersand Substitution Variable (continued)


When SQL Developer detects that the SQL statement contains an ampersand, you are prompted to enter a value for the substitution variable that is named in the SQL statement.

After you enter a value and click the OK button, the results are displayed in the Results tab of your SQL Developer session.

## Character and Date Values with Substitution Variables

Use single quotation marks for date and character values:

```
SELECT last_name, department_id, salary*12
FROM employees
WHERE job_id = '&job_title' ;
```



	LAST_NAME	DEPARTMENT_ID	SALARY*12
1	Hunold	60	108000
2	Ernst	60	72000
3	Lorentz	60	50400

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Character and Date Values with Substitution Variables


In a WHERE clause, date and character values must be enclosed with single quotation marks. The same rule applies to the substitution variables.

Enclose the variable with single quotation marks within the SQL statement itself.

The slide shows a query to retrieve the employee names, department numbers, and annual salaries of all employees based on the job title value of the SQL Developer substitution variable.

## Specifying Column Names, Expressions, and Text

```
SELECT employee_id, last_name, job_id, &column_name  
FROM employees  
WHERE &condition  
ORDER BY &order_column ;
```



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Specifying Column Names, Expressions, and Text

You can use the substitution variables not only in the WHERE clause of a SQL statement, but also as substitution for column names, expressions, or text.

#### Example:

The slide example displays the employee number, last name, job title, and any other column that is specified by the user at run time, from the EMPLOYEES table. For each substitution variable in the SELECT statement, you are prompted to enter a value, and then click OK to proceed.


If you do not enter a value for the substitution variable, you get an error when you execute the preceding statement.

**Note:** A substitution variable can be used anywhere in the SELECT statement, except as the first word entered at the command prompt.

## Using the Double-Ampersand Substitution Variable

Use double ampersand (&&) if you want to reuse the variable value without prompting the user each time:

```
SELECT employee_id, last_name, job_id, &&column_name
FROM employees
ORDER BY &column_name ;
```



EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
1	200 Whalen	AD_ASST	10
2	201 Hartstein	MK_MAN	20
3	202 Fay	MK_REP	20

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the Double-Ampersand Substitution Variable

You can use the double-ampersand (&&) substitution variable if you want to reuse the variable value without prompting the user each time. The user sees the prompt for the value only once. In the example in the slide, the user is asked to give the value for the variable, `column_name`, only once. The value that is supplied by the user (`department_id`) is used for both display and ordering of data. If you run the query again, you will not be prompted for the value of the variable.

SQL Developer stores the value that is supplied by using the `DEFINE` command; it uses it again whenever you reference the variable name. After a user variable is in place, you need to use the `UNDEFINE` command to delete it:

```
UNDEFINE column_name
```

## Lesson Agenda

- Limiting rows with:
  - The `WHERE` clause
  - The comparison conditions using `=`, `<=`, `BETWEEN`, `IN`, `LIKE`, and `NULL` operators
  - Logical conditions using `AND`, `OR`, and `NOT` operators
- Rules of precedence for operators in an expression
- Sorting rows using the `ORDER BY` clause
- Substitution variables
- `DEFINE` and `VERIFY` commands

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Using the DEFINE Command

- Use the DEFINE command to create and assign a value to a variable.
- Use the UNDEFINE command to remove a variable.

```
DEFINE employee_num = 200

SELECT employee_id, last_name, salary, department_id
FROM employees
WHERE employee_id = &employee_num ;

UNDEFINE employee_num
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the DEFINE Command

The example shown creates a substitution variable for an employee number by using the DEFINE command. At run time, this displays the employee number, name, salary, and department number for that employee.

Because the variable is created using the SQL Developer DEFINE command, the user is not prompted to enter a value for the employee number. Instead, the defined variable value is automatically substituted in the SELECT statement.



The EMPLOYEE\_NUM substitution variable is present in the session until the user undefines it or exits the SQL Developer session.

## Using the VERIFY Command

Use the VERIFY command to toggle the display of the substitution variable, both before and after SQL Developer replaces substitution variables with values:

```
SET VERIFY ON
```

```
SELECT employee_id, last_name, salary  
FROM employees  
WHERE employee_id = &employee_num;
```



EMPLOYEE_ID	LAST_NAME	SALARY
200	Whalen	4400

1 rows selected

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the VERIFY Command

To confirm the changes in the SQL statement, use the VERIFY command. Setting SET VERIFY ON forces SQL Developer to display the text of a command after it replaces substitution variables with values. To see the VERIFY output, you should use the Run Script (F5) icon in the SQL Worksheet. SQL Developer displays the text of a command after it replaces substitution variables with values, in the Script Output tab as shown in the slide.

The example in the slide displays the new value of the EMPLOYEE\_ID column in the SQL statement followed by the output.

### SQL\*Plus System Variables

SQL\*Plus uses various system variables that control the working environment. One of the variables is VERIFY. To obtain a complete list of all the system variables, you can issue the SHOW ALL command on the SQL\*Plus command prompt.

## Quiz

Which of the following are valid operators for the WHERE clause?

1. >=
2. IS NULL
3. !=
4. IS LIKE
5. IN BETWEEN
6. <>

ORACLE

Copyright © 2009, Oracle. All rights reserved.

**Answer: 1, 2, 3, 6**

## Summary

In this lesson, you should have learned how to:

- Use the `WHERE` clause to restrict rows of output:
  - Use the comparison conditions
  - Use the `BETWEEN`, `IN`, `LIKE`, and `NULL` operators
  - Apply the logical `AND`, `OR`, and `NOT` operators
- Use the `ORDER BY` clause to sort rows of output:

```
SELECT *|{[DISTINCT] column/expression [alias],...}  
FROM   table  
[WHERE condition(s)]  
[ORDER BY {column, expr, alias} [ASC|DESC]] ;
```

- Use ampersand substitution to restrict and sort output at run time

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Summary

In this lesson, you should have learned about restricting and sorting rows that are returned by the `SELECT` statement. You should also have learned how to implement various operators and conditions.

By using the substitution variables, you can add flexibility to your SQL statements. This enables the queries to prompt for the filter condition for the rows during run time.

## Practice 2: Overview

This practice covers the following topics:

- Selecting data and changing the order of the rows that are displayed
- Restricting rows by using the `WHERE` clause
- Sorting rows by using the `ORDER BY` clause
- Using substitution variables to add flexibility to your `SQL SELECT` statements

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice 2: Overview

In this practice, you build more reports, including statements that use the `WHERE` clause and the `ORDER BY` clause. You make the `SQL` statements more reusable and generic by including the ampersand substitution.

## Practice 2

The HR department needs your assistance in creating some queries.

1. Because of budget issues, the HR department needs a report that displays the last name and salary of employees who earn more than \$12,000. Save your SQL statement as a file named `lab_02_01.sql`. Run your query.

	LAST_NAME	SALARY
1	King	24000
2	Kochhar	17000
3	De Haan	17000
4	Hartstein	13000

2. Open a new SQL Worksheet. Create a report that displays the last name and department number for employee number 176. Run the query.

	LAST_NAME	DEPARTMENT_ID
1	Taylor	80

3. The HR department needs to find high-salary and low-salary employees. Modify `lab_02_01.sql` to display the last name and salary for any employee whose salary is not in the range of \$5,000 to \$12,000. Save your SQL statement as `lab_02_03.sql`.

	LAST_NAME	SALARY
1	King	24000
2	Kochhar	17000
3	De Haan	17000
4	Lorentz	4200
5	Rajs	3500
6	Davies	3100
7	Matos	2600
8	Vargas	2500
9	Whalen	4400
10	Hartstein	13000

## Practice 2 (continued)

4. Create a report to display the last name, job ID, and hire date for employees with the last names of Matos and Taylor. Order the query in ascending order by the hire date.

	LAST_NAME	JOB_ID	HIRE_DATE
1	Matos	ST_CLERK	15-MAR-98
2	Taylor	SA_REP	24-MAR-98

5. Display the last name and department ID of all employees in departments 20 or 50 in ascending alphabetical order by name.

	LAST_NAME	DEPARTMENT_ID
1	Davies	50
2	Fay	20
3	Hartstein	20
4	Matos	50
5	Mourgos	50
6	Rajs	50
7	Vargas	50

6. Modify lab\_02\_03.sql to display the last name and salary of employees who earn between \$5,000 and \$12,000, and are in department 20 or 50. Label the columns Employee and Monthly Salary, respectively. Resave lab\_02\_03.sql as lab\_02\_06.sql. Run the statement in lab\_02\_06.sql.

	Employee	Monthly Salary
1	Fay	6000
2	Mourgos	5800

## Practice 2 (continued)

7. The HR department needs a report that displays the last name and hire date for all employees who were hired in 1994.

	LAST_NAME	HIRE_DATE
1	Higgins	07-JUN-94
2	Gietz	07-JUN-94

8. Create a report to display the last name and job title of all employees who do not have a manager.

	LAST_NAME	JOB_ID
1	King	AD_PRES

9. Create a report to display the last name, salary, and commission of all employees who earn commissions. Sort data in descending order of salary and commissions. Use the column's numeric position in the ORDER BY clause.

	LAST_NAME	SALARY	COMMISSION_PCT
1	Abel	11000	0.3
2	Zlotkey	10500	0.2
3	Taylor	8600	0.2
4	Grant	7000	0.15

10. Members of the HR department want to have more flexibility with the queries that you are writing. They would like a report that displays the last name and salary of employees who earn more than an amount that the user specifies after a prompt. Save this query to a file named lab\_02\_10.sql. If you enter 12000 when prompted, the report displays the following results:

	LAST_NAME	SALARY
1	King	24000
2	Kochhar	17000
3	De Haan	17000
4	Hartstein	13000

## Practice 2 (continued)

11. The HR department wants to run reports based on a manager. Create a query that prompts the user for a manager ID and generates the employee ID, last name, salary, and department for that manager's employees. The HR department wants the ability to sort the report on a selected column. You can test the data with the following values:

manager\_id = 103, sorted by last\_name:

	EMPLOYEE_ID	LAST_NAME	SALARY	DEPARTMENT_ID
1	104	Ernst	6000	60
2	107	Lorentz	4200	60

manager\_id = 201, sorted by salary:

	EMPLOYEE_ID	LAST_NAME	SALARY	DEPARTMENT_ID
1	202	Fay	6000	20

manager\_id = 124, sorted by employee\_id:

	EMPLOYEE_ID	LAST_NAME	SALARY	DEPARTMENT_ID
1	141	Rajs	3500	50
2	142	Davies	3100	50
3	143	Matos	2600	50
4	144	Vargas	2500	50

## Practice 2 (continued)

If you have time, complete the following exercises:

12. Display all employee last names in which the third letter of the name is “a.”

	LAST_NAME
1	Grant
2	Whalen

13. Display the last names of all employees who have both an “a” and an “e” in their last name.

	LAST_NAME
1	Davies
2	De Haan
3	Hartstein
4	Whalen

If you want an extra challenge, complete the following exercises:

14. Display the last name, job, and salary for all employees whose jobs are either those of a sales representative or of a stock clerk, and whose salaries are not equal to \$2,500, \$3,500, or \$7,000.

	LAST_NAME	JOB_ID	SALARY
1	Abel	SA_REP	11000
2	Taylor	SA_REP	8600
3	Davies	ST_CLERK	3100
4	Matos	ST_CLERK	2600

15. Modify lab\_02\_06.sql to display the last name, salary, and commission for all employees whose commission is 20%. Resave lab\_02\_06.sql as lab\_02\_15.sql. Rerun the statement in lab\_02\_15.sql.

	Employee	Monthly Salary	COMMISSION_PCT
1	Zlotkey	10500	0.2
2	Taylor	8600	0.2

# 3

## Using Single-Row Functions to Customize Output

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- Describe various types of functions available in SQL
- Use character, number, and date functions in `SELECT` statements

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

Functions make the basic query block more powerful, and they are used to manipulate data values. This is the first of two lessons that explore functions. It focuses on single-row character, number, and date functions.

## Lesson Agenda


- Single-row SQL functions
- Character functions
- Number functions
- Working with dates
- Date functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# SQL Functions



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## SQL Functions


Functions are a very powerful feature of SQL. They can be used to do the following:

- Perform calculations on data
- Modify individual data items
- Manipulate output for groups of rows
- Format dates and numbers for display
- Convert column data types

SQL functions sometimes take arguments and always return a value.

**Note:** If you want to know whether a function is a SQL:2003 compliant function, refer to the *Oracle Compliance To Core SQL:2003* section in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

## Two Types of SQL Functions



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Two Types of SQL Functions

There are two types of functions:

- Single-row functions
- Multiple-row functions

#### Single-Row Functions

These functions operate on single rows only and return one result per row. There are different types of single-row functions. This lesson covers the following ones:

- Character
- Number
- Date
- Conversion
- General

#### Multiple-Row Functions

Functions can manipulate groups of rows to give one result per group of rows. These functions are also known as *group functions* (covered in lesson 5 titled “Reporting Aggregated Data Using the Group Functions”).

**Note:** For more information and a complete list of available functions and their syntax, see the topic, *Functions* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

# Single-Row Functions

Single-row functions:

- Manipulate data items
- Accept arguments and return one value
- Act on each row that is returned
- Return one result per row
- May modify the data type
- Can be nested
- Accept arguments that can be a column or an expression

```
function_name [(arg1, arg2,...)]
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Single-Row Functions

Single-row functions are used to manipulate data items. They accept one or more arguments and return one value for each row that is returned by the query. An argument can be one of the following:

- User-supplied constant
- Variable value
- Column name
- Expression

Features of single-row functions include:

- Acting on each row that is returned in the query
- Returning one result per row
- Possibly returning a data value of a different type than the one that is referenced
- Possibly expecting one or more arguments
- Can be used in SELECT, WHERE, and ORDER BY clauses; can be nested


In the syntax:

*function\_name*  
*arg1, arg2*

is the name of the function

is any argument to be used by the function. This can be represented by a column name or expression.

# Single-Row Functions



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Single-Row Functions (continued)

This lesson covers the following single-row functions:

- **Character functions:** Accept character input and can return both character and number values
- **Number functions:** Accept numeric input and return numeric values
- **Date functions:** Operate on values of the DATE data type (All date functions return a value of the DATE data type except the MONTHS BETWEEN function, which returns a number.)

The following single-row functions are discussed in the next lesson titled “Using Conversion Functions and Conditional Expressions”:

- **Conversion functions:** Convert a value from one data type to another
- **General functions:**
  - NVL
  - NVL2
  - NULLIF
  - COALESCE
  - CASE
  - DECODE

## Lesson Agenda


- Single-row SQL functions
- **Character functions**
- Number functions
- Working with dates
- Date functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Character Functions



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Character Functions

Single-row character functions accept character data as input and can return both character and numeric values. Character functions can be divided into the following:

- Case-conversion functions
- Character-manipulation functions

Function	Purpose
LOWER( <i>column</i> / <i>expression</i> )	Converts alpha character values to lowercase
UPPER( <i>column</i> / <i>expression</i> )	Converts alpha character values to uppercase
INITCAP( <i>column</i> / <i>expression</i> )	Converts alpha character values to uppercase for the first letter of each word; all other letters in lowercase
CONCAT( <i>column1</i> / <i>expression1</i> , <i>column2</i> / <i>expression2</i> )	Concatenates the first character value to the second character value; equivalent to concatenation operator (  )
SUBSTR( <i>column</i> / <i>expression</i> , <i>m</i> [ <i>,n</i> ])	Returns specified characters from character value starting at character position <i>m</i> , <i>n</i> characters long (If <i>m</i> is negative, the count starts from the end of the character value. If <i>n</i> is omitted, all characters to the end of the string are returned.)

**Note:** The functions discussed in this lesson are only some of the available functions.

## Character Functions (continued)

Function	Purpose
LENGTH( <i>column</i> / <i>expression</i> )	Returns the number of characters in the expression
INSTR( <i>column</i> / <i>expression</i> , ' <i>string</i> ', [ <i>m</i> ], [ <i>n</i> ])	Returns the numeric position of a named string. Optionally, you can provide a position <i>m</i> to start searching, and the occurrence <i>n</i> of the string. <i>m</i> and <i>n</i> default to 1, meaning start the search at the beginning of the string and report the first occurrence.
LPAD( <i>column</i>   <i>expression</i> , <i>n</i> , ' <i>string</i> ') RPAD( <i>column</i>   <i>expression</i> , <i>n</i> , ' <i>string</i> ')	Returns an expression left-padded to length of <i>n</i> characters with a character expression. Returns an expression right-padded to length of <i>n</i> characters with a character expression.
TRIM( <i>leading</i> / <i>trailing</i> / <i>both</i> , <i>trim_character</i> FROM <i>trim_source</i> )	Enables you to trim leading or trailing characters (or both) from a character string. If <i>trim_character</i> or <i>trim_source</i> is a character literal, you must enclose it in single quotation marks. This is a feature that is available in Oracle8i and later versions.
REPLACE( <i>text</i> , <i>search_string</i> , <i>replacement_string</i> )	Searches a text expression for a character string and, if found, replaces it with a specified replacement string

**Note:** Some of the functions that are fully or partially SQL:2003 compliant are:

UPPER

LOWER

TRIM

LENGTH

SUBSTR

INSTR

Refer to the *Oracle Compliance To Core SQL:2003* section in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)* for more information.

# Case-Conversion Functions

These functions convert the case for character strings:

Function	Result
LOWER('SQL Course')	sql course
UPPER('SQL Course')	SQL COURSE
INITCAP('SQL Course')	Sql Course

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Case-Conversion Functions

LOWER, UPPER, and INITCAP are the three case-conversion functions.

- LOWER: Converts mixed-case or uppercase character strings to lowercase
- UPPER: Converts mixed-case or lowercase character strings to uppercase
- INITCAP: Converts the first letter of each word to uppercase and the remaining letters to lowercase

```
SELECT 'The job id for '||UPPER(last_name)||' is '  
||LOWER(job_id) AS "EMPLOYEE DETAILS"  
FROM employees;
```

EMPLOYEE DETAILS
1 The job id for ABEL is sa_rep
2 The job id for DAVIES is st_clerk
3 The job id for DE HAAN is ad_vp
...
19 The job id for WHALEN is ad_asst
20 The job id for ZLOTKEY is sa_man

## Using Case-Conversion Functions

Display the employee number, name, and department number for employee Higgins:

```
SELECT employee_id, last_name, department_id
FROM employees
WHERE last_name = 'higgins';
```

0 rows selected

```
SELECT employee_id, last_name, department_id
FROM employees
WHERE LOWER(last_name) = 'higgins';
```

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
1	205 Higgins	110

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using Case-Conversion Functions

The slide example displays the employee number, name, and department number of employee Higgins.

The WHERE clause of the first SQL statement specifies the employee name as `higgins`. Because all the data in the `EMPLOYEES` table is stored in proper case, the name `higgins` does not find a match in the table, and no rows are selected.

The WHERE clause of the second SQL statement specifies that the employee name in the `EMPLOYEES` table is compared to `higgins`, converting the `LAST_NAME` column to lowercase for comparison purposes. Because both names are now lowercase, a match is found and one row is selected. The WHERE clause can be rewritten in the following manner to produce the same result:

```
...WHERE last_name = 'Higgins'
```

The name in the output appears as it was stored in the database. To display the name in uppercase, use the `UPPER` function in the `SELECT` statement.

```
SELECT employee_id, UPPER(last_name), department_id
FROM employees
WHERE INITCAP(last_name) = 'Higgins';
```

# Character-Manipulation Functions

These functions manipulate character strings:

Function	Result
CONCAT('Hello', 'World')	HelloWorld
SUBSTR('HelloWorld',1,5)	Hello
LENGTH('HelloWorld')	10
INSTR('HelloWorld', 'W')	6
LPAD(salary,10, '*')	*****24000
RPAD(salary, 10, '*')	24000*****
REPLACE ( 'JACK and JUE', 'J', 'BL')	BLACK and BLUE
TRIM('H' FROM 'HelloWorld')	elloWorld

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Character-Manipulation Functions


CONCAT, SUBSTR, LENGTH, INSTR, LPAD, RPAD, and TRIM are the character-manipulation functions that are covered in this lesson.

- CONCAT: Joins values together (You are limited to using two parameters with CONCAT.)
- SUBSTR: Extracts a string of determined length
- LENGTH: Shows the length of a string as a numeric value
- INSTR: Finds the numeric position of a named character
- LPAD: Returns an expression left-padded to the length of *n* characters with a character expression
- RPAD: Returns an expression right-padded to the length of *n* characters with a character expression
- TRIM: Trims leading or trailing characters (or both) from a character string (If *trim\_character* or *trim\_source* is a character literal, you must enclose it within single quotation marks.)


**Note:** You can use functions such as UPPER and LOWER with ampersand substitution. For example, use UPPER('&job\_title') so that the user does not have to enter the job title in a specific case.

# Using the Character-Manipulation Functions

```
SELECT employee_id, CONCAT(first_name, last_name) NAME,  
       job_id, LENGTH (last_name),  
       INSTR(last_name, 'a') "Contains 'a'?"  
FROM   employees  
WHERE  SUBSTR(job_id, 4) = 'REP';
```



EMPLOYEE_ID	NAME	JOB_ID	LENGTH(LAST_NAME)	Contains 'a'?
1	EllenAbel	SA_REP	4	0
2	JonathonTaylor	SA_REP	6	2
3	KimberelyGrant	SA_REP	5	3
4	PatFay	MK_REP	3	2



Copyright © 2009, Oracle. All rights reserved.

ORACLE

## Using the Character-Manipulation Functions

The slide example displays employee first names and last names joined together, the length of the employee last name, and the numeric position of the letter “a” in the employee last name for all employees who have the string, REP, contained in the job ID starting at the fourth position of the job ID.

### Example:

Modify the SQL statement in the slide to display the data for those employees whose last names end with the letter “n.”

```
SELECT employee_id, CONCAT(first_name, last_name) NAME,  
       LENGTH (last_name), INSTR(last_name, 'a') "Contains 'a'?"  
FROM   employees  
WHERE  SUBSTR(last_name, -1, 1) = 'n';
```

EMPLOYEE_ID	NAME	LENGTH(LAST_NAME)	Contains 'a'?
1	102 LexDe Haan	7	5
2	200 JenniferWhalen	6	3
3	201 MichaelHartstein	9	2

## Lesson Agenda

- Single-row SQL functions
- Character functions
- **Number functions**
- Working with dates
- Date Functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Number Functions

- ROUND: Rounds value to a specified decimal
- TRUNC: Truncates value to a specified decimal
- MOD: Returns remainder of division

Function	Result
ROUND (45.926, 2)	45.93
TRUNC (45.926, 2)	45.92
MOD (1600, 300)	100

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Number Functions


Number functions accept numeric input and return numeric values. This section describes some of the number functions.

Function	Purpose
ROUND ( <i>column</i>   <i>expression</i> , <i>n</i> )	Rounds the column, expression, or value to <i>n</i> decimal places or, if <i>n</i> is omitted, no decimal places (If <i>n</i> is negative, numbers to the left of decimal point are rounded.)
TRUNC ( <i>column</i>   <i>expression</i> , <i>n</i> )	Truncates the column, expression, or value to <i>n</i> decimal places or, if <i>n</i> is omitted, <i>n</i> defaults to zero
MOD ( <i>m</i> , <i>n</i> )	Returns the remainder of <i>m</i> divided by <i>n</i>

**Note:** This list contains only some of the available number functions.

For more information, see the section on *Numeric Functions* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

## Using the ROUND Function



DUAL is a dummy table that you can use to view results from functions and calculations.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the ROUND Function


The ROUND function rounds the column, expression, or value to  $n$  decimal places. If the second argument is 0 or is missing, the value is rounded to zero decimal places. If the second argument is 2, the value is rounded to two decimal places. Conversely, if the second argument is  $-2$ , the value is rounded to two decimal places to the left (rounded to the nearest unit of 100).

The ROUND function can also be used with date functions. You will see examples later in this lesson.

#### DUAL Table

The DUAL table is owned by the user SYS and can be accessed by all users. It contains one column, DUMMY, and one row with the value X. The DUAL table is useful when you want to return a value only once (for example, the value of a constant, pseudocolumn, or expression that is not derived from a table with user data). The DUAL table is generally used for completeness of the SELECT clause syntax, because both SELECT and FROM clauses are mandatory, and several calculations do not need to select from the actual tables.

## Using the TRUNC Function



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the TRUNC Function

The TRUNC function truncates the column, expression, or value to  $n$  decimal places.

The TRUNC function works with arguments similar to those of the ROUND function. If the second argument is 0 or is missing, the value is truncated to zero decimal places. If the second argument is 2, the value is truncated to two decimal places. Conversely, if the second argument is  $-2$ , the value is truncated to two decimal places to the left. If the second argument is  $-1$ , the value is truncated to one decimal place to the left.

Like the ROUND function, the TRUNC function can be used with date functions.

## Using the MOD Function

For all employees with the job title of Sales Representative, calculate the remainder of the salary after it is divided by 5,000.

```
SELECT last_name, salary, MOD(salary, 5000)
FROM employees
WHERE job_id = 'SA_REP';
```

	LAST_NAME	SALARY	MOD(SALARY,5000)
1	Abel	11000	1000
2	Taylor	8600	3600
3	Grant	7000	2000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the MOD Function

The MOD function finds the remainder of the first argument divided by the second argument. The slide example calculates the remainder of the salary after dividing it by 5,000 for all employees whose job ID is SA\_REP.

**Note:** The MOD function is often used to determine whether a value is odd or even.

## Lesson Agenda

- Single-row SQL functions
- Character functions
- Number functions
- **Working with dates**
- Date functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Working with Dates

- The Oracle database stores dates in an internal numeric format: century, year, month, day, hours, minutes, and seconds.
- The default date display format is DD-MON-RR.
  - Enables you to store 21st-century dates in the 20th century by specifying only the last two digits of the year
  - Enables you to store 20th-century dates in the 21st century in the same way

```
SELECT last_name, hire_date
FROM employees
WHERE hire_date < '01-FEB-88';
```

	LAST_NAME	HIRE_DATE
1	King	17-JUN-87
2	Whalen	17-SEP-87

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Working with Dates

The Oracle database stores dates in an internal numeric format, representing the century, year, month, day, hours, minutes, and seconds.

The default display and input format for any date is DD-MON-RR. Valid Oracle dates are between January 1, 4712 B.C., and December 31, 9999 A.D.

In the example in the slide, the HIRE\_DATE column output is displayed in the default format DD-MON-RR. However, dates are not stored in the database in this format. All the components of the date and time are stored. So, although a HIRE\_DATE such as 17-JUN-87 is displayed as day, month, and year, there is also *time* and *century* information associated with the date. The complete data might be June 17, 1987, 5:10:43 PM.

## RR Date Format

Current Year	Specified Date	RR Format	YY Format
1995	27-OCT-95	1995	1995
1995	27-OCT-17	2017	1917
2001	27-OCT-17	2017	2017
2001	27-OCT-95	1995	2095

		If the specified two-digit year is:	
		0–49	50–99
If two digits of the current year are:	0–49	The return date is in the current century	The return date is in the century before the current one
	50–99	The return date is in the century after the current one	The return date is in the current century

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### RR Date Format

The RR date format is similar to the YY element, but you can use it to specify different centuries. Use the RR date format element instead of YY so that the century of the return value varies according to the specified two-digit year and the last two digits of the current year. The table in the slide summarizes the behavior of the RR element.

Current Year	Given Date	Interpreted (RR)	Interpreted (YY)
1994	27-OCT-95	1995	1995
1994	27-OCT-17	2017	1917
2001	27-OCT-17	2017	2017

## RR Date Format (continued)

This data is stored internally as follows:

CENTURY	YEAR	MONTH	DAY	HOUR	MINUTE	SECOND
19	87	06	17	17	10	43

### Centuries and the Year 2000

When a record with a date column is inserted into a table, the *century* information is picked up from the `SYSDATE` function. However, when the date column is displayed on the screen, the century component is not displayed (by default).

The `DATE` data type uses 2 bytes for the year information, one for century and one for year. The century value is always included, whether or not it is specified or displayed. In this case, `RR` determines the default value for century on `INSERT`.

Oracle Internal & Oracle Academy  
Use Only

## Using the SYSDATE Function

SYSDATE is a function that returns:

- Date
- Time

```
SELECT sysdate
FROM dual;
```

	SYSDATE
1	31-MAY-07

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the SYSDATE Function

SYSDATE is a date function that returns the current database server date and time. You can use SYSDATE just as you would use any other column name. For example, you can display the current date by selecting SYSDATE from a table. It is customary to select SYSDATE from a dummy table called DUAL.

**Note:** SYSDATE returns the current date and time set for the operating system on which the database resides. Therefore, if you are in a place in Australia and connected to a remote database in a location in the United States (US), sysdate function will return the US date and time. In that case, you can use the CURRENT\_DATE function that returns the current date in the session time zone.

The CURRENT\_DATE function and other related time zone functions are discussed in detail in the course titled *Oracle Database 11g: SQL Fundamentals II*.

## Arithmetic with Dates

- Add or subtract a number to or from a date for a resultant date value.
- Subtract two dates to find the number of days between those dates.
- Add hours to a date by dividing the number of hours by 24.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Arithmetic with Dates

Because the database stores dates as numbers, you can perform calculations using arithmetic operators such as addition and subtraction. You can add and subtract number constants as well as dates.

You can perform the following operations:

Operation	Result	Description
date + number	Date	Adds a number of days to a date
date – number	Date	Subtracts a number of days from a date
date – date	Number of days	Subtracts one date from another
date + number/24	Date	Adds a number of hours to a date

## Using Arithmetic Operators with Dates

```
SELECT last_name, (SYSDATE-hire_date)/7 AS WEEKS
FROM employees
WHERE department_id = 90;
```

	LAST_NAME	WEEKS
1	King	1041.168239087301587301587301587301587302
2	Kochhar	923.025381944444444444444444444444444444
3	De Haan	750.168239087301587301587301587301587302

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using Arithmetic Operators with Dates

The example in the slide displays the last name and the number of weeks employed for all employees in department 90. It subtracts the date on which the employee was hired from the current date (SYSDATE) and divides the result by 7 to calculate the number of weeks that a worker has been employed.

**Note:** SYSDATE is a SQL function that returns the current date and time. Your results may differ depending on the date and time set for the operating system of your local database when you run the SQL query.

If a more current date is subtracted from an older date, the difference is a negative number.

## Lesson Agenda

- Single-row SQL functions
- Character functions
- Number functions
- Working with dates
- Date functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Date-Manipulation Functions

Function	Result
MONTHS_BETWEEN	Number of months between two dates
ADD_MONTHS	Add calendar months to date
NEXT_DAY	Next day of the date specified
LAST_DAY	Last day of the month
ROUND	Round date
TRUNC	Truncate date

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Date-Manipulation Functions

Date functions operate on Oracle dates. All date functions return a value of the DATE data type except MONTHS\_BETWEEN, which returns a numeric value.

- MONTHS\_BETWEEN(*date1*, *date2*): Finds the number of months between *date1* and *date2*. The result can be positive or negative. If *date1* is later than *date2*, the result is positive; if *date1* is earlier than *date2*, the result is negative. The noninteger part of the result represents a portion of the month.
- ADD\_MONTHS(*date*, *n*): Adds *n* number of calendar months to *date*. The value of *n* must be an integer and can be negative.
- NEXT\_DAY(*date*, '*char*') : Finds the date of the next specified day of the week ('*char*') following *date*. The value of *char* may be a number representing a day or a character string.
- LAST\_DAY(*date*): Finds the date of the last day of the month that contains *date*

The above list is a subset of the available date functions. ROUND and TRUNC number functions can also be used to manipulate the date values as shown below:

- ROUND(*date* [, '*fmt*']): Returns *date* rounded to the unit that is specified by the format model *fmt*. If the format model *fmt* is omitted, *date* is rounded to the nearest day.
- TRUNC(*date* [, '*fmt*']): Returns *date* with the time portion of the day truncated to the unit that is specified by the format model *fmt*. If the format model *fmt* is omitted, *date* is truncated to the nearest day.

The format models are covered in detail in the next lesson titled “Using Conversion Functions and Conditional Expressions.”

# Using Date Functions

Function	Result
MONTHS_BETWEEN ( '01-SEP-95 ' , '11-JAN-94 ' )	19.6774194
ADD_MONTHS ( '31-JAN-96 ' , 1 )	'29-FEB-96 '
NEXT_DAY ( '01-SEP-95 ' , 'FRIDAY' )	'08-SEP-95 '
LAST_DAY ( '01-FEB-95 ' )	'28-FEB-95 '

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using Date Functions

In the slide example, the ADD\_MONTHS function adds one month to the supplied date value, “31-JAN-96” and returns “29-FEB-96.” The function recognizes the year 1996 as the leap year and hence returns the last day of the February month. If you change the input date value to “31-JAN-95,” the function returns “28-FEB-95.”

For example, display the employee number, hire date, number of months employed, six-month review date, first Friday after hire date, and the last day of the hire month for all employees who have been employed for fewer than 100 months.

```
SELECT employee_id, hire_date,
       MONTHS_BETWEEN (SYSDATE, hire_date) TENURE,
       ADD_MONTHS (hire_date, 6) REVIEW,
       NEXT_DAY (hire_date, 'FRIDAY'), LAST_DAY(hire_date)
FROM   employees
WHERE  MONTHS_BETWEEN (SYSDATE, hire_date) < 100;
```

	EMPLOYEE_ID	HIRE_DATE	TENURE	REVIEW	NEXT_DAY(HIRE_DATE,'FRIDAY')	LAST_DAY(HIRE_DATE)
1	124	16-NOV-99	91.1099600...	16-MAY-00	19-NOV-99	30-NOV-99
2	149	29-JAN-00	88.6906052...	29-JUL-00	04-FEB-00	31-JAN-00
3	178	24-MAY-99	96.8518955...	24-NOV-99	28-MAY-99	31-MAY-99
4	99999	07-JUN-99	96.4002826...	07-DEC-99	11-JUN-99	30-JUN-99
5	113	11-JUN-07	0.25824335...	11-DEC-07	15-JUN-07	30-JUN-07

## Using ROUND and TRUNC Functions with Dates

Assume SYSDATE = '25-JUL-03':

Function	Result
ROUND(SYSDATE, 'MONTH')	01-AUG-03
ROUND(SYSDATE, 'YEAR')	01-JAN-04
TRUNC(SYSDATE, 'MONTH')	01-JUL-03
TRUNC(SYSDATE, 'YEAR')	01-JAN-03

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using ROUND and TRUNC Functions with Dates

The ROUND and TRUNC functions can be used for number and date values. When used with dates, these functions round or truncate to the specified format model. Therefore, you can round dates to the nearest year or month. If the format model is month, dates 1-15 result in the first day of the current month. Dates 16-31 result in the first day of the next month. If the format model is year, months 1-6 result in January 1 of the current year. Months 7-12 result in January 1 of the next year.

#### Example:

Compare the hire dates for all employees who started in 1997. Display the employee number, hire date, and starting month using the ROUND and TRUNC functions.

```
SELECT employee_id, hire_date,
       ROUND(hire_date, 'MONTH'), TRUNC(hire_date, 'MONTH')
FROM   employees
WHERE  hire_date LIKE '%97';
```

	EMPLOYEE_ID	HIRE_DATE	ROUND(HIRE_DATE,'MONTH')	TRUNC(HIRE_DATE,'MONTH')
1	142	29-JAN-97	01-FEB-97	01-JAN-97
2	202	17-AUG-97	01-SEP-97	01-AUG-97

## Quiz

Which of the following statements are true about single-row functions?

1. Manipulate data items
2. Accept arguments and return one value per argument
3. Act on each row that is returned
4. Return one result per set of rows
5. May not modify the data type
6. Can be nested
7. Accept arguments that can be a column or an expression

ORACLE

Copyright © 2009, Oracle. All rights reserved.

**Answer: 1, 3, 6, 7**

# Summary

In this lesson, you should have learned how to:

- Perform calculations on data using functions
- Modify individual data items using functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Summary

Single-row functions can be nested to any level. Single-row functions can manipulate the following:

- Character data: LOWER, UPPER, INITCAP, CONCAT, SUBSTR, INSTR, LENGTH
- Number data: ROUND, TRUNC, MOD
- Date values: SYSDATE, MONTHS\_BETWEEN, ADD\_MONTHS, NEXT\_DAY, LAST\_DAY

Remember the following:

- Date values can also use arithmetic operators.
- ROUND and TRUNC functions can also be used with date values.

## **SYSDATE and DUAL**

SYSDATE is a date function that returns the current date and time. It is customary to select SYSDATE from a dummy table called DUAL.

## Practice 3: Overview

This practice covers the following topics:

- Writing a query that displays the current date
- Creating queries that require the use of numeric, character, and date functions
- Performing calculations of years and months of service for an employee

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice 3: Overview

This practice provides a variety of exercises using different functions that are available for character, number, and date data types.

### Practice 3

#### Part 1

1. Write a query to display the system date. Label the column as Date.

**Note:** If your database is remotely located in a different time zone, the output will be the date for the operating system on which the database resides.

Date
1 31-MAY-07

2. The HR department needs a report to display the employee number, last name, salary, and salary increased by 15.5% (expressed as a whole number) for each employee. Label the column New Salary. Save your SQL statement in a file named lab\_03\_02.sql.
3. Run your query in the lab\_03\_02.sql file.

	EMPLOYEE_ID	LAST_NAME	SALARY	New Salary
1	100	King	24000	27720
2	101	Kochhar	17000	19635
3	102	De Haan	17000	19635
4	103	Hunold	9000	10395
5	104	Ernst	6000	6930
6	107	Lorentz	4200	4851
7	124	Mourgos	5800	6699
8	141	Rajs	3500	4043
9	142	Davies	3100	3581
10	143	Matos	2600	3003
...				
19	205	Higgins	12000	13860
20	206	Gietz	8300	9587

4. Modify your query lab\_03\_02.sql to add a column that subtracts the old salary from the new salary. Label the column Increase. Save the contents of the file as lab\_03\_04.sql. Run the revised query.

	EMPLOYEE_ID	LAST_NAME	SALARY	New Salary	Increase
1	100	King	24000	27720	3720
2	101	Kochhar	17000	19635	2635
3	102	De Haan	17000	19635	2635
4	103	Hunold	9000	10395	1395
5	104	Ernst	6000	6930	930
...					
20	206	Gietz	8300	9587	1287

### Practice 3 (continued)


- Write a query that displays the last name (with the first letter in uppercase and all the other letters in lowercase) and the length of the last name for all employees whose name starts with the letters “J,” “A,” or “M.” Give each column an appropriate label. Sort the results by the employees’ last names.

	A-Z	Name	A-Z	Length
1		Abel		4
2		Matos		5
3		Mourgos		7

Rewrite the query so that the user is prompted to enter a letter that the last name starts with. For example, if the user enters “H” (capitalized) when prompted for a letter, then the output should show all employees whose last name starts with the letter “H.”

	A-Z	Name	A-Z	Length
1		Hartstein		9
2		Higgins		7
3		Hunold		6

Modify the query such that the case of the entered letter does not affect the output. The entered letter must be capitalized before being processed by the SELECT query.



	A-Z	Name	A-Z	Length
1		Hartstein		9
2		Higgins		7
3		Hunold		6

### Practice 3 (continued)

- The HR department wants to find the duration of employment for each employee. For each employee, display the last name and calculate the number of months between today and the date on which the employee was hired. Label the column as MONTHS\_WORKED. Order your results by the number of months employed. Round the number of months up to the closest whole number.

**Note:** Because this query depends on the date when it was executed, the values in the MONTHS\_WORKED column will differ for you.

	LAST_NAME	MONTHS_WORKED
1	Zlotkey	88
2	Mourgos	90
3	Grant	96
4	Lorentz	100
5	Vargas	107
6	Taylor	110
7	Matos	111
8	Fay	117
9	Davies	124
10	Abel	133
11	Hartstein	135
12	Rajs	139
13	Higgins	156
14	Gietz	156
15	De Haan	173
16	Ernst	192
17	Hunold	209
18	Kochhar	212
19	Whalen	236
20	King	239

### Practice 3 (continued)

If you have time, complete the following exercises:

7. Create a query to display the last name and salary for all employees. Format the salary to be 15 characters long, left-padded with the \$ symbol. Label the column as SALARY.

	LAST_NAME	SALARY
1	King	\$\$\$\$\$\$\$\$\$24000
2	Kochhar	\$\$\$\$\$\$\$\$\$17000

...

20	Gietz	\$\$\$\$\$\$\$\$\$8300
----	-------	------------------------

8. Create a query that displays the first eight characters of the employees' last names and indicates the amounts of their salaries with asterisks. Each asterisk signifies a thousand dollars. Sort the data in descending order of salary. Label the column as EMPLOYEES\_AND\_THEIR\_SALARIES.

	EMPLOYEES_AND_THEIR_SALARIES
1	King *****
2	Kochhar *****
3	De Haan *****
4	Hartstei *****
5	Higgins *****

...

19	Matos **
20	Vargas **

9. Create a query to display the last name and the number of weeks employed for all employees in department 90. Label the number of weeks column as TENURE. Truncate the number of weeks value to 0 decimal places. Show the records in descending order of the employee's tenure.  
**Note:** The TENURE value will differ as it depends on the date on which you run the query.

	LAST_NAME	TENURE
1	King	1041
2	Kochhar	923
3	De Haan	750



# 4

## Using Conversion Functions and Conditional Expressions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- Describe various types of conversion functions that are available in SQL
- Use the `TO_CHAR`, `TO_NUMBER`, and `TO_DATE` conversion functions
- Apply conditional expressions in a `SELECT` statement

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

This lesson focuses on functions that convert data from one type to another (for example, conversion from character data to numeric data) and discusses the conditional expressions in SQL `SELECT` statements.

## Lesson Agenda


- Implicit and explicit data type conversion
- TO\_CHAR, TO\_DATE, TO\_NUMBER functions
- Nesting functions
- General functions:
  - NVL
  - NVL2
  - NULLIF
  - COALESCE
- Conditional expressions:
  - CASE
  - DECODE

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Conversion Functions



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Conversion Functions

In addition to Oracle data types, columns of tables in an Oracle database can be defined by using the American National Standards Institute (ANSI), DB2, and SQL/DS data types. However, the Oracle server internally converts such data types to Oracle data types.

In some cases, the Oracle server receives data of one data type where it expects data of a different data type. When this happens, the Oracle server can automatically convert the data to the expected data type. This data type conversion can be done *implicitly* by the Oracle server or *explicitly* by the user.

Implicit data type conversions work according to the rules explained in the next two slides.

Explicit data type conversions are done by using the conversion functions. Conversion functions convert a value from one data type to another. Generally, the form of the function names follows the convention *data type TO data type*. The first data type is the input data type and the second data type is the output.

**Note:** Although implicit data type conversion is available, it is recommended that you do the explicit data type conversion to ensure the reliability of your SQL statements.

## Implicit Data Type Conversion

In expressions, the Oracle server can automatically convert the following:

From	To
VARCHAR2 or CHAR	NUMBER
VARCHAR2 or CHAR	DATE

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Implicit Data Type Conversion

Oracle server can automatically perform data type conversion in an expression. For example, the expression `hire_date > '01-JAN-90'` results in the implicit conversion from the string '01-JAN-90' to a date. Therefore, a VARCHAR2 or CHAR value can be implicitly converted to a number or date data type in an expression.

# Implicit Data Type Conversion

For expression evaluation, the Oracle server can automatically convert the following:

From	To
NUMBER	VARCHAR2 or CHAR
DATE	VARCHAR2 or CHAR

ORACLE


Copyright © 2009, Oracle. All rights reserved.

## Implicit Data Type Conversion (continued)

In general, the Oracle server uses the rule for expressions when a data type conversion is needed. For example, the expression `grade = 2` results in the implicit conversion of the number 20000 to the string "2" because `grade` is a `CHAR(2)` column.

**Note:** CHAR to NUMBER conversions succeed only if the character string represents a valid number.

## Explicit Data Type Conversion



ORACLE


Copyright © 2009, Oracle. All rights reserved.

### Explicit Data Type Conversion

SQL provides three functions to convert a value from one data type to another:

Function	Purpose
<code>TO_CHAR(number date, [fmt], [nlsparams])</code>	<p>Converts a number or date value to a VARCHAR2 character string with the format model <i>fmt</i></p> <p><b>Number conversion:</b> The <i>nlsparams</i> parameter specifies the following characters, which are returned by number format elements:</p> <ul style="list-style-type: none"> <li>• Decimal character</li> <li>• Group separator</li> <li>• Local currency symbol</li> <li>• International currency symbol</li> </ul> <p>If <i>nlsparams</i> or any other parameter is omitted, this function uses the default parameter values for the session.</p>

## Explicit Data Type Conversion



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Explicit Data Type Conversion (continued)

Function	Purpose
<code>TO_CHAR(number date, [fmt], [nlsparams])</code>	<b>Date conversion:</b> The <code>nlsparams</code> parameter specifies the language in which the month and day names, and abbreviations are returned. If this parameter is omitted, this function uses the default date languages for the session.
<code>TO_NUMBER(char, [fmt], [nlsparams])</code>	Converts a character string containing digits to a number in the format specified by the optional format model <code>fmt</code> . The <code>nlsparams</code> parameter has the same purpose in this function as in the <code>TO_CHAR</code> function for number conversion.
<code>TO_DATE(char, [fmt], [nlsparams])</code>	Converts a character string representing a date to a date value according to the <code>fmt</code> that is specified. If <code>fmt</code> is omitted, the format is DD-MON-YY. The <code>nlsparams</code> parameter has the same purpose in this function as in the <code>TO_CHAR</code> function for date conversion.

## Explicit Data Type Conversion (continued)

**Note:** The list of functions mentioned in this lesson includes only some of the available conversion functions.

For more information, see the section on *Conversion Functions* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

Oracle Internal & Oracle Academy  
Use Only

## Lesson Agenda

- Implicit and explicit data type conversion
- **TO\_CHAR, TO\_DATE, TO\_NUMBER functions**
- Nesting functions
- General functions:
  - NVL
  - NVL2
  - NULLIF
  - COALESCE
- Conditional expressions:
  - CASE
  - DECODE

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Using the TO\_CHAR Function with Dates

```
TO_CHAR(date, 'format_model')
```

The format model:

- Must be enclosed with single quotation marks
- Is case-sensitive
- Can include any valid date format element
- Has an *fm* element to remove padded blanks or suppress leading zeros
- Is separated from the date value by a comma

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the TO\_CHAR Function with Dates

TO\_CHAR converts a datetime data type to a value of VARCHAR2 data type in the format specified by the *format\_model*. A format model is a character literal that describes the format of datetime stored in a character string. For example, the datetime format model for the string '11-NOV-1999' is 'DD-Mon-YYYY'. You can use the TO\_CHAR function to convert a date from its default format to the one that you specify.

#### Guidelines

- The format model must be enclosed with single quotation marks and is case-sensitive.
- The format model can include any valid date format element. But be sure to separate the date value from the format model with a comma.
- The names of days and months in the output are automatically padded with blanks.
- To remove padded blanks or to suppress leading zeros, use the fill mode *fm* element.

```
SELECT employee_id, TO_CHAR(hire_date, 'MM/YY') Month_Hired
FROM employees
WHERE last_name = 'Higgins';
```

	EMPLOYEE_ID	MONTH_HIRED
1	205	06/94

## Elements of the Date Format Model

Element	Result
YYYY	Full year in numbers
YEAR	Year spelled out (in English)
MM	Two-digit value for the month
MONTH	Full name of the month
MON	Three-letter abbreviation of the month
DY	Three-letter abbreviation of the day of the week
DAY	Full name of the day of the week
DD	Numeric day of the month

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Sample Format Elements of Valid Date Formats

Element	Description
SCC or CC	Century; server prefixes B.C. date with -
Years in dates YYYY or SYYYY	Year; server prefixes B.C. date with -
YYY or YY or Y	Last three, two, or one digit of the year
Y,YYY	Year with comma in this position
IYYY, IYY, IY, I	Four-, three-, two-, or one-digit year based on the ISO standard
SYEAR or YEAR	Year spelled out; server prefixes B.C. date with -
BC or AD	Indicates B.C. or A.D. year
B.C. or A.D.	Indicates B.C. or A.D. year using periods
Q	Quarter of year
MM	Month: two-digit value
MONTH	Name of the month padded with blanks to a length of nine characters
MON	Name of the month, three-letter abbreviation
RM	Roman numeral month
WW or W	Week of the year or month
DDD or DD or D	Day of the year, month, or week
DAY	Name of the day padded with blanks to a length of nine characters
DY	Name of the day; three-letter abbreviation
J	Julian day; the number of days since December 31, 4713 B.C.
IW	Weeks in the year from ISO standard (1 to 53)

## Elements of the Date Format Model

- Time elements format the time portion of the date:

HH24:MI:SS AM	15:45:32 PM
---------------	-------------

- Add character strings by enclosing them with double quotation marks:

DD "of" MONTH	12 of OCTOBER
---------------	---------------

- Number suffixes spell out numbers:

ddspth	fourteenth
--------	------------

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Elements of the Date Format Model

Use the formats that are listed in the following tables to display time information and literals, and to change numerals to spelled numbers.

Element	Description
AM or PM	Meridian indicator
A.M. or P.M.	Meridian indicator with periods
HH or HH12 or HH24	Hour of day, or hour (1–12), or hour (0–23)
MI	Minute (0–59)
SS	Second (0–59)
SSSSS	Seconds past midnight (0–86399)

## Other Formats

Element	Description
/ . ,	Punctuation is reproduced in the result.
“of the”	Quoted string is reproduced in the result.

## Specifying Suffixes to Influence Number Display

Element	Description
TH	Ordinal number (for example, DDTH for 4TH)
SP	Spelled-out number (for example, DDSP for FOUR)
SPTH or THSP	Spelled-out ordinal numbers (for example, DDSPTH for FOURTH)

Oracle Internal & Oracle Academy  
Use Only

## Using the TO\_CHAR Function with Dates

```
SELECT last_name,  
       TO_CHAR(hire_date, 'fmDD Month YYYY')  
       AS HIREDATE  
FROM   employees;
```

	LAST_NAME	HIREDATE
1	King	17 June 1987
2	Kochhar	21 September 1989
3	De Haan	13 January 1993
4	Hunold	3 January 1990
5	Ernst	21 May 1991
6	Lorentz	7 February 1999
7	Mourgos	16 November 1999
8	Rajs	17 October 1995
9	Davies	29 January 1997
10	Matos	15 March 1998
...		
19	Higgins	7 June 1994
20	Gietz	7 June 1994

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the TO\_CHAR Function with Dates

The SQL statement in the slide displays the last names and hire dates for all the employees. The hire date appears as 17 June 1987.

#### Example:

Modify the example in the slide to display the dates in a format that appears as “Seventeenth of June 1987 12:00:00 AM.”

```
SELECT last_name,  
       TO_CHAR(hire_date,  
               'fmDdspth "of" Month YYYY fmHH:MI:SS AM')  
       HIREDATE  
FROM   employees;
```

	LAST_NAME	HIREDATE
1	King	Seventeenth of June 1987 12:00:00 AM
2	Kochhar	Twenty-First of September 1989 12:00:00 AM

Notice that the month follows the format model specified; in other words, the first letter is capitalized and the rest are in lowercase.

## Using the TO\_CHAR Function with Numbers

```
TO_CHAR(number, 'format_model')
```

These are some of the format elements that you can use with the TO\_CHAR function to display a number value as a character:

Element	Result
9	Represents a number
0	Forces a zero to be displayed
\$	Places a floating dollar sign
L	Uses the floating local currency symbol
.	Prints a decimal point
,	Prints a comma as a thousands indicator

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the TO\_CHAR Function with Numbers

When working with number values, such as character strings, you should convert those numbers to the character data type using the TO\_CHAR function, which translates a value of NUMBER data type to VARCHAR2 data type. This technique is especially useful with concatenation.

## Using the TO\_CHAR Function with Numbers (continued)

### Number Format Elements

If you are converting a number to the character data type, you can use the following format elements:

Element	Description	Example	Result
9	Numeric position (number of 9s determine display width)	999999	1234
0	Display leading zeros	0999999	001234
\$	Floating dollar sign	\$999999	\$1234
L	Floating local currency symbol	L999999	FF1234
D	Returns the decimal character in the specified position. The default is a period (.).	99D99	99.99
.	Decimal point in position specified	999999.99	1234.00
G	Returns the group separator in the specified position. You can specify multiple group separators in a number format model.	9,999	9G999
,	Comma in position specified	999,999	1,234
MI	Minus signs to right (negative values)	999999MI	1234-
PR	Parenthesize negative numbers	999999PR	<1234>
EEEE	Scientific notation (format must specify four Es)	99.999EEEE	1.234E+03
U	Returns in the specified position the “Euro” (or other) dual currency	U9999	€1234
V	Multiply by 10 <i>n</i> times ( <i>n</i> = number of 9s after V)	9999V99	123400
S	Returns the negative or positive value	S9999	-1234 or +1234
B	Display zero values as blank, not 0	B9999.99	1234.00

## Using the TO\_CHAR Function with Numbers

```
SELECT TO_CHAR(salary, '$99,999.00') SALARY
FROM   employees
WHERE  last_name = 'Ernst';
```

	SALARY
1	\$6,000.00

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the TO\_CHAR Function with Numbers (continued)

- The Oracle server displays a string of number signs (#) in place of a whole number whose digits exceed the number of digits provided in the format model.
- The Oracle server rounds the stored decimal value to the number of decimal places provided in the format model.

## Using the TO\_NUMBER and TO\_DATE Functions

- Convert a character string to a number format using the TO\_NUMBER function:

```
TO_NUMBER(char[, 'format_model'])
```

- Convert a character string to a date format using the TO\_DATE function:

```
TO_DATE(char[, 'format_model'])
```

- These functions have an `fx` modifier. This modifier specifies the exact match for the character argument and date format model of a TO\_DATE function.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the TO\_NUMBER and TO\_DATE Functions

You may want to convert a character string to either a number or a date. To accomplish this task, use the TO\_NUMBER or TO\_DATE functions. The format model that you select is based on the previously demonstrated format elements.

The `fx` modifier specifies the exact match for the character argument and date format model of a TO\_DATE function:

- Punctuation and quoted text in the character argument must exactly match (except for case) the corresponding parts of the format model.
- The character argument cannot have extra blanks. Without `fx`, the Oracle server ignores extra blanks.
- Numeric data in the character argument must have the same number of digits as the corresponding element in the format model. Without `fx`, the numbers in the character argument can omit leading zeros.


## Using the TO\_NUMBER and TO\_DATE Functions (continued)

### Example:

Display the name and hire date for all employees who started on May 24, 1999. There are two spaces after the month *May* and before the number *24* in the following example. Because the `fx` modifier is used, an exact match is required and the spaces after the word *May* are not recognized:

```
SELECT last_name, hire_date
FROM   employees
WHERE  hire_date = TO_DATE('May  24, 1999', 'fxMonth DD, YYYY');
```

The resulting error output looks like this:



## Using the TO\_CHAR and TO\_DATE Function with RR Date Format

To find employees hired before 1990, use the RR date format, which produces the same results whether the command is run in 1999 or now:

```
SELECT last_name, TO_CHAR(hire_date, 'DD-Mon-YYYY')
FROM employees
WHERE hire_date < TO_DATE('01-Jan-90', 'DD-Mon-RR');
```

	LAST_NAME	TO_CHAR(HIRE_DATE,'DD-MON-YYYY')
1	King	17-Jun-1987
2	Kochhar	21-Sep-1989
3	Whalen	17-Sep-1987

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the TO\_CHAR and TO\_DATE Function with RR Date Format

To find employees who were hired before 1990, the RR format can be used. Because the current year is greater than 1999, the RR format interprets the year portion of the date from 1950 to 1999.

The following command, on the other hand, results in no rows being selected because the YY format interprets the year portion of the date in the current century (2090).

```
SELECT last_name, TO_CHAR(hire_date, 'DD-Mon-yyyy')
FROM employees
WHERE TO_DATE(hire_date, 'DD-Mon-yy') < '01-Jan-1990';
```

```
0 rows selected
```

## Lesson Agenda

- Implicit and explicit data type conversion
- TO\_CHAR, TO\_DATE, TO\_NUMBER functions
- **Nesting functions**
- General functions:
  - NVL
  - NVL2
  - NULLIF
  - COALESCE
- Conditional expressions:
  - CASE
  - DECODE


ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Nesting Functions

- Single-row functions can be nested to any level.
- Nested functions are evaluated from the deepest level to the least deep level.



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Nesting Functions

Single-row functions can be nested to any depth. Nested functions are evaluated from the innermost level to the outermost level. Some examples follow to show you the flexibility of these functions.

# Nesting Functions

```
SELECT last_name,  
       UPPER(CONCAT(SUBSTR (LAST_NAME, 1, 8), '_US'))  
FROM   employees  
WHERE  department_id = 60;
```

	LAST_NAME	UPPER(CONCAT(SUBSTR(LAST_NAME,1,8),'_US'))
1	Hunold	HUNOLD_US
2	Ernst	ERNST_US
3	Lorentz	LORENTZ_US

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Nesting Functions (continued)

The slide example displays the last names of employees in department 60. The evaluation of the SQL statement involves three steps:

1. The inner function retrieves the first eight characters of the last name.  
Result1 = SUBSTR (LAST\_NAME, 1, 8)
2. The outer function concatenates the result with \_US.  
Result2 = CONCAT(Result1, '\_US')
3. The outermost function converts the results to uppercase.

The entire expression becomes the column heading because no column alias was given.

### Example:

Display the date of the next Friday that is six months from the hire date. The resulting date should appear as Friday, August 13th, 1999. Order the results by hire date.

```
SELECT      TO_CHAR(NEXT_DAY(ADD_MONTHS  
                    (hire_date, 6), 'FRIDAY'),  
            'fmDay, Month ddth, YYYY')  
            "Next 6 Month Review"  
FROM        employees  
ORDER BY   hire_date;
```

## Lesson Agenda

- Implicit and explicit data type conversion
- TO\_CHAR, TO\_DATE, TO\_NUMBER functions
- Nesting functions
- **General functions:**
  - NVL
  - NVL2
  - NULLIF
  - COALESCE
- **Conditional expressions:**
  - CASE
  - DECODE

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## General Functions

The following functions work with any data type and pertain to using nulls:

- NVL (expr1, expr2)
- NVL2 (expr1, expr2, expr3)
- NULLIF (expr1, expr2)
- COALESCE (expr1, expr2, ..., exprn)

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### General Functions

These functions work with any data type and pertain to the use of null values in the expression list.

Function	Description
NVL	Converts a null value to an actual value
NVL2	If expr1 is not null, NVL2 returns expr2. If expr1 is null, NVL2 returns expr3. The argument expr1 can have any data type.
NULLIF	Compares two expressions and returns null if they are equal; returns the first expression if they are not equal
COALESCE	Returns the first non-null expression in the expression list

**Note:** For more information about the hundreds of functions available, see the section on *Functions* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

# NVL Function

Converts a null value to an actual value:

- Data types that can be used are date, character, and number.
- Data types must match:
  - `NVL(commission_pct, 0)`
  - `NVL(hire_date, '01-JAN-97')`
  - `NVL(job_id, 'No Job Yet')`

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## NVL Function

To convert a null value to an actual value, use the NVL function.

### Syntax

`NVL (expr1, expr2)`

In the syntax:

- *expr1* is the source value or expression that may contain a null
- *expr2* is the target value for converting the null

You can use the NVL function to convert any data type, but the return value is always the same as the data type of *expr1*.

### NVL Conversions for Various Data Types

Data Type	Conversion Example
NUMBER	<code>NVL(number_column, 9)</code>
DATE	<code>NVL(date_column, '01-JAN-95')</code>
CHAR or VARCHAR2	<code>NVL(character_column, 'Unavailable')</code>

# Using the NVL Function

```
SELECT last name, salary, NVL(commission pct, 0),  
       (salary*12) + (salary*12*NVL(commission_pct, 0)) AN_SAL  
FROM employees;
```

	LAST_NAME	SALARY	NVL(COMMISSION_PCT,0)	AN_SAL
1	King	24000	0	288000
2	Kochhar	17000	0	204000
3	De Haan	17000	0	204000
4	Hunold	9000	0	108000
5	Ernst	6000	0	72000
6	Lorentz	4200	0	50400
7	Mourgos	5800	0	69600
8	Rajs	3500	0	42000
9	Davies	3100	0	37200
10	Matos	2600	0	31200
11	Vargas	2500	0	30000
12	Zlotkey	10500	0.2	151200

...

1

2

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the NVL Function

To calculate the annual compensation of all employees, you need to multiply the monthly salary by 12 and then add the commission percentage to the result:

```
SELECT last_name, salary, commission_pct,  
       (salary*12) + (salary*12*commission_pct) AN_SAL  
FROM employees;
```

	LAST_NAME	SALARY	COMMISSION_PCT	AN_SAL
1	King	24000	(null)	(null)

...

11	Vargas	2500	(null)	(null)
12	Zlotkey	10500	0.2	151200
13	Abel	11000	0.3	171600

...

Notice that the annual compensation is calculated for only those employees who earn a commission. If any column value in an expression is null, the result is null. To calculate values for all employees, you must convert the null value to a number before applying the arithmetic operator. In the example in the slide, the NVL function is used to convert null values to zero.

# Using the NVL2 Function

```
SELECT last name, salary, commission_pct,
       NVL2 (commission_pct,
            'SAL+COMM', 'SAL') income
FROM   employees WHERE department_id IN (50, 80);
```

	LAST_NAME	SALARY	COMMISSION_PCT	INCOME
1	Mourgos	5800	(null)	SAL
2	Rajs	3500	(null)	SAL
3	Davies	3100	(null)	SAL
4	Matos	2600	(null)	SAL
5	Vargas	2500	(null)	SAL
6	Zlotkey	10500	0.2	SAL+COMM
7	Abel	11000	0.3	SAL+COMM
8	Taylor	8600	0.2	SAL+COMM

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the NVL2 Function

The NVL2 function examines the first expression. If the first expression is not null, then the NVL2 function returns the second expression. If the first expression is null, then the third expression is returned.

### Syntax

```
NVL2 (expr1, expr2, expr3)
```

In the syntax:

- *expr1* is the source value or expression that may contain a null
- *expr2* is the value that is returned if *expr1* is not null
- *expr3* is the value that is returned if *expr1* is null

In the example shown in the slide, the COMMISSION\_PCT column is examined. If a value is detected, the text literal value of SAL+COMM is returned. If the COMMISSION\_PCT column contains a null value, the text literal value of SAL is returned.

**Notes:** The argument *expr1* can have any data type. The arguments *expr2* and *expr3* can have any data types except LONG.

# Using the NULLIF Function

```
SELECT first_name, LENGTH(first_name) "expr1",  
       last_name, LENGTH(last_name) "expr2",  
       NULLIF(LENGTH(first_name), LENGTH(last_name)) result  
FROM employees;
```

	FIRST_NAME	expr1	LAST_NAME	expr2	RESULT
1	Ellen	5	Abel	4	5
2	Curtis	6	Davies	6	(null)
3	Lex	3	De Haan	7	3
4	Bruce	5	Ernst	5	(null)
5	Pat	3	Fay	3	(null)
6	William	7	Gietz	5	7
7	Kimberely	9	Grant	5	9
...					
19	Jennifer	8	Whalen	6	8
20	Eleni	5	Zlotkey	7	5

Diagram annotations: 1 points to the LENGTH expressions in the SELECT clause. 2 points to the NULLIF function. 3 points to the result column in the table.

Copyright © 2009, Oracle. All rights reserved.

## Using the NULLIF Function

The NULLIF function compares two expressions. If they are equal, the function returns a null. If they are not equal, the function returns the first expression. However, you cannot specify the literal NULL for the first expression.

### Syntax

```
NULLIF (expr1, expr2)
```

In the syntax:

- NULLIF compares *expr1* and *expr2*. If they are equal, then the function returns null. If they are not, then the function returns *expr1*. However, you cannot specify the literal NULL for *expr1*.

In the example shown in the slide, the length of the first name in the EMPLOYEES table is compared to the length of the last name in the EMPLOYEES table. When the lengths of the names are equal, a null value is displayed. When the lengths of the names are not equal, the length of the first name is displayed.

**Note:** The NULLIF function is logically equivalent to the following CASE expression. The CASE expression is discussed on a subsequent page:

```
CASE WHEN expr1 = expr 2 THEN NULL ELSE expr1 END
```

## Using the COALESCE Function

- The advantage of the COALESCE function over the NVL function is that the COALESCE function can take multiple alternate values.
- If the first expression is not null, the COALESCE function returns that expression; otherwise, it does a COALESCE of the remaining expressions.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the COALESCE Function

The COALESCE function returns the first non-null expression in the list.

#### Syntax

```
COALESCE (expr1, expr2, ... exprn)
```

In the syntax:

- *expr1* returns this expression if it is not null
- *expr2* returns this expression if the first expression is null and this expression is not null
- *exprn* returns this expression if the preceding expressions are null

Note that all expressions must be of the same data type.

## Using the COALESCE Function

```
SELECT last name, employee id,  
COALESCE(TO_CHAR(commission_pct), TO_CHAR(manager_id),  
         'No commission and no manager')  
FROM employees;
```

LAST_NAME	EMPLOYEE_ID	COALESCE(TO_CHAR(COMMISSION_PCT), TO_CHAR(MANAGER_ID), 'No commission and no manager')
King	100	No commission and no manager
Kochhar	101	100
De Haan	102	100
Hunold	103	102
Ernst	104	103
Lorentz	107	103
Mourgos	124	100
Rajs	141	124

...

Zlotkey	149	.2
Abel	174	.3
Taylor	176	.2
Grant	178	.15
Whalen	200	101

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the COALESCE Function (continued)

In the example shown in the slide, if the `manager_id` value is not null, it is displayed. If the `manager_id` value is null, then the `commission_pct` is displayed. If the `manager_id` and `commission_pct` values are null, then “No commission and no manager” is displayed. Note, `TO_CHAR` function is applied so that all expressions are of the same data type.

## Using the COALESCE Function (continued)

### Example:

For the employees who do not get any commission, your organization wants to give a salary increment of \$2,000 and for employees who get commission, the query should compute the new salary that is equal to the existing salary added to the commission amount.

```
SELECT last_name, salary, commission_pct,  
       COALESCE((salary+(commission_pct*salary)), salary+2000, salary) "New  
       Salary"  
FROM   employees;
```

**Note:** Examine the output. For employees who do not get any commission, the New Salary column shows the salary incremented by \$2,000 and for employees who get commission, the New Salary column shows the computed commission amount added to the salary.

	A Z	LAST_NAME	A Z	SALARY	A Z	COMMISSION_PCT	A Z	New Salary
1		King		24000		(null)		26000
2		Kochhar		17000		(null)		19000
3		De Haan		17000		(null)		19000
4		Hunold		9000		(null)		11000

...

9		Davies		3100		(null)		5100
10		Matos		2600		(null)		4600
11		Vargas		2500		(null)		4500
12		Zlotkey		10500		0.2		12600
13		Abel		11000		0.3		14300
14		Taylor		8600		0.2		10320
15		Grant		7000		0.15		8050
16		Whalen		4400		(null)		6400
17		Hartstein		13000		(null)		15000
18		Fay		6000		(null)		8000
19		Higgins		12000		(null)		14000
20		Gietz		8300		(null)		10300

...

## Lesson Agenda

- Implicit and explicit data type conversion
- TO\_CHAR, TO\_DATE, TO\_NUMBER functions
- Nesting functions
- General functions:
  - NVL
  - NVL2
  - NULLIF
  - COALESCE
- Conditional expressions:
  - CASE
  - DECODE

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Conditional Expressions

- Provide the use of the `IF-THEN-ELSE` logic within a SQL statement
- Use two methods:
  - `CASE` expression
  - `DECODE` function

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Conditional Expressions

The two methods that are used to implement conditional processing (`IF-THEN-ELSE` logic) in a SQL statement are the `CASE` expression and the `DECODE` function.

**Note:** The `CASE` expression complies with the ANSI SQL. The `DECODE` function is specific to Oracle syntax.

## CASE Expression

Facilitates conditional inquiries by doing the work of an IF-THEN-ELSE statement:

```
CASE expr WHEN comparison_expr1 THEN return_expr1
      [WHEN comparison_expr2 THEN return_expr2
      WHEN comparison_exprn THEN return_exprn
      ELSE else_expr]
END
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### CASE Expression

CASE expressions allow you to use the IF-THEN-ELSE logic in SQL statements without having to invoke procedures.

In a simple CASE expression, the Oracle server searches for the first WHEN . . . THEN pair for which *expr* is equal to *comparison\_expr* and returns *return\_expr*. If none of the WHEN . . . THEN pairs meet this condition, and if an ELSE clause exists, then the Oracle server returns *else\_expr*. Otherwise, the Oracle server returns a null. You cannot specify the literal NULL for all the *return\_exprs* and the *else\_expr*.

All of the expressions (*expr*, *comparison\_expr*, and *return\_expr*) must be of the same data type, which can be CHAR, VARCHAR2, NCHAR, or NVARCHAR2.

## Using the CASE Expression

Facilitates conditional inquiries by doing the work of an IF-THEN-ELSE statement:

```
SELECT last_name, job_id, salary,  
       CASE job_id WHEN 'IT_PROG' THEN 1.10*salary  
                  WHEN 'ST_CLERK' THEN 1.15*salary  
                  WHEN 'SA_REP' THEN 1.20*salary  
                  ELSE salary END "REVISED_SALARY"  
FROM employees;
```

LAST_NAME	JOB_ID	SALARY	REVISED_SALARY
...			
5 Ernst	IT_PROG	6000	6600
6 Lorentz	IT_PROG	4200	4620
7 Mourgos	ST_MAN	5800	5800
8 Rajs	ST_CLERK	3500	4025
9 Davies	ST_CLERK	3100	3565
...			
13 Abel	SA_REP	11000	13200
14 Taylor	SA_REP	8600	10320
...			

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the CASE Expression

In the SQL statement in the slide, the value of JOB\_ID is decoded. If JOB\_ID is IT\_PROG, the salary increase is 10%; if JOB\_ID is ST\_CLERK, the salary increase is 15%; if JOB\_ID is SA\_REP, the salary increase is 20%. For all other job roles, there is no increase in salary.

The same statement can be written with the DECODE function.

The following code is an example of the searched CASE expression. In a searched CASE expression, the search occurs from left to right until an occurrence of the listed condition is found, and then it returns the return expression. If no condition is found to be true, and if an ELSE clause exists, the return expression in the ELSE clause is returned; otherwise, a NULL is returned.

```
SELECT last_name, salary,  
       (CASE WHEN salary<5000 THEN 'Low'  
            WHEN salary<10000 THEN 'Medium'  
            WHEN salary<20000 THEN 'Good'  
            ELSE 'Excellent'  
            END) qualified_salary  
FROM employees;
```

## DECODE Function

Facilitates conditional inquiries by doing the work of a `CASE` expression or an `IF-THEN-ELSE` statement:

```
DECODE(col/expression, search1, result1  
      [, search2, result2,...],  
      [, default])
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### DECODE Function

The `DECODE` function decodes an expression in a way similar to the `IF-THEN-ELSE` logic that is used in various languages. The `DECODE` function decodes *expression* after comparing it to each *search* value. If the expression is the same as *search*, *result* is returned.

If the default value is omitted, a null value is returned where a search value does not match any of the result values.

## Using the DECODE Function

```
SELECT last name, job id, salary,  
       DECODE(job_id, 'IT_PROG', 1.10*salary,  
              'ST_CLERK', 1.15*salary,  
              'SA_REP', 1.20*salary,  
              salary)  
       REVISED_SALARY  
FROM   employees;
```

	LAST_NAME	JOB_ID	SALARY	REVISED_SALARY
...				
6	Lorentz	IT_PROG	4200	4620
7	Mourgos	ST_MAN	5800	5800
8	Rajs	ST_CLERK	3500	4025
...				
13	Abel	SA_REP	11000	13200
14	Taylor	SA_REP	8600	10320
...				

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the DECODE Function

In the SQL statement in the slide, the value of JOB\_ID is tested. If JOB\_ID is IT\_PROG, the salary increase is 10%; if JOB\_ID is ST\_CLERK, the salary increase is 15%; if JOB\_ID is SA\_REP, the salary increase is 20%. For all other job roles, there is no increase in salary.

The same statement can be expressed in pseudocode as an IF-THEN-ELSE statement:

```
IF job_id = 'IT_PROG' THEN salary = salary*1.10  
IF job_id = 'ST_CLERK' THEN salary = salary*1.15  
IF job_id = 'SA_REP' THEN salary = salary*1.20  
ELSE salary = salary
```

## Using the DECODE Function

Display the applicable tax rate for each employee in department 80:

```
SELECT last name, salary,  
       DECODE (TRUNC(salary/2000, 0),  
              0, 0.00,  
              1, 0.09,  
              2, 0.20,  
              3, 0.30,  
              4, 0.40,  
              5, 0.42,  
              6, 0.44,  
              0.45) TAX_RATE  
FROM   employees  
WHERE  department_id = 80;
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the DECODE Function (continued)

This slide shows another example using the DECODE function. In this example, you determine the tax rate for each employee in department 80 based on the monthly salary. The tax rates are as follows:

<i>Monthly Salary Range</i>	<i>Tax Rate</i>
\$0.00–1,999.99	00%
\$2,000.00–3,999.99	09%
\$4,000.00–5,999.99	20%
\$6,000.00–7,999.99	30%
\$8,000.00–9,999.99	40%
\$10,000.00–11,999.99	42%
\$12,200.00–13,999.99	44%
\$14,000.00 or greater	45%

	LAST_NAME	SALARY	TAX_RATE
1	Zlotkey	10500	0.42
2	Abel	11000	0.42
3	Taylor	8600	0.4

## Quiz

The `TO_NUMBER` function converts either character strings or date values to a number in the format specified by the optional format model.

1. True
2. False

ORACLE

Copyright © 2009, Oracle. All rights reserved.

**Answer: 2**

Oracle Internal & Oracle Academy  
Use Only

## Summary

In this lesson, you should have learned how to:

- Alter date formats for display using functions
- Convert column data types using functions
- Use NVL functions
- Use IF-THEN-ELSE logic and other conditional expressions in a SELECT statement

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Summary

Remember the following:

- Conversion functions can convert character, date, and numeric values: TO\_CHAR, TO\_DATE, TO\_NUMBER
- There are several functions that pertain to nulls, including NVL, NVL2, NULLIF, and COALESCE.
- IF-THEN-ELSE logic can be applied within a SQL statement by using the CASE expression or the DECODE function.

## Practice 4: Overview

This practice covers the following topics:

- Creating queries that use `TO_CHAR`, `TO_DATE`, and other `DATE` functions
- Creating queries that use conditional expressions such as `DECODE` and `CASE`

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice 4: Overview

This practice provides a variety of exercises using `TO_CHAR` and `TO_DATE` functions, and conditional expressions such as `DECODE` and `CASE`. Remember that for nested functions, the results are evaluated from the innermost function to the outermost function.

## Practice 4

1. Create a report that produces the following for each employee:  
`<employee last name> earns <salary> monthly but wants <3 times salary.>`. Label the column `Dream Salaries`.

	 Dream Salaries
1	King earns \$24,000.00 monthly but wants \$72,000.00.
2	Kochhar earns \$17,000.00 monthly but wants \$51,000.00.
3	De Haan earns \$17,000.00 monthly but wants \$51,000.00.
4	Hunold earns \$9,000.00 monthly but wants \$27,000.00.
5	Ernst earns \$6,000.00 monthly but wants \$18,000.00.

...

19	Higgins earns \$12,000.00 monthly but wants \$36,000.00.
20	Gietz earns \$8,300.00 monthly but wants \$24,900.00.

2. Display each employee's last name, hire date, and salary review date, which is the first Monday after six months of service. Label the column `REVIEW`. Format the dates to appear in the format similar to "Monday, the Thirty-First of July, 2000."

	 LAST_NAME	HIRE_DATE	 REVIEW
1	King	17-JUN-87	Monday, the Twenty-First of December, 1987
2	Kochhar	21-SEP-89	Monday, the Twenty-Sixth of March, 1990
3	De Haan	13-JAN-93	Monday, the Nineteenth of July, 1993
4	Hunold	03-JAN-90	Monday, the Ninth of July, 1990
5	Ernst	21-MAY-91	Monday, the Twenty-Fifth of November, 1991

...

19	Higgins	07-JUN-94	Monday, the Twelfth of December, 1994
20	Gietz	07-JUN-94	Monday, the Twelfth of December, 1994

### Practice 4 (continued)

3. Display the last name, hire date, and day of the week on which the employee started. Label the column DAY. Order the results by the day of the week, starting with Monday.

	LAST_NAME	HIRE_DATE	DAY
1	Grant	24-MAY-99	MONDAY
2	Gietz	07-JUN-94	TUESDAY
3	Taylor	24-MAR-98	TUESDAY
4	Higgins	07-JUN-94	TUESDAY
5	Rajs	17-OCT-95	TUESDAY

...

19	Lorentz	07-FEB-99	SUNDAY
20	Fay	17-AUG-97	SUNDAY

4. Create a query that displays the employees' last names and commission amounts. If an employee does not earn commission, show "No Commission." Label the column COMM.

	LAST_NAME	COMM
1	King	No Commission
2	Kochhar	No Commission
3	De Haan	No Commission
4	Hunold	No Commission
5	Ernst	No Commission
6	Lorentz	No Commission

...

12	Zlotkey	.2
13	Abel	.3
14	Taylor	.2
15	Grant	.15
16	Whalen	No Commission
17	Hartstein	No Commission
18	Fay	No Commission
19	Higgins	No Commission
20	Gietz	No Commission

**Practice 4 (continued)**

If you have time, complete the following exercises:

- Using the DECODE function, write a query that displays the grade of all employees based on the value of the column JOB\_ID, using the following data:

<i>Job</i>	<i>Grade</i>
AD_PRES	A
ST_MAN	B
IT_PROG	C
SA_REP	D
ST_CLERK	E
None of the above	0

	JOB_ID	GRADE
1	AC_ACCOUNT	0
2	AC_MGR	0
3	AD_ASST	0
4	AD_PRES	A
5	AD_VP	0

...

18	ST_CLERK	E
19	ST_CLERK	E
20	ST_MAN	B

- Rewrite the statement in the preceding exercise using the CASE syntax.

	JOB_ID	GRADE
1	AC_ACCOUNT	0
2	AC_MGR	0
3	AD_ASST	0
4	AD_PRES	A
5	AD_VP	0

...

18	ST_CLERK	E
19	ST_CLERK	E
20	ST_MAN	B



# 5

## Reporting Aggregated Data Using the Group Functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- Identify the available group functions
- Describe the use of group functions
- Group data by using the `GROUP BY` clause
- Include or exclude grouped rows by using the `HAVING` clause

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

This lesson further addresses functions. It focuses on obtaining summary information (such as averages) for groups of rows. It discusses how to group rows in a table into smaller sets and how to specify search criteria for groups of rows.

## Lesson Agenda

- Group functions:
  - Types and syntax
  - Use AVG, SUM, MIN, MAX, COUNT
  - Use DISTINCT keyword within group functions
  - NULL values in a group function
- Grouping rows:
  - GROUP BY clause
  - HAVING clause
- Nesting group functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# What Are Group Functions?

Group functions operate on sets of rows to give one result per group.

## EMPLOYEES

EMPLOYEE_ID	DEPARTMENT_ID	SALARY
1	90	24000
2	90	17000
3	90	17000
4	60	9000
5	60	6000
6	60	4200
7	50	5800
8	50	3500
9	50	3100
10	50	2600
...		
18	20	6000
19	110	12000
20	110	8300

Maximum salary in  
EMPLOYEES table

MAX(SALARY)
24000

ORACLE


Copyright © 2009, Oracle. All rights reserved.

## What Are Group Functions?

Unlike single-row functions, group functions operate on sets of rows to give one result per group. These sets may comprise the entire table or the table split into groups.

## Types of Group Functions

- AVG
- COUNT
- MAX
- MIN
- STDDEV
- SUM
- VARIANCE



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Types of Group Functions

Each of the functions accepts an argument. The following table identifies the options that you can use in the syntax:

Function	Description
AVG ( [DISTINCT   <u>ALL</u> ] <i>n</i> )	Average value of <i>n</i> , ignoring null values
COUNT ( { *   [DISTINCT   <u>ALL</u> ] <i>expr</i> } )	Number of rows, where <i>expr</i> evaluates to something other than null (count all selected rows using *, including duplicates and rows with nulls)
MAX ( [DISTINCT   <u>ALL</u> ] <i>expr</i> )	Maximum value of <i>expr</i> , ignoring null values
MIN ( [DISTINCT   <u>ALL</u> ] <i>expr</i> )	Minimum value of <i>expr</i> , ignoring null values
STDDEV ( [DISTINCT   <u>ALL</u> ] <i>x</i> )	Standard deviation of <i>n</i> , ignoring null values
SUM ( [DISTINCT   <u>ALL</u> ] <i>n</i> )	Sum values of <i>n</i> , ignoring null values
VARIANCE ( [DISTINCT   <u>ALL</u> ] <i>x</i> )	Variance of <i>n</i> , ignoring null values

## Group Functions: Syntax

```
SELECT    group_function(column), ...
FROM      table
[WHERE    condition]
[ORDER BY column];
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Group Functions: Syntax

The group function is placed after the `SELECT` keyword. You may have multiple group functions separated by commas.

Guidelines for using the group functions:

- `DISTINCT` makes the function consider only nonduplicate values; `ALL` makes it consider every value, including duplicates. The default is `ALL` and therefore does not need to be specified.
- The data types for the functions with an `expr` argument may be `CHAR`, `VARCHAR2`, `NUMBER`, or `DATE`.
- All group functions ignore null values. To substitute a value for null values, use the `NVL`, `NVL2`, or `COALESCE` functions.

## Using the AVG and SUM Functions

You can use `AVG` and `SUM` for numeric data.

```
SELECT AVG(salary), MAX(salary),  
       MIN(salary), SUM(salary)  
FROM   employees  
WHERE  job_id LIKE '%REP%';
```

	AVG(SALARY)	MAX(SALARY)	MIN(SALARY)	SUM(SALARY)
1	8150	11000	6000	32600

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the AVG and SUM Functions

You can use the `AVG`, `SUM`, `MIN`, and `MAX` functions against the columns that can store numeric data. The example in the slide displays the average, highest, lowest, and sum of monthly salaries for all sales representatives.

## Using the MIN and MAX Functions

You can use MIN and MAX for numeric, character, and date data types.

```
SELECT MIN(hire_date), MAX(hire_date)
FROM employees;
```

	MIN(HIRE_DATE)	MAX(HIRE_DATE)
1	17-JUN-87	29-JAN-00

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the MIN and MAX Functions

You can use the MAX and MIN functions for numeric, character, and date data types. The example in the slide displays the most junior and most senior employees.

The following example displays the employee last name that is first and the employee last name that is last in an alphabetic list of all employees:

```
SELECT MIN(last_name), MAX(last_name)
FROM employees;
```

	MIN(LAST_NAME)	MAX(LAST_NAME)
1	Abel	Zlotkey

**Note:** The AVG, SUM, VARIANCE, and STDDEV functions can be used only with numeric data types. MAX and MIN cannot be used with LOB or LONG data types.

# Using the COUNT Function

COUNT (\*) returns the number of rows in a table:

1

```
SELECT COUNT(*)  
FROM employees  
WHERE department_id = 50;
```

	COUNT(*)
1	5

COUNT (expr) returns the number of rows with non-null values for expr:

2

```
SELECT COUNT(commission_pct)  
FROM employees  
WHERE department_id = 80;
```

	COUNT(COMMISSION_PCT)
1	3

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the COUNT Function

The COUNT function has three formats:

- COUNT (\*)
- COUNT (expr)
- COUNT (DISTINCT expr)

COUNT (\*) returns the number of rows in a table that satisfy the criteria of the SELECT statement, including duplicate rows and rows containing null values in any of the columns. If a WHERE clause is included in the SELECT statement, COUNT (\*) returns the number of rows that satisfy the condition in the WHERE clause.

In contrast, COUNT (expr) returns the number of non-null values that are in the column identified by expr.

COUNT (DISTINCT expr) returns the number of unique, non-null values that are in the column identified by expr.

### Examples:

1. The example in the slide displays the number of employees in department 50.
2. The example in the slide displays the number of employees in department 80 who can earn a commission.

## Using the DISTINCT Keyword

- COUNT (DISTINCT expr) returns the number of distinct non-null values of *expr*.
- To display the number of distinct department values in the EMPLOYEES table:

```
SELECT COUNT(DISTINCT department_id)
FROM employees;
```

	COUNT(DISTINCTDEPARTMENT_ID)
1	7

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the DISTINCT Keyword

Use the DISTINCT keyword to suppress the counting of any duplicate values in a column.

The example in the slide displays the number of distinct department values that are in the EMPLOYEES table.

# Group Functions and Null Values

Group functions ignore null values in the column:

1

```
SELECT AVG(commission_pct)
FROM employees;
```

	AVG(COMMISSION_PCT)
1	0.2125

The NVL function forces group functions to include null values:

2

```
SELECT AVG(NVL(commission_pct, 0))
FROM employees;
```

	AVG(NVL(COMMISSION_PCT,0))
1	0.0425

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Group Functions and Null Values

All group functions ignore null values in the column.

However, the NVL function forces group functions to include null values.

### Examples:

1. The average is calculated based on *only* those rows in the table in which a valid value is stored in the COMMISSION\_PCT column. The average is calculated as the total commission that is paid to all employees divided by the number of employees receiving a commission (four).
2. The average is calculated based on *all* rows in the table, regardless of whether null values are stored in the COMMISSION\_PCT column. The average is calculated as the total commission that is paid to all employees divided by the total number of employees in the company (20).

## Lesson Agenda

- Group functions:
  - Types and syntax
  - Use AVG, SUM, MIN, MAX, COUNT
  - Use DISTINCT keyword within group functions
  - NULL values in a group function
- Grouping rows:
  - GROUP BY clause
  - HAVING clause
- Nesting group functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Creating Groups of Data

## EMPLOYEES

EMPLOYEE_ID	DEPARTMENT_ID	SALARY	AVERAGE
1	10	4400	4400
2	20	13000	9500
3	20	6000	
4	50	5800	3500
5	50	2500	
6	50	2600	
7	50	3100	
8	50	3500	
9	60	4200	6400
10	60	6000	10033
11	60	9000	
12	80	11000	
13	80	10500	10033
14	80	8600	
...			
19	110	12000	
20	(null)	7000	

Average salary in  
EMPLOYEES table for  
each department

DEPARTMENT_ID	AVG(SALARY)
10	4400
20	9500
50	3500
60	6400
80	10033.333333333333...
90	19333.333333333333...
110	10150
(null)	7000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Creating Groups of Data

Until this point in our discussion, all group functions have treated the table as one large group of information. At times, however, you need to divide the table of information into smaller groups. This can be done by using the GROUP BY clause.

## Creating Groups of Data: GROUP BY Clause Syntax

```
SELECT    column, group_function(column)
FROM      table
[WHERE    condition]
[GROUP BY group_by_expression]
[ORDER BY column];
```

You can divide rows in a table into smaller groups by using the GROUP BY clause.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Creating Groups of Data: GROUP BY Clause Syntax

You can use the GROUP BY clause to divide the rows in a table into groups. You can then use the group functions to return summary information for each group.

In the syntax:

*group\_by\_expression* specifies columns whose values determine the basis for grouping rows

#### Guidelines

- If you include a group function in a SELECT clause, you cannot select individual results as well, *unless* the individual column appears in the GROUP BY clause. You receive an error message if you fail to include the column list in the GROUP BY clause.
- Using a WHERE clause, you can exclude rows before dividing them into groups.
- You must include the *columns* in the GROUP BY clause.
- You cannot use a column alias in the GROUP BY clause.

## Using the GROUP BY Clause

All columns in the `SELECT` list that are not in group functions must be in the `GROUP BY` clause.

```
SELECT department_id, AVG(salary)
FROM employees
GROUP BY department_id ;
```

	DEPARTMENT_ID	AVG(SALARY)
1	(null)	7000
2	90	19333.33333333333...
3	20	9500
4	110	10150
5	50	3500
6	80	10033.33333333333...
7	60	6400
8	10	4400

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the GROUP BY Clause

When using the `GROUP BY` clause, make sure that all columns in the `SELECT` list that are not group functions are included in the `GROUP BY` clause. The example in the slide displays the department number and the average salary for each department. Here is how this `SELECT` statement, containing a `GROUP BY` clause, is evaluated:

- The `SELECT` clause specifies the columns to be retrieved, as follows:
  - Department number column in the `EMPLOYEES` table
  - The average of all salaries in the group that you specified in the `GROUP BY` clause
- The `FROM` clause specifies the tables that the database must access: the `EMPLOYEES` table
- The `WHERE` clause specifies the rows to be retrieved. Because there is no `WHERE` clause, all rows are retrieved by default.
- The `GROUP BY` clause specifies how the rows should be grouped. The rows are grouped by department number, so the `AVG` function that is applied to the salary column calculates the average salary for each department.

## Using the GROUP BY Clause

The GROUP BY column does not have to be in the SELECT list.

```
SELECT  AVG(salary)
FROM    employees
GROUP BY department_id ;
```

	AVG(SALARY)
1	7000
2	19333.33333333333333333333...
3	9500
4	10150
5	3500
6	10033.33333333333333333333...
7	6400
8	4400

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the GROUP BY Clause (continued)

The GROUP BY column does not have to be in the SELECT clause. For example, the SELECT statement in the slide displays the average salaries for each department without displaying the respective department numbers. Without the department numbers, however, the results do not look meaningful.

You can also use the group function in the ORDER BY clause:

```
SELECT  department_id, AVG(salary)
FROM    employees
GROUP BY department_id
ORDER BY AVG(salary) ;
```

	DEPARTMENT_ID	AVG(SALARY)
1	50	3500
2	10	4400
3	60	6400

...

7	110	10150
8	90	19333.33333333333333333333...

# Grouping by More than One Column

## EMPLOYEES

	DEPARTMENT_ID	JOB_ID	SALARY
1	10	AD_ASST	4400
2	20	MK_MAN	13000
3	20	MK_REP	6000
4	50	ST_MAN	5800
5	50	ST_CLERK	2500
6	50	ST_CLERK	2600
7	50	ST_CLERK	3100
8	50	ST_CLERK	3500
9	60	IT_PROG	4200
10	60	IT_PROG	6000
11	60	IT_PROG	9000
12	80	SA_REP	11000
13	80	SA_MAN	10500
14	80	SA_REP	8600
...			
19	110	AC_MGR	12000
20	(null)	SA_REP	7000

Add the salaries in the **EMPLOYEES** table for each job, grouped by department.

	DEPARTMENT_ID	JOB_ID	SUM(SALARY)
1	10	AD_ASST	4400
2	20	MK_MAN	13000
3	20	MK_REP	6000
4	50	ST_CLERK	11700
5	50	ST_MAN	5800
6	60	IT_PROG	19200
7	80	SA_MAN	10500
8	80	SA_REP	19600
9	90	AD_PRES	24000
10	90	AD_VP	34000
11	110	AC_ACCOUNT	8300
12	110	AC_MGR	12000
13	(null)	SA_REP	7000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Grouping by More than One Column

Sometimes, you need to see results for groups within groups. The slide shows a report that displays the total salary that is paid to each job title in each department.

The **EMPLOYEES** table is grouped first by the department number, and then by the job title within that grouping. For example, the four stock clerks in department 50 are grouped together, and a single result (total salary) is produced for all stock clerks in the group.

The following **SELECT** statement returns the result shown in the slide:

```
SELECT department_id, job_id, sum(salary)
FROM employees
GROUP BY department_id, job_id
ORDER BY job_id;
```

## Using the GROUP BY Clause on Multiple Columns

```
SELECT department_id, job_id, SUM(salary)
FROM employees
WHERE department_id > 40
GROUP BY department_id, job_id
ORDER BY department_id;
```

	DEPARTMENT_ID	JOB_ID	SUM(SALARY)
1	50	ST_CLERK	11700
2	50	ST_MAN	5800
3	60	IT_PROG	19200
4	80	SA_MAN	10500
5	80	SA_REP	19600
6	90	AD_PRES	24000
7	90	AD_VP	34000
8	110	AC_ACCOUNT	8300
9	110	AC_MGR	12000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the Group By Clause on Multiple Columns

You can return summary results for groups and subgroups by listing multiple GROUP BY columns. The GROUP BY clause groups rows but does not guarantee the order of the result set. To order the groupings, use the ORDER BY clause.

In the example in the slide, the SELECT statement that contains a GROUP BY clause is evaluated as follows:

- The SELECT clause specifies the column to be retrieved:
  - Department ID in the EMPLOYEES table
  - Job ID in the EMPLOYEES table
  - The sum of all salaries in the group that you specified in the GROUP BY clause
- The FROM clause specifies the tables that the database must access: the EMPLOYEES table.
- The WHERE clause reduces the result set to those rows where department ID is greater than 40.
- The GROUP BY clause specifies how you must group the resulting rows:
  - First, the rows are grouped by the department ID.
  - Second, the rows are grouped by job ID in the department ID groups.
- The ORDER BY clause sorts the results by department ID.

**Notes:** The SUM function is applied to the salary column for all job IDs in the result set in each department ID group. Also, note that the SA\_REP row is not returned. The department ID for this row is NULL, and therefore, does not meet the WHERE condition.

# Illegal Queries Using Group Functions

Any column or expression in the `SELECT` list that is not an aggregate function must be in the `GROUP BY` clause:

```
SELECT department_id, COUNT(last_name)
FROM employees;
```

ORA-00937: not a single-group group function  
00937.00000 - "not a single-group group function"

**A `GROUP BY` clause must be added to count the last names for each `department_id`.**

```
SELECT department_id, job_id, COUNT(last_name)
FROM employees
GROUP BY department_id;
```

ORA-00979: not a GROUP BY expression  
00979.00000 - "not a GROUP BY expression"

**Either add `job_id` in the `GROUP BY` or remove the `job_id` column from the `SELECT` list.**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Illegal Queries Using Group Functions

Whenever you use a mixture of individual items (`DEPARTMENT_ID`) and group functions (`COUNT`) in the same `SELECT` statement, you must include a `GROUP BY` clause that specifies the individual items (in this case, `DEPARTMENT_ID`). If the `GROUP BY` clause is missing, then the error message “not a single-group group function” appears and an asterisk (\*) points to the offending column. You can correct the error in the first example in the slide by adding the `GROUP BY` clause:

```
SELECT department_id, count(last_name)
FROM employees
GROUP BY department_id;
```


Any column or expression in the `SELECT` list that is not an aggregate function must be in the `GROUP BY` clause. In the second example in the slide, `job_id` is neither in the `GROUP BY` clause nor is it being used by a group function, so there is a “not a `GROUP BY` expression” error. You can correct the error in the second slide example by adding `job_id` in the `GROUP BY` clause.

```
SELECT department_id, job_id, COUNT(last_name)
FROM employees
GROUP BY department_id, job_id;
```

## Illegal Queries Using Group Functions

- You cannot use the `WHERE` clause to restrict groups.
- You use the `HAVING` clause to restrict groups.
- You cannot use group functions in the `WHERE` clause.

```
SELECT department_id, AVG(salary)
FROM employees
WHERE AVG(salary) > 8000
GROUP BY department_id;
```



**Cannot use the  
`WHERE` clause to  
restrict groups**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Illegal Queries Using Group Functions (continued)

The `WHERE` clause cannot be used to restrict groups. The `SELECT` statement in the example in the slide results in an error because it uses the `WHERE` clause to restrict the display of the average salaries of those departments that have an average salary greater than \$8,000.

However, you can correct the error in the example by using the `HAVING` clause to restrict groups:

```
SELECT department_id, AVG(salary)
FROM employees
GROUP BY department_id
HAVING AVG(salary) > 8000;
```

	DEPARTMENT_ID	AVG(SALARY)
1	90	19333.3333333333333333...
2	20	9500
3	110	10150
4	80	10033.3333333333333333...

## Restricting Group Results

### EMPLOYEES

	DEPARTMENT_ID	SALARY
1	10	4400
2	20	13000
3	20	6000
4	50	5800
5	50	2500
6	50	2600
7	50	3100
8	50	3500
9	60	4200
10	60	6000
11	60	9000
12	80	11000
13	80	10500
14	80	8600
...		
18	110	8300
19	110	12000
20	(null)	7000

The maximum salary per department when it is greater than \$10,000

	DEPARTMENT_ID	MAX(SALARY)
1	20	13000
2	80	11000
3	90	24000
4	110	12000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Restricting Group Results

You use the **HAVING** clause to restrict groups in the same way that you use the **WHERE** clause to restrict the rows that you select. To find the maximum salary in each of the departments that have a maximum salary greater than \$10,000, you need to do the following:

1. Find the average salary for each department by grouping by department number.
2. Restrict the groups to those departments with a maximum salary greater than \$10,000.

## Restricting Group Results with the HAVING Clause

When you use the HAVING clause, the Oracle server restricts groups as follows:

1. Rows are grouped.
2. The group function is applied.
3. Groups matching the HAVING clause are displayed.

```
SELECT    column, group_function
FROM      table
[WHERE    condition]
[GROUP BY group_by_expression]
[HAVING   group_condition]
[ORDER BY column];
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Restricting Group Results with the HAVING Clause

You use the HAVING clause to specify the groups that are to be displayed, thus further restricting the groups on the basis of aggregate information.

In the syntax, *group\_condition* restricts the groups of rows returned to those groups for which the specified condition is true.

The Oracle server performs the following steps when you use the HAVING clause:

1. Rows are grouped.
2. The group function is applied to the group.
3. The groups that match the criteria in the HAVING clause are displayed.

The HAVING clause can precede the GROUP BY clause, but it is recommended that you place the GROUP BY clause first because it is more logical. Groups are formed and group functions are calculated before the HAVING clause is applied to the groups in the SELECT list.

## Using the HAVING Clause

```
SELECT department_id, MAX(salary)
FROM employees
GROUP BY department_id
HAVING MAX(salary) > 10000 ;
```

	DEPARTMENT_ID	MAX(SALARY)
1	90	24000
2	20	13000
3	110	12000
4	80	11000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the HAVING Clause

The example in the slide displays the department numbers and maximum salaries for those departments with a maximum salary greater than \$10,000.

You can use the GROUP BY clause without using a group function in the SELECT list. If you restrict rows based on the result of a group function, you must have a GROUP BY clause as well as the HAVING clause.

The following example displays the department numbers and average salaries for those departments with a maximum salary greater than \$10,000:

```
SELECT department_id, AVG(salary)
FROM employees
GROUP BY department_id
HAVING max(salary) > 10000 ;
```

	DEPARTMENT_ID	AVG(SALARY)
1	90	19333.333333333333...
2	20	9500
3	110	10150
4	80	10033.333333333333...

## Using the HAVING Clause

```
SELECT  job_id, SUM(salary) PAYROLL
FROM    employees
WHERE   job_id NOT LIKE '%REP%'
GROUP BY job_id
HAVING  SUM(salary) > 13000
ORDER BY SUM(salary);
```

	JOB_ID	PAYROLL
1	IT_PROG	19200
2	AD_PRES	24000
3	AD_VP	34000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the HAVING Clause (continued)

The example in the slide displays the job ID and total monthly salary for each job that has a total payroll exceeding \$13,000. The example excludes sales representatives and sorts the list by the total monthly salary.

## Lesson Agenda

- Group functions:
  - Types and syntax
  - Use AVG, SUM, MIN, MAX, COUNT
  - Use DISTINCT keyword within group functions
  - NULL values in a group function
- Grouping rows:
  - GROUP BY clause
  - HAVING clause
- Nesting group functions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only



## Quiz

Identify the guidelines for group functions and the GROUP BY clause.

1. You cannot use a column alias in the GROUP BY clause.
2. The GROUP BY column must be in the SELECT clause.
3. By using a WHERE clause, you can exclude rows before dividing them into groups.
4. The GROUP BY clause groups rows and ensures order of the result set.
5. If you include a group function in a SELECT clause, you cannot select individual results as well.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Answer: 1, 3

## Summary

In this lesson, you should have learned how to:

- Use the group functions COUNT, MAX, MIN, SUM, and AVG
- Write queries that use the GROUP BY clause
- Write queries that use the HAVING clause

```
SELECT    column, group_function
FROM      table
[WHERE    condition]
[GROUP BY group_by_expression]
[HAVING   group_condition]
[ORDER BY column];
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Summary

There are several group functions available in SQL, such as:

AVG, COUNT, MAX, MIN, SUM, STDDEV, and VARIANCE

You can create subgroups by using the GROUP BY clause. Further, groups can be restricted using the HAVING clause.

Place the HAVING and GROUP BY clauses after the WHERE clause in a statement. The order of the GROUP BY and HAVING clauses following the WHERE clause is not important. Place the ORDER BY clause at the end.

The Oracle server evaluates the clauses in the following order:

1. If the statement contains a WHERE clause, the server establishes the candidate rows.
2. The server identifies the groups that are specified in the GROUP BY clause.
3. The HAVING clause further restricts result groups that do not meet the group criteria in the HAVING clause.

**Note:** For a complete list of the group functions, see *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

## Practice 5: Overview

This practice covers the following topics:

- Writing queries that use the group functions
- Grouping by rows to achieve more than one result
- Restricting groups by using the `HAVING` clause

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice 5: Overview

At the end of this practice, you should be familiar with using group functions and selecting groups of data.

## Practice 5

Determine the validity of the following three statements. Circle either True or False.

1. Group functions work across many rows to produce one result per group.  
True/False
2. Group functions include nulls in calculations.  
True/False
3. The WHERE clause restricts rows before inclusion in a group calculation.  
True/False

The HR department needs the following reports:

4. Find the highest, lowest, sum, and average salary of all employees. Label the columns as Maximum, Minimum, Sum, and Average, respectively. Round your results to the nearest whole number. Save your SQL statement as lab\_05\_04.sql. Run the query.

	Maximum	Minimum	Sum	Average
1	24000	2500	175500	8775

5. Modify the query in lab\_05\_04.sql to display the minimum, maximum, sum, and average salary for each job type. Resave lab\_05\_04.sql as lab\_05\_05.sql. Run the statement in lab\_05\_05.sql.

	JOB_ID	Maximum	Minimum	Sum	Average
1	IT_PROG	9000	4200	19200	6400
2	AC_MGR	12000	12000	12000	12000
3	AC_ACCOUNT	8300	8300	8300	8300
4	ST_MAN	5800	5800	5800	5800
5	AD_ASST	4400	4400	4400	4400
6	AD_VP	17000	17000	34000	17000
7	SA_MAN	10500	10500	10500	10500
8	MK_MAN	13000	13000	13000	13000
9	AD_PRES	24000	24000	24000	24000
10	SA_REP	11000	7000	26600	8867
11	MK_REP	6000	6000	6000	6000
12	ST_CLERK	3500	2500	11700	2925

**Practice 5 (continued)**

6. Write a query to display the number of people with the same job.

	JOB_ID	COUNT(*)
1	AC_ACCOUNT	1
2	AC_MGR	1
3	AD_ASST	1
4	AD_PRES	1
5	AD_VP	2
6	IT_PROG	3
7	MK_MAN	1
8	MK_REP	1
9	SA_MAN	1
10	SA_REP	3
11	ST_CLERK	4
12	ST_MAN	1

Generalize the query so that the user in the HR department is prompted for a job title. Save the script to a file named lab\_05\_06.sql. Run the query. Enter IT\_PROG when prompted.

	JOB_ID	COUNT(*)
1	IT_PROG	3

7. Determine the number of managers without listing them. Label the column as Number of Managers. *Hint: Use the MANAGER\_ID column to determine the number of managers.*

	Number of Managers
1	8

8. Find the difference between the highest and lowest salaries. Label the column DIFFERENCE.

	DIFFERENCE
1	21500

### Practice 5 (continued)

If you have time, complete the following exercises:

9. Create a report to display the manager number and the salary of the lowest-paid employee for that manager. Exclude anyone whose manager is not known. Exclude any groups where the minimum salary is \$6,000 or less. Sort the output in descending order of salary.

	MANAGER_ID	MIN(SALARY)
1	102	9000
2	205	8300
3	149	7000

If you want an extra challenge, complete the following exercises:

10. Create a query to display the total number of employees and, of that total, the number of employees hired in 1995, 1996, 1997, and 1998. Create appropriate column headings.

	TOTAL	1995	1996	1997	1998
1	20	1	2	2	3

11. Create a matrix query to display the job, the salary for that job based on department number, and the total salary for that job, for departments 20, 50, 80, and 90, giving each column an appropriate heading.

	Job	Dept 20	Dept 50	Dept 80	Dept 90	Total
1	IT_PROG	(null)	(null)	(null)	(null)	19200
2	AC_MGR	(null)	(null)	(null)	(null)	12000
3	AC_ACCOUNT	(null)	(null)	(null)	(null)	8300
4	ST_MAN	(null)	5800	(null)	(null)	5800
5	AD_ASST	(null)	(null)	(null)	(null)	4400
6	AD_VP	(null)	(null)	(null)	34000	34000
7	SA_MAN	(null)	(null)	10500	(null)	10500
8	MK_MAN	13000	(null)	(null)	(null)	13000
9	AD_PRES	(null)	(null)	(null)	24000	24000
10	SA_REP	(null)	(null)	19600	(null)	26600
11	MK_REP	6000	(null)	(null)	(null)	6000
12	ST_CLERK	(null)	11700	(null)	(null)	11700

# 6

## Displaying Data from Multiple Tables

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- Write `SELECT` statements to access data from more than one table using equijoins and nonequijoins
- Join a table to itself by using a self-join
- View data that generally does not meet a join condition by using `OUTER` joins
- Generate a Cartesian product of all rows from two or more tables

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

This lesson explains how to obtain data from more than one table. A *join* is used to view information from multiple tables. Therefore, you can *join* tables together to view information from more than one table.

**Note:** Information on joins is found in the section on *SQL Queries and Subqueries: Joins* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

## Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
  - USING clause
  - ON clause
- Self-join
- Nonequijoins
- OUTER join:
  - LEFT OUTER join
  - RIGHT OUTER join
  - FULL OUTER join
- Cartesian product
  - Cross join

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Obtaining Data from Multiple Tables

## EMPLOYEES

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
1	100	King	90
2	101	Kochhar	90
3	102	De Haan	90
...			
18	202	Fay	20
19	205	Higgins	110
20	206	Gietz	110

## DEPARTMENTS

	DEPARTMENT_ID	DEPARTMENT_NAME	LOCATION_ID
1	10	Administration	1700
2	20	Marketing	1800
3	50	Shipping	1500
4	60	IT	1400
5	80	Sales	2500
6	90	Executive	1700
7	110	Accounting	1700
8	190	Contracting	1700

	EMPLOYEE_ID	DEPARTMENT_ID	DEPARTMENT_NAME
1	200	10	Administration
2	201	20	Marketing
3	202	20	Marketing
4	124	50	Shipping
5	144	50	Shipping
...			
18	205	110	Accounting
19	206	110	Accounting

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Obtaining Data from Multiple Tables

Sometimes you need to use data from more than one table. In the example in the slide, the report displays data from two separate tables:

- Employee IDs exist in the EMPLOYEES table.
- Department IDs exist in both the EMPLOYEES and DEPARTMENTS tables.
- Department names exist in the DEPARTMENTS table.

To produce the report, you need to link the EMPLOYEES and DEPARTMENTS tables, and access data from both of them.

## Types of Joins

Joins that are compliant with the SQL:1999 standard include the following:

- **Natural joins:**
  - NATURAL JOIN clause
  - USING clause
  - ON clause
- **OUTER joins:**
  - LEFT OUTER JOIN
  - RIGHT OUTER JOIN
  - FULL OUTER JOIN
- **Cross joins**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Types of Joins

To join tables, you can use a join syntax that is compliant with the SQL:1999 standard.

#### Note

- Before the Oracle9i release, the join syntax was different from the American National Standards Institute (ANSI) standards. The SQL:1999-compliant join syntax does not offer any performance benefits over the Oracle-proprietary join syntax that existed in the prior releases. For detailed information about the proprietary join syntax, see Appendix C: Oracle Join Syntax.
- The following slide discusses the SQL:1999 join syntax.

## Joining Tables Using SQL:1999 Syntax

Use a join to query data from more than one table:

```
SELECT  table1.column, table2.column
FROM    table1
[NATURAL JOIN table2] |
[JOIN table2 USING (column_name)] |
[JOIN table2
  ON (table1.column_name = table2.column_name)] |
[LEFT|RIGHT|FULL OUTER JOIN table2
  ON (table1.column_name = table2.column_name)] |
[CROSS JOIN table2];
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Joining Tables Using SQL:1999 Syntax

In the syntax:

*table1.column* denotes the table and the column from which data is retrieved

NATURAL JOIN joins two tables based on the same column name

JOIN *table2* USING *column\_name* performs an equijoin based on the column name

JOIN *table2* ON *table1.column\_name* = *table2.column\_name* performs an equijoin based on the condition in the ON clause

LEFT/RIGHT/FULL OUTER is used to perform OUTER joins

CROSS JOIN returns a Cartesian product from the two tables

For more information, see the section titled *SELECT* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

## Qualifying Ambiguous Column Names

- Use table prefixes to qualify column names that are in multiple tables.
- Use table prefixes to improve performance.
- Instead of full table name prefixes, use table aliases.
- Table alias gives a table a shorter name:
  - Keeps SQL code smaller, uses less memory
- Use column aliases to distinguish columns that have identical names, but reside in different tables.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Qualifying Ambiguous Column Names

When joining two or more tables, you need to qualify the names of the columns with the table name to avoid ambiguity. Without the table prefixes, the `DEPARTMENT_ID` column in the `SELECT` list could be from either the `DEPARTMENTS` table or the `EMPLOYEES` table. It is necessary to add the table prefix to execute your query. If there are no common column names between the two tables, there is no need to qualify the columns. However, using the table prefix improves performance, because you tell the Oracle server exactly where to find the columns.

However, qualifying column names with table names can be time consuming, particularly if the table names are lengthy. Instead, you can use *table aliases*. Just as a column alias gives a column another name, a table alias gives a table another name. Table aliases help to keep SQL code smaller, therefore using less memory.

The table name is specified in full, followed by a space and then the table alias. For example, the `EMPLOYEES` table can be given an alias of `e`, and the `DEPARTMENTS` table an alias of `d`.

#### Guidelines

- Table aliases can be up to 30 characters in length, but shorter aliases are better than longer ones.
- If a table alias is used for a particular table name in the `FROM` clause, then that table alias must be substituted for the table name throughout the `SELECT` statement.
  - Table aliases should be meaningful.
  - The table alias is valid for only the current `SELECT` statement.

## Lesson Agenda

- Types of JOINS and its syntax
- **Natural join:**
  - USING clause
  - ON clause
- Self-join
- Nonequijoins
- OUTER join:
  - LEFT OUTER join
  - RIGHT OUTER join
  - FULL OUTER join
- Cartesian product
  - Cross join

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Creating Natural Joins

- The `NATURAL JOIN` clause is based on all columns in the two tables that have the same name.
- It selects rows from the two tables that have equal values in all matched columns.
- If the columns having the same names have different data types, an error is returned.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Creating Natural Joins

You can join tables automatically based on the columns in the two tables that have matching data types and names. You do this by using the `NATURAL JOIN` keywords.

**Note:** The join can happen on only those columns that have the same names and data types in both tables. If the columns have the same name but different data types, then the `NATURAL JOIN` syntax causes an error.

## Retrieving Records with Natural Joins

```
SELECT department_id, department_name,  
       location_id, city  
FROM   departments  
NATURAL JOIN locations ;
```

	DEPARTMENT_ID	DEPARTMENT_NAME	LOCATION_ID	CITY
1	60	IT	1400	Southlake
2	50	Shipping	1500	South San Francisco
3	10	Administration	1700	Seattle
4	90	Executive	1700	Seattle
5	110	Accounting	1700	Seattle
6	190	Contracting	1700	Seattle
7	20	Marketing	1800	Toronto
8	80	Sales	2500	Oxford

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Retrieving Records with Natural Joins

In the example in the slide, the LOCATIONS table is joined to the DEPARTMENT table by the LOCATION\_ID column, which is the only column of the same name in both tables. If other common columns were present, the join would have used them all.

#### Natural Joins with a WHERE Clause

Additional restrictions on a natural join are implemented by using a WHERE clause. The following example limits the rows of output to those with a department ID equal to 20 or 50:

```
SELECT department_id, department_name,  
       location_id, city  
FROM   departments  
NATURAL JOIN locations  
WHERE  department_id IN (20, 50);
```

## Creating Joins with the USING Clause

- If several columns have the same names but the data types do not match, use the `USING` clause to specify the columns for the equijoin.
- Use the `USING` clause to match only one column when more than one column matches.
- The `NATURAL JOIN` and `USING` clauses are mutually exclusive.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Creating Joins with the USING Clause

Natural joins use all columns with matching names and data types to join the tables. The `USING` clause can be used to specify only those columns that should be used for an equijoin.

# Joining Column Names

**EMPLOYEES**

EMPLOYEE_ID	DEPARTMENT_ID
100	90
101	90
102	90
103	60
104	60
107	60
124	50
141	50
142	50
143	50
144	50
149	80
174	80
176	80
...	...

**DEPARTMENTS**

DEPARTMENT_ID	DEPARTMENT_NAME
1	10 Administration
2	20 Marketing
3	50 Shipping
4	60 IT
5	80 Sales
6	90 Executive
7	110 Accounting
8	190 Contracting

...

**Foreign key**

**Primary key**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Joining Column Names

To determine an employee's department name, you compare the value in the DEPARTMENT\_ID column in the EMPLOYEES table with the DEPARTMENT\_ID values in the DEPARTMENTS table. The relationship between the EMPLOYEES and DEPARTMENTS tables is an *equijoin*; that is, values in the DEPARTMENT\_ID column in both the tables must be equal. Frequently, this type of join involves primary and foreign key complements.

**Note:** Equijoins are also called *simple joins* or *inner joins*.

## Retrieving Records with the USING Clause

```
SELECT employee_id, last_name,  
       location_id, department_id  
FROM   employees JOIN departments  
USING (department_id) ;
```

	EMPLOYEE_ID	LAST_NAME	LOCATION_ID	DEPARTMENT_ID
1	200	Whalen	1700	10
2	201	Hartstein	1800	20
3	202	Fay	1800	20
4	124	Mourgos	1500	50
5	144	Vargas	1500	50
6	143	Matos	1500	50
7	142	Davies	1500	50
8	141	Rajs	1500	50
9	107	Lorentz	1400	60
10	104	Ernst	1400	60
...				
19	205	Higgins	1700	110

ORACLE

Copyright © 2009, Oracle. All rights reserved.


### Retrieving Records with the USING Clause

In the example in the slide, the DEPARTMENT\_ID columns in the EMPLOYEES and DEPARTMENTS tables are joined and thus the LOCATION\_ID of the department where an employee works is shown.

## Using Table Aliases with the USING Clause

- Do not qualify a column that is used in the USING clause.
- If the same column is used elsewhere in the SQL statement, do not alias it.

```
SELECT l.city, d.department_name
FROM   locations l JOIN departments d
USING (location_id)
WHERE  d.location_id = 1400;
```



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using Table Aliases with the USING clause

When joining with the USING clause, you cannot qualify a column that is used in the USING clause itself. Furthermore, if that column is used anywhere in the SQL statement, you cannot alias it. For example, in the query mentioned in the slide, you should not alias the `location_id` column in the WHERE clause because the column is used in the USING clause.

The columns that are referenced in the USING clause should not have a qualifier (table name or alias) anywhere in the SQL statement. For example, the following statement is valid:

```
SELECT l.city, d.department_name
FROM   locations l JOIN departments d USING (location_id)
WHERE  location_id = 1400;
```

Because, other columns that are common in both the tables, but not used in the USING clause, must be prefixed with a table alias otherwise you get the “column ambiguously defined” error.

In the following statement, `manager_id` is present in both the `employees` and `departments` table and if `manager_id` is not prefixed with a table alias, it gives a “column ambiguously defined” error.

The following statement is valid:

```
SELECT first_name, d.department_name, d.manager_id
FROM   employees e JOIN departments d USING (department_id)
WHERE  department_id = 50;
```

## Creating Joins with the ON Clause

- The join condition for the natural join is basically an equijoin of all columns with the same name.
- Use the ON clause to specify arbitrary conditions or specify columns to join.
- The join condition is separated from other search conditions.
- The ON clause makes code easy to understand.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Creating Joins with the ON Clause

Use the ON clause to specify a join condition. With this, you can specify join conditions separate from any search or filter conditions in the WHERE clause.

## Retrieving Records with the ON Clause

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.location_id  
FROM   employees e JOIN departments d  
ON     (e.department_id = d.department_id);
```

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_ID_1	LOCATION_ID
1	200	Whalen	10	10	1700
2	201	Hartstein	20	20	1800
3	202	Fay	20	20	1800
4	124	Mourgos	50	50	1500
5	144	Vargas	50	50	1500
6	143	Matos	50	50	1500
7	142	Davies	50	50	1500
8	141	Rajs	50	50	1500
9	107	Lorentz	60	60	1400
10	104	Ernst	60	60	1400

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Retrieving Records with the ON Clause

In this example, the DEPARTMENT\_ID columns in the EMPLOYEES and DEPARTMENTS table are joined using the ON clause. Wherever a department ID in the EMPLOYEES table equals a department ID in the DEPARTMENTS table, the row is returned. The table alias is necessary to qualify the matching column\_names.

You can also use the ON clause to join columns that have different names. The parenthesis around the joined columns as in the slide example, (e.department\_id = d.department\_id) is optional. So, even ON e.department\_id = d.department\_id will work.

**Note:** SQL Developer suffixes a '\_1' to differentiate between the two department\_ids.

## Creating Three-Way Joins with the ON Clause

```
SELECT employee_id, city, department_name
FROM employees e
JOIN departments d
ON d.department_id = e.department_id
JOIN locations l
ON d.location_id = l.location_id;
```

	EMPLOYEE_ID	CITY	DEPARTMENT_NAME
1	100	Seattle	Executive
2	101	Seattle	Executive
3	102	Seattle	Executive
4	103	Southlake	IT
5	104	Southlake	IT
6	107	Southlake	IT
7	124	South San Francisco	Shipping
8	141	South San Francisco	Shipping

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Creating Three-Way Joins with the ON Clause

A three-way join is a join of three tables. In SQL:1999-compliant syntax, joins are performed from left to right. So, the first join to be performed is EMPLOYEES JOIN DEPARTMENTS. The first join condition can reference columns in EMPLOYEES and DEPARTMENTS but cannot reference columns in LOCATIONS. The second join condition can reference columns from all three tables.

**Note:** The code example in the slide can also be accomplished with the USING clause:

```
SELECT e.employee_id, l.city, d.department_name
FROM employees e
JOIN departments d
USING (department_id)
JOIN locations l
USING (location_id)
```

## Applying Additional Conditions to a Join

Use the `AND` clause or the `WHERE` clause to apply additional conditions:

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.location_id  
FROM   employees e JOIN departments d  
ON     (e.department_id = d.department_id)  
AND    e.manager_id = 149 ;
```

Or

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.location_id  
FROM   employees e JOIN departments d  
ON     (e.department_id = d.department_id)  
WHERE  e.manager_id = 149 ;
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Applying Additional Conditions to a Join

You can apply additional conditions to the join.

The example shown performs a join on the `EMPLOYEES` and `DEPARTMENTS` tables and, in addition, displays only employees who have a manager ID of 149. To add additional conditions to the `ON` clause, you can add `AND` clauses. Alternatively, you can use a `WHERE` clause to apply additional conditions.

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_ID_1	LOCATION_ID
1	174	Abel	80	80	2500
2	176	Taylor	80	80	2500

## Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
  - USING clause
  - ON clause
- **Self-join**
- Nonequijoins
- OUTER join:
  - LEFT OUTER join
  - RIGHT OUTER join
  - FULL OUTER join
- Cartesian product
  - Cross join

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Joining a Table to Itself

**EMPLOYEES (WORKER)**

EMPLOYEE_ID	LAST_NAME	MANAGER_ID
1	100 King	(null)
2	101 Kochhar	100
3	102 De Haan	100
4	103 Hunold	102
5	104 Ernst	103
6	107 Lorentz	103
7	124 Mourgos	100
8	141 Rajs	124
9	142 Davies	124
10	143 Matos	124

...

**EMPLOYEES (MANAGER)**

EMPLOYEE_ID	LAST_NAME
100	King
101	Kochhar
102	De Haan
103	Hunold
104	Ernst
107	Lorentz
124	Mourgos
141	Rajs
142	Davies
143	Matos

...

**MANAGER\_ID in the WORKER table is equal to  
EMPLOYEE\_ID in the MANAGER table.**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Joining a Table to Itself

Sometimes you need to join a table to itself. To find the name of each employee's manager, you need to join the EMPLOYEES table to itself, or perform a self-join. For example, to find the name of Lorentz's manager, you need to:

- Find Lorentz in the EMPLOYEES table by looking at the LAST\_NAME column
- Find the manager number for Lorentz by looking at the MANAGER\_ID column. Lorentz's manager number is 103.
- Find the name of the manager with EMPLOYEE\_ID 103 by looking at the LAST\_NAME column. Hunold's employee number is 103, so Hunold is Lorentz's manager.

In this process, you look in the table twice. The first time you look in the table to find Lorentz in the LAST\_NAME column and the MANAGER\_ID value of 103. The second time you look in the EMPLOYEE\_ID column to find 103 and the LAST\_NAME column to find Hunold.

## Self-Joins Using the ON Clause

```
SELECT worker.last_name emp, manager.last_name mgr
FROM   employees worker JOIN employees manager
ON     (worker.manager_id = manager.employee_id);
```

EMP	MGR
1 Hunold	De Haan
2 Fay	Hartstein
3 Gietz	Higgins
4 Lorentz	Hunold
5 Ernst	Hunold
6 Zlotkey	King
7 Mourgos	King
8 Kochhar	King
9 Hartstein	King
10 De Haan	King

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Self-Joins Using the ON Clause

The ON clause can also be used to join columns that have different names, within the same table or in a different table.

The example shown is a self-join of the EMPLOYEES table, based on the EMPLOYEE\_ID and MANAGER\_ID columns.

**Note:** The parenthesis around the joined columns as in the slide example, (e.manager\_id = m.employee\_id) is **optional**. So, even ON e.manager\_id = m.employee\_id will work.

## Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
  - USING clause
  - ON clause
- Self-join
- **Nonequijoins**
- OUTER join:
  - LEFT OUTER join
  - RIGHT OUTER join
  - FULL OUTER join
- Cartesian product
  - Cross join

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Nonequijoins

**EMPLOYEES**

	LAST_NAME	SALARY
1	King	24000
2	Kochhar	17000
3	De Haan	17000
4	Hunold	9000
5	Ernst	6000
6	Lorentz	4200
7	Mourgos	5800
8	Rajs	3500
9	Davies	3100
10	Matos	2600
...		
19	Higgins	12000
20	Gietz	8300

**JOB\_GRADES**

	GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
1	A	1000	2999
2	B	3000	5999
3	C	6000	9999
4	D	10000	14999
5	E	15000	24999
6	F	25000	40000

**JOB\_GRADES table defines the LOWEST\_SAL and HIGHEST\_SAL range of values for each GRADE\_LEVEL. Hence, the GRADE\_LEVEL column can be used to assign grades to each employee.**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Nonequijoins

A nonequijoin is a join condition containing something other than an equality operator.

The relationship between the EMPLOYEES table and the JOB\_GRADES table is an example of a nonequijoin. The SALARY column in the EMPLOYEES table ranges between the values in the LOWEST\_SAL and HIGHEST\_SAL columns of the JOB\_GRADES table. Therefore, each employee can be graded based on their salary. The relationship is obtained using an operator other than the equality (=) operator.

## Retrieving Records with Nonequijoins

```
SELECT e.last_name, e.salary, j.grade_level
FROM   employees e JOIN job_grades j
ON     e.salary
      BETWEEN j.lowest_sal AND j.highest_sal;
```

	LAST_NAME	SALARY	GRADE_LEVEL
1	Vargas	2500	A
2	Matos	2600	A
3	Davies	3100	B
4	Rajs	3500	B
5	Lorentz	4200	B
6	Whalen	4400	B
7	Mourgos	5800	B
8	Ernst	6000	C
9	Fay	6000	C
10	Grant	7000	C

...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Retrieving Records with Nonequijoins

The slide example creates a nonequijoin to evaluate an employee's salary grade. The salary must be *between* any pair of the low and high salary ranges.

It is important to note that all employees appear exactly once when this query is executed. No employee is repeated in the list. There are two reasons for this:

- None of the rows in the JOB\_GRADES table contain grades that overlap. That is, the salary value for an employee can lie only between the low salary and high salary values of one of the rows in the salary grade table.
- All of the employees' salaries lie within the limits provided by the job grade table. That is, no employee earns less than the lowest value contained in the LOWEST\_SAL column or more than the highest value contained in the HIGHEST\_SAL column.

**Note:** Other conditions (such as  $\leq$  and  $\geq$ ) can be used, but BETWEEN is the simplest. Remember to specify the low value first and the high value last when using the BETWEEN condition. The Oracle server translates the BETWEEN condition to a pair of AND conditions. Therefore, using BETWEEN has no performance benefits, but should be used only for logical simplicity.

Table aliases have been specified in the slide example for performance reasons, not because of possible ambiguity.

## Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
  - USING clause
  - ON clause
- Self-join
- Nonequijoins
- OUTER join:
  - LEFT OUTER join
  - RIGHT OUTER join
  - FULL OUTER join
- Cartesian product
  - Cross join

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Returning Records with No Direct Match Using OUTER Joins

**DEPARTMENTS**

DEPARTMENT_NAME	DEPARTMENT_ID
Administration	10
Marketing	20
Shipping	50
IT	60
Sales	80
Executive	90
Accounting	110
Contracting	190

**There are no employees in department 190.**

**Employee "Grant" has not been assigned a department ID.**

**Equijoin with EMPLOYEES**

DEPARTMENT_ID	LAST_NAME
1	90 King
2	90 Kochhar
3	90 De Haan
4	60 Hunold
5	60 Ernst
6	60 Lorentz
7	50 Mourgos
8	50 Rajs
9	50 Davies
10	50 Matos
...	
18	110 Higgins
19	110 Gietz

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Returning Records with No Direct Match Using OUTER Joins

If a row does not satisfy a join condition, the row does not appear in the query result.

In the slide example, a simple equijoin condition is used on the EMPLOYEES and DEPARTMENTS tables to return the result on the right. The result set does not contain the following:

- Department ID 190, because there are no employees with that department ID recorded in the EMPLOYEES table
- The employee with the last name of Grant, because this employee has not been assigned a department ID

To return the department record that does not have any employees, or employees that do not have an assigned department, you can use an OUTER join.

## INNER Versus OUTER Joins

- In SQL:1999, the join of two tables returning only matched rows is called an `INNER` join.
- A join between two tables that returns the results of the `INNER` join as well as the unmatched rows from the left (or right) table is called a left (or right) `OUTER` join.
- A join between two tables that returns the results of an `INNER` join as well as the results of a left and right join is a `full OUTER` join.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### INNER Versus OUTER Joins

Joining tables with the `NATURAL JOIN`, `USING`, or `ON` clauses results in an `INNER` join. Any unmatched rows are not displayed in the output. To return the unmatched rows, you can use an `OUTER` join. An `OUTER` join returns all rows that satisfy the join condition and also returns some or all of those rows from one table for which no rows from the other table satisfy the join condition.

There are three types of `OUTER` joins:

- `LEFT OUTER`
- `RIGHT OUTER`
- `FULL OUTER`

## LEFT OUTER JOIN

```
SELECT e.last_name, e.department_id, d.department_name
FROM   employees e LEFT OUTER JOIN departments d
ON     (e.department_id = d.department_id) ;
```

	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
1	Whalen	10	Administration
2	Fay	20	Marketing
3	Hartstein	20	Marketing
4	Vargas	50	Shipping
5	Matos	50	Shipping

...

17	King	90	Executive
18	Gietz	110	Accounting
19	Higgins	110	Accounting
20	Grant	(null)	(null)

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### LEFT OUTER JOIN

This query retrieves all the rows in the EMPLOYEES table, which is the left table, even if there is no match in the DEPARTMENTS table.

## RIGHT OUTER JOIN

```
SELECT e.last_name, d.department_id, d.department_name
FROM   employees e RIGHT OUTER JOIN departments d
ON     (e.department_id = d.department_id) ;
```

	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
1	Whalen	10	Administration
2	Hartstein	20	Marketing
3	Fay	20	Marketing
4	Mourgos	50	Shipping
...			
18	Gietz	110	Accounting
19	Higgins	110	Accounting
20	(null)	190	Contracting

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### RIGHT OUTER JOIN

This query retrieves all the rows in the DEPARTMENTS table, which is the table at the right, even if there is no match in the EMPLOYEES table.

## FULL OUTER JOIN

```
SELECT e.last_name, d.department_id, d.department_name
FROM   employees e FULL OUTER JOIN departments d
ON     (e.department_id = d.department_id) ;
```

	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
1	King	90	Executive
2	Kochhar	90	Executive
3	De Haan	90	Executive
4	Hunold	60	IT

...

15	Grant	(null)	(null)
16	Whalen	10	Administration
17	Hartstein	20	Marketing
18	Fay	20	Marketing
19	Higgins	110	Accounting
20	Gietz	110	Accounting
21	(null)	190	Contracting

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### FULL OUTER JOIN

This query retrieves all rows in the EMPLOYEES table, even if there is no match in the DEPARTMENTS table. It also retrieves all rows in the DEPARTMENTS table, even if there is no match in the EMPLOYEES table.

## Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
  - USING clause
  - ON clause
- Self-join
- Nonequijoin
- OUTER join:
  - LEFT OUTER join
  - RIGHT OUTER join
  - FULL OUTER join
- Cartesian product
  - Cross join

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Cartesian Products

- A Cartesian product is formed when:
  - A join condition is omitted
  - A join condition is invalid
  - All rows in the first table are joined to all rows in the second table
- To avoid a Cartesian product, always include a valid join condition.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Cartesian Products

When a join condition is invalid or omitted completely, the result is a *Cartesian product*, in which all combinations of rows are displayed. All rows in the first table are joined to all rows in the second table.

A Cartesian product tends to generate a large number of rows and the result is rarely useful. You should, therefore, always include a valid join condition unless you have a specific need to combine all rows from all tables.

However, Cartesian products are useful for some tests when you need to generate a large number of rows to simulate a reasonable amount of data.

# Generating a Cartesian Product

## EMPLOYEES (20 rows)

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
1	King	90
2	Kochhar	90
3	De Haan	90
4	Hunold	60
...		
19	Higgins	110
20	Gietz	110

## DEPARTMENTS (8 rows)

DEPARTMENT_ID	DEPARTMENT_NAME	LOCATION_ID
1	Administration	1700
2	Marketing	1800
3	Shipping	1500
4	IT	1400
5	Sales	2500
6	Executive	1700
7	Accounting	1700
8	Contracting	1700

**Cartesian product:**  
**20 x 8 = 160 rows**

EMPLOYEE_ID	DEPARTMENT_ID	LOCATION_ID
1	90	1700
2	90	1700
3	90	1700
4	60	1700
...		
159	110	1700
160	110	1700

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Generating a Cartesian Product

A Cartesian product is generated if a join condition is omitted. The example in the slide displays the employee last name and the department name from the EMPLOYEES and DEPARTMENTS tables. Because no join condition was specified, all rows (20 rows) from the EMPLOYEES table are joined with all rows (8 rows) in the DEPARTMENTS table, thereby generating 160 rows in the output.

## Creating Cross Joins

- The `CROSS JOIN` clause produces the cross-product of two tables.
- This is also called a Cartesian product between the two tables.

```
SELECT last_name, department_name
FROM employees
CROSS JOIN departments ;
```

	LAST_NAME	DEPARTMENT_NAME
1	Abel	Administration
2	Davies	Administration
3	De Haan	Administration
4	Ernst	Administration
5	Fay	Administration
...		
159	Whalen	Contracting
160	Zlotkey	Contracting

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Creating Cross Joins

The example in the slide produces a Cartesian product of the `EMPLOYEES` and `DEPARTMENTS` tables.

## Quiz

The SQL:1999 standard join syntax supports the following types of joins. Which of these join types does Oracle join syntax support?

1. Equijoins
2. Nonequijoins
3. Left OUTER join
4. Right OUTER join
5. Full OUTER join
6. Self joins
7. Natural joins
8. Cartesian products

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Answer: 1, 2, 3, 4, 6, 8

## Summary

In this lesson, you should have learned how to use joins to display data from multiple tables by using:

- Equijoins
- Nonequijoins
- OUTER joins
- Self-joins
- Cross joins
- Natural joins
- Full (or two-sided) OUTER joins

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Summary

There are multiple ways to join tables.

#### Types of Joins

- Equijoins
- Nonequijoins
- OUTER joins
- Self-joins
- Cross joins
- Natural joins
- Full (or two-sided) OUTER joins

#### Cartesian Products

A Cartesian product results in the display of all combinations of rows. This is done by either omitting the WHERE clause or by specifying the CROSS JOIN clause.

#### Table Aliases

- Table aliases speed up database access.
- Table aliases can help to keep SQL code smaller by conserving memory.
- Table aliases are sometimes mandatory to avoid column ambiguity.

## Practice 6: Overview

This practice covers the following topics:

- Joining tables using an equijoin
- Performing outer and self-joins
- Adding conditions

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice 6: Overview

This practice is intended to give you experience in extracting data from more than one table using the SQL:1999-compliant joins.

## Practice 6

1. Write a query for the HR department to produce the addresses of all the departments. Use the LOCATIONS and COUNTRIES tables. Show the location ID, street address, city, state or province, and country in the output. Use a NATURAL JOIN to produce the results.

LOCATION_ID	STREET_ADDRESS	CITY	STATE_PROVINCE	COUNTRY_NAME
1	1400 2014 Jabberwocky Rd	Southlake	Texas	United States of America
2	1500 2011 Interiors Blvd	South San Francisco	California	United States of America
3	1700 2004 Charade Rd	Seattle	Washington	United States of America
4	1800 460 Bloor St. W.	Toronto	Ontario	Canada
5	2500 Magdalen Centre, The ...	Oxford	Oxford	United Kingdom

2. The HR department needs a report of all employees. Write a query to display the last name, department number, and department name for all the employees.

LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
1 Whalen	10	Administration
2 Hartstein	20	Marketing
3 Fay	20	Marketing
4 Davies	50	Shipping
5 Vargas	50	Shipping
6 Rajs	50	Shipping
7 Mourgos	50	Shipping
8 Matos	50	Shipping
9 Hunold	60	IT
10 Ernst	60	IT

...

18 Higgins	110	Accounting
19 Gietz	110	Accounting

### Practice 6 (continued)

3. The HR department needs a report of employees in Toronto. Display the last name, job, department number, and the department name for all employees who work in Toronto.

	LAST_NAME	JOB_ID	DEPARTMENT_ID	DEPARTMENT_NAME
1	Hartstein	MK_MAN	20	Marketing
2	Fay	MK_REP	20	Marketing

4. Create a report to display employees' last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, respectively. Save your SQL statement as lab\_06\_04.sql. Run the query.

	Employee	EMP#	Manager	Mgr#
1	Kochhar	101	King	100
2	De Haan	102	King	100
3	Hunold	103	De Haan	102
4	Ernst	104	Hunold	103
5	Lorentz	107	Hunold	103
6	Mourgos	124	King	100
7	Rajs	141	Mourgos	124
8	Davies	142	Mourgos	124
9	Matos	143	Mourgos	124
10	Vargas	144	Mourgos	124

...

15	Whalen	200	Kochhar	101
16	Hartstein	201	King	100
17	Fay	202	Hartstein	201
18	Higgins	205	Kochhar	101
19	Gietz	206	Higgins	205

### Practice 6 (continued)

- Modify `lab_06_04.sql` to display all employees including King, who has no manager. Order the results by the employee number. Save your SQL statement as `lab_06_05.sql`. Run the query in `lab_06_05.sql`.

	Employee	EMP#	Manager	Mgr#
1	King	100	(null)	(null)
2	Kochhar	101	King	100
3	De Haan	102	King	100
4	Hunold	103	De Haan	102
5	Ernst	104	Hunold	103
6	Lorentz	107	Hunold	103
7	Mourgos	124	King	100
8	Rajs	141	Mourgos	124
9	Davies	142	Mourgos	124
10	Matos	143	Mourgos	124

...

18	Fay	202	Hartstein	201
19	Higgins	205	Kochhar	101
20	Gietz	206	Higgins	205

- Create a report for the HR department that displays employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label. Save the script to a file named `lab_06_06.sql`.

	DEPARTMENT	EMPLOYEE	COLLEAGUE
1	20	Fay	Hartstein
2	20	Hartstein	Fay
3	50	Davies	Matos
4	50	Davies	Mourgos
5	50	Davies	Rajs
6	50	Davies	Vargas
7	50	Matos	Davies
8	50	Matos	Mourgos
9	50	Matos	Rajs
10	50	Matos	Vargas

...

42	110	Higgins	Gietz
----	-----	---------	-------

**Practice 6 (continued)**

- The HR department needs a report on job grades and salaries. To familiarize yourself with the JOB\_GRADES table, first show the structure of the JOB\_GRADES table. Then create a query that displays the name, job, department name, salary, and grade for all employees.

```
DESC JOB_GRADES
Name                               Null    Type
-----
GRADE_LEVEL                        VARCHA2(3)
LOWEST_SAL                          NUMBER
HIGHEST_SAL                         NUMBER

3 rows selected
```

	A2	LAST_NAME	A2	JOB_ID	A2	DEPARTMENT_NAME	A2	SALARY	A2	GRADE_LEVEL
1		Vargas		ST_CLERK		Shipping		2500		A
2		Matos		ST_CLERK		Shipping		2600		A
3		Davies		ST_CLERK		Shipping		3100		B
4		Rajs		ST_CLERK		Shipping		3500		B
5		Lorentz		IT_PROG		IT		4200		B
6		Whalen		AD_ASST		Administration		4400		B
7		Mourgos		ST_MAN		Shipping		5800		B
8		Ernst		IT_PROG		IT		6000		C
9		Fay		MK_REP		Marketing		6000		C
10		Gietz		AC_ACCOUNT		Accounting		8300		C

...

18		De Haan		AD_VP		Executive		17000		E
19		King		AD_PRES		Executive		24000		E

### Practice 6 (continued)

If you want an extra challenge, complete the following exercises:

- The HR department wants to determine the names of all the employees who were hired after Davies. Create a query to display the name and hire date of any employee hired after employee Davies.

	LAST_NAME	HIRE_DATE
1	Lorentz	07-FEB-99
2	Mourgos	16-NOV-99
3	Matos	15-MAR-98
4	Vargas	09-JUL-98
5	Zlotkey	29-JAN-00
6	Taylor	24-MAR-98
7	Grant	24-MAY-99
8	Fay	17-AUG-97

- The HR department needs to find the names and hire dates of all the employees who were hired before their managers, along with their managers' names and hire dates. Save the script to a file named `lab_06_09.sql`.

	LAST_NAME	HIRE_DATE	LAST_NAME_1	HIRE_DATE_1
1	Whalen	17-SEP-87	Kochhar	21-SEP-89
2	Hunold	03-JAN-90	De Haan	13-JAN-93
3	Vargas	09-JUL-98	Mourgos	16-NOV-99
4	Matos	15-MAR-98	Mourgos	16-NOV-99
5	Davies	29-JAN-97	Mourgos	16-NOV-99
6	Rajs	17-OCT-95	Mourgos	16-NOV-99
7	Grant	24-MAY-99	Zlotkey	29-JAN-00
8	Taylor	24-MAR-98	Zlotkey	29-JAN-00
9	Abel	11-MAY-96	Zlotkey	29-JAN-00

# 7

## Using Subqueries to Solve Queries

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- Define subqueries
- Describe the types of problems that the subqueries can solve
- List the types of subqueries
- Write single-row and multiple-row subqueries

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

In this lesson, you learn about the more advanced features of the `SELECT` statement. You can write subqueries in the `WHERE` clause of another SQL statement to obtain values based on an unknown conditional value. This lesson also covers single-row subqueries and multiple-row subqueries.

## Lesson Agenda

- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
  - Group functions in a subquery
  - HAVING clause with subqueries
- Multiple-row subqueries
  - Use ALL or ANY operator.
- Null values in a subquery


ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Using a Subquery to Solve a Problem

Who has a salary greater than Abel's?



ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using a Subquery to Solve a Problem

Suppose you want to write a query to find out who earns a salary greater than Abel's salary.

To solve this problem, you need *two* queries: one to find how much Abel earns, and a second query to find who earns more than that amount.

You can solve this problem by combining the two queries, placing one query *inside* the other query.

The inner query (or *subquery*) returns a value that is used by the outer query (or *main query*). Using a subquery is equivalent to performing two sequential queries and using the result of the first query as the search value in the second query.

## Subquery Syntax

```
SELECT    select_list
FROM      table
WHERE     expr operator
          (SELECT    select_list
           FROM      table);
```

- The subquery (inner query) executes *before* the main query (outer query).
- The result of the subquery is used by the main query.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Subquery Syntax

A subquery is a `SELECT` statement that is embedded in the clause of another `SELECT` statement. You can build powerful statements out of simple ones by using subqueries. They can be very useful when you need to select rows from a table with a condition that depends on the data in the table itself.

You can place the subquery in a number of SQL clauses, including the following:

- `WHERE` clause
- `HAVING` clause
- `FROM` clause

In the syntax:

*operator* includes a comparison condition such as `>`, `=`, or `IN`

**Note:** Comparison conditions fall into two classes: single-row operators (`>`, `=`, `>=`, `<`, `<>`, `<=`) and multiple-row operators (`IN`, `ANY`, `ALL`).

The subquery is often referred to as a nested `SELECT`, sub-`SELECT`, or inner `SELECT` statement. The subquery generally executes first, and its output is used to complete the query condition for the main (or outer) query.

## Using a Subquery

```
SELECT last_name, salary
FROM employees
WHERE salary > 11000
      (SELECT salary
        FROM employees
        WHERE last_name = 'Abel');
```

	LAST_NAME	SALARY
1	King	24000
2	Kochhar	17000
3	De Haan	17000
4	Hartstein	13000
5	Higgins	12000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using a Subquery

In the slide, the inner query determines the salary of employee Abel. The outer query takes the result of the inner query and uses this result to display all the employees who earn more than employee Abel.

## Guidelines for Using Subqueries

- Enclose subqueries in parentheses.
- Place subqueries on the right side of the comparison condition for readability (However, the subquery can appear on either side of the comparison operator.).
- Use single-row operators with single-row subqueries and multiple-row operators with multiple-row subqueries.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Guidelines for Using Subqueries

- A subquery must be enclosed in parentheses.
- Place the subquery on the right side of the comparison condition for readability. However, the subquery can appear on either side of the comparison operator.
- Two classes of comparison conditions are used in subqueries: single-row operators and multiple-row operators.

## Types of Subqueries

- Single-row subquery



- Multiple-row subquery



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Types of Subqueries

- **Single-row subqueries:** Queries that return only one row from the inner SELECT statement
- **Multiple-row subqueries:** Queries that return more than one row from the inner SELECT statement

**Note:** There are also multiple-column subqueries, which are queries that return more than one column from the inner SELECT statement. These are covered in the *Oracle Database 11g: SQL Fundamentals II* course.

## Lesson Agenda

- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
  - Group functions in a subquery
  - HAVING clause with subqueries
- Multiple-row subqueries
  - Use ALL or ANY operator
- Null values in a subquery

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# Single-Row Subqueries

- Return only one row
- Use single-row comparison operators

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<>	Not equal to

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Single-Row Subqueries

A single-row subquery is one that returns one row from the inner `SELECT` statement. This type of subquery uses a single-row operator. The slide gives a list of single-row operators.

### Example:

Display the employees whose job ID is the same as that of employee 141:

```
SELECT last_name, job_id
FROM employees
WHERE job_id =
      (SELECT job_id
       FROM employees
       WHERE employee_id = 141);
```

	LAST_NAME	JOB_ID
1	Rajs	ST_CLERK
2	Davies	ST_CLERK
3	Matos	ST_CLERK
4	Vargas	ST_CLERK

## Executing Single-Row Subqueries

```
SELECT last_name, job_id, salary
FROM employees
WHERE job_id = SA_REP
AND salary > 8600
      (SELECT job_id
       FROM employees
       WHERE last_name = 'Taylor')
      (SELECT salary
       FROM employees
       WHERE last name = 'Taylor');
```

	LAST_NAME	JOB_ID	SALARY
1	Abel	SA_REP	11000

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Executing Single-Row Subqueries

A SELECT statement can be considered as a query block. The example in the slide displays employees who do the same job as “Taylor,” but earn more salary than him.

The example consists of three query blocks: the outer query and two inner queries. The inner query blocks are executed first, producing the query results SA\_REP and 8600, respectively. The outer query block is then processed and uses the values that were returned by the inner queries to complete its search conditions.

Both inner queries return single values (SA\_REP and 8600, respectively), so this SQL statement is called a single-row subquery.

**Note:** The outer and inner queries can get data from different tables.

## Using Group Functions in a Subquery

```
SELECT last_name, job_id, salary
FROM employees
WHERE salary = ← 2500
               (SELECT MIN(salary)
                FROM employees);
```

	LAST_NAME	JOB_ID	SALARY
1	Vargas	ST_CLERK	2500

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using Group Functions in a Subquery

You can display data from a main query by using a group function in a subquery to return a single row. The subquery is in parentheses and is placed after the comparison condition.

The example in the slide displays the employee last name, job ID, and salary of all employees whose salary is equal to the minimum salary. The MIN group function returns a single value (2500) to the outer query.

## The HAVING Clause with Subqueries

- The Oracle server executes the subqueries first.
- The Oracle server returns results into the HAVING clause of the main query.

```
SELECT department_id, MIN(salary)
FROM employees
GROUP BY department_id
HAVING MIN(salary) > (SELECT MIN(salary)
FROM employees
WHERE department_id = 50);
```

2500

DEPARTMENT_ID	MIN(SALARY)
1	(null) 7000
2	90 17000
3	20 6000
...	
7	10 4400

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## The HAVING Clause with Subqueries

You can use subqueries not only in the WHERE clause, but also in the HAVING clause. The Oracle server executes the subquery and the results are returned into the HAVING clause of the main query.

The SQL statement in the slide displays all the departments that have a minimum salary greater than that of department 50.

### Example:

Find the job with the lowest average salary.

```
SELECT job_id, AVG(salary)
FROM employees
GROUP BY job_id
HAVING AVG(salary) = (SELECT MIN(AVG(salary))
FROM employees
GROUP BY job_id);
```

JOB_ID	AVG(SALARY)
1 ST_CLERK	2925

## What Is Wrong with This Statement?

```
SELECT employee_id, last_name
FROM employees
WHERE salary =
  (SELECT MIN(salary)
   FROM employees
   GROUP BY department_id);
```

ORA-01427: single-row subquery returns more than one ...



An error was encountered performing the requested operation:

ORA-01427: single-row subquery returns more than one row  
01427. 00000 - "single-row subquery returns more than one row"

\*Cause:

\*Action:

Error at Line:1

**Single-row operator  
with multiple-row  
subquery**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## What Is Wrong with This Statement?

A common error with subqueries occurs when more than one row is returned for a single-row subquery.

In the SQL statement in the slide, the subquery contains a GROUP BY clause, which implies that the subquery will return multiple rows, one for each group that it finds. In this case, the results of the subquery are 4400, 6000, 2500, 4200, 7000, 17000, and 8300.

The outer query takes those results and uses them in its WHERE clause. The WHERE clause contains an equal (=) operator, a single-row comparison operator that expects only one value. The = operator cannot accept more than one value from the subquery and, therefore, generates the error.

To correct this error, change the = operator to IN.

## No Rows Returned by the Inner Query

```
SELECT last_name, job_id
FROM employees
WHERE job_id =
    (SELECT job_id
     FROM employees
     WHERE last_name = 'Haas');
```

0 rows selected

**Subquery returns no rows because there is no employee named "Haas."**

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### No Rows Returned by the Inner Query

A common problem with subqueries occurs when no rows are returned by the inner query.

In the SQL statement in the slide, the subquery contains a `WHERE` clause. Presumably, the intention is to find the employee whose name is Haas. The statement is correct, but selects no rows when executed.

Because, there is no employee named Haas. So the subquery returns no rows. The outer query takes the results of the subquery (null) and uses these results in its `WHERE` clause. The outer query finds no employee with a job ID equal to null, and so returns no rows. If a job existed with a value of null, the row is not returned because comparison of two null values yields a null; therefore, the `WHERE` condition is not true.

## Lesson Agenda

- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
  - Group functions in a subquery
  - HAVING clause with subqueries
- Multiple-row subqueries
  - Use ALL or ANY operator
- Null values in a subquery

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Multiple-Row Subqueries

- Return more than one row
- Use multiple-row comparison operators

Operator	Meaning
IN	Equal to any member in the list
ANY	Must be preceded by =, !=, >, <, <=, >=. Compares a value to each value in a list or returned by a query. Evaluates to FALSE if the query returns no rows.
ALL	Must be preceded by =, !=, >, <, <=, >=. Compares a value to every value in a list or returned by a query. Evaluates to TRUE if the query returns no rows.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Multiple-Row Subqueries

Subqueries that return more than one row are called multiple-row subqueries. You use a multiple-row operator, instead of a single-row operator, with a multiple-row subquery. The multiple-row operator expects one or more values:

```
SELECT last_name, salary, department_id
FROM employees
WHERE salary IN (SELECT MIN(salary)
                 FROM employees
                 GROUP BY department_id);
```

#### Example:

Find the employees who earn the same salary as the minimum salary for each department.

The inner query is executed first, producing a query result. The main query block is then processed and uses the values that were returned by the inner query to complete its search condition. In fact, the main query appears to the Oracle server as follows:

```
SELECT last_name, salary, department_id
FROM employees
WHERE salary IN (2500, 4200, 4400, 6000, 7000, 8300,
                8600, 17000);
```

## Using the ANY Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary
FROM employees 9000, 6000, 4200
WHERE salary < ANY
  (SELECT salary
   FROM employees
   WHERE job_id = 'IT_PROG')
AND job_id <> 'IT_PROG';
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	144 Vargas	ST_CLERK	2500
2	143 Matos	ST_CLERK	2600
3	142 Davies	ST_CLERK	3100
4	141 Rajs	ST_CLERK	3500
5	200 Whalen	AD_ASST	4400
...			
9	206 Gietz	AC_ACCOUNT	8300
10	176 Taylor	SA_REP	8600

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the ANY Operator in Multiple-Row Subqueries

The ANY operator (and its synonym, the SOME operator) compares a value to *each* value returned by a subquery. The slide example displays employees who are not IT programmers and whose salary is less than that of any IT programmer. The maximum salary that a programmer earns is \$9,000.

<ANY means less than the maximum. >ANY means more than the minimum. =ANY is equivalent to IN.

## Using the ALL Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary
FROM employees 9000, 6000, 4200
WHERE salary < ALL
  (SELECT salary
   FROM employees
   WHERE job_id = 'IT_PROG')
AND job_id <> 'IT_PROG';
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	141 Rajs	ST_CLERK	3500
2	142 Davies	ST_CLERK	3100
3	143 Matos	ST_CLERK	2600
4	144 Vargas	ST_CLERK	2500

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the ALL Operator in Multiple-Row Subqueries

The ALL operator compares a value to *every* value returned by a subquery. The example in the slide displays employees whose salary is less than the salary of all employees with a job ID of IT\_PROG and whose job is not IT\_PROG.

>ALL means more than the maximum and <ALL means less than the minimum.

The NOT operator can be used with IN, ANY, and ALL operators.

## Lesson Agenda

- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
  - Group functions in a subquery
  - HAVING clause with subqueries
- Multiple-row subqueries
  - Use ALL or ANY operator
- Null values in a subquery

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Null Values in a Subquery

```
SELECT emp.last_name
FROM   employees emp
WHERE  emp.employee_id NOT IN
                                (SELECT mgr.manager_id
                                FROM   employees mgr);
```

0 rows selected

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Null Values in a Subquery

The SQL statement in the slide attempts to display all the employees who do not have any subordinates. Logically, this SQL statement should have returned 12 rows. However, the SQL statement does not return any rows. One of the values returned by the inner query is a null value, and, therefore, the entire query returns no rows.

The reason is that all conditions that compare a null value result in a null. So whenever null values are likely to be part of the results set of a subquery, do not use the NOT IN operator. The NOT IN operator is equivalent to <> ALL.

Notice that the null value as part of the results set of a subquery is not a problem if you use the IN operator. The IN operator is equivalent to =ANY. For example, to display the employees who have subordinates, use the following SQL statement:

```
SELECT emp.last_name
FROM   employees emp
WHERE  emp.employee_id IN
                                (SELECT mgr.manager_id
                                FROM   employees mgr);
```

## Null Values in a Subquery (continued)

Alternatively, a WHERE clause can be included in the subquery to display all employees who do not have any subordinates:

```
SELECT last_name FROM employees
WHERE employee_id NOT IN
      (SELECT manager_id
       FROM employees
       WHERE manager_id IS NOT NULL);
```

Oracle Internal & Oracle Academy  
Use Only

## Quiz

Using a subquery is equivalent to performing two sequential queries and using the result of the first query as the search value(s) in the second query.

1. True
2. False

ORACLE

Copyright © 2009, Oracle. All rights reserved.

**Answer: 1**

Oracle Internal & Oracle Academy  
Use Only

## Summary

In this lesson, you should have learned how to:

- Identify when a subquery can help solve a problem
- Write subqueries when a query is based on unknown values

```
SELECT  select_list
FROM    table
WHERE   expr operator
        (SELECT select_list
         FROM table);
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Summary

In this lesson, you should have learned how to use subqueries. A subquery is a `SELECT` statement that is embedded in the clause of another SQL statement. Subqueries are useful when a query is based on a search criterion with unknown intermediate values.

Subqueries have the following characteristics:

- Can pass one row of data to a main statement that contains a single-row operator, such as `=`, `<>`, `>`, `>=`, `<`, or `<=`
- Can pass multiple rows of data to a main statement that contains a multiple-row operator, such as `IN`
- Are processed first by the Oracle server, after which the `WHERE` or `HAVING` clause uses the results
- Can contain group functions

## Practice 7: Overview

This practice covers the following topics:

- Creating subqueries to query values based on unknown criteria
- Using subqueries to find out the values that exist in one set of data and not in another

ORACLE

Copyright © 2009, Oracle. All rights reserved.


### Practice 7: Overview

In this practice, you write complex queries using nested `SELECT` statements.

For practice questions, you may want to create the inner query first. Make sure that it runs and produces the data that you anticipate before you code the outer query.

## Practice 7

1. The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).



	LAST_NAME	HIRE_DATE
1	Abel	11-MAY-96
2	Taylor	24-MAR-98

2. Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary.

	EMPLOYEE_ID	LAST_NAME	SALARY
1	103	Hunold	9000
2	149	Zlotkey	10500
3	174	Abel	11000
4	205	Higgins	12000
5	201	Hartstein	13000
6	101	Kochhar	17000
7	102	De Haan	17000
8	100	King	24000

### Practice 7 (continued)

- Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains the letter “u.” Save your SQL statement as `lab_07_03.sql`. Run your query.

	EMPLOYEE_ID	LAST_NAME
1	124	Mourgos
2	141	Rajs
3	142	Davies
4	143	Matos
5	144	Vargas
6	103	Hunold
7	104	Ernst
8	107	Lorentz

- The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.

	LAST_NAME	DEPARTMENT_ID	JOB_ID
1	Whalen	10	AD_ASST
2	King	90	AD_PRES
3	Kochhar	90	AD_VP
4	De Haan	90	AD_VP
5	Higgins	110	AC_MGR
6	Gietz	110	AC_ACCOUNT

Modify the query so that the user is prompted for a location ID. Save this to a file named `lab_07_04.sql`.

- Create a report for HR that displays the last name and salary of every employee who reports to King.

	LAST_NAME	SALARY
1	Kochhar	17000
2	De Haan	17000
3	Mourgos	5800
4	Zlotkey	10500
5	Hartstein	13000

### Practice 7 (continued)

6. Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

	DEPARTMENT_ID	LAST_NAME	JOB_ID
1	90	King	AD_PRES
2	90	Kochhar	AD_VP
3	90	De Haan	AD_VP

If you have the time, complete the following exercise:

7. Modify the query in `lab_07_03.sql` to display the employee number, last name, and salary of all employees who earn more than the average salary, and who work in a department with any employee whose last name contains a “u.” Resave `lab_07_03.sql` as `lab_07_07.sql`. Run the statement in `lab_07_07.sql`.

	EMPLOYEE_ID	LAST_NAME	SALARY
1	103	Hunold	9000

Oracle Internal & Oracle Academy  
Use Only

# Using the Set Operators



ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Objectives

After completing this lesson, you should be able to do the following:

- Describe set operators
- Use a set operator to combine multiple queries into a single query
- Control the order of rows returned

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Objectives

In this lesson, you learn how to write queries by using set operators.

## Lesson Agenda


- Set Operators: Types and guidelines
- Tables used in this lesson
- UNION and UNION ALL operator
- INTERSECT operator
- MINUS operator
- Matching the SELECT statements
- Using the ORDER BY clause in set operations

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Set Operators



ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Set Operators

Set operators combine the results of two or more component queries into one result. Queries containing set operators are called *compound queries*.

Operator	Returns
UNION	Rows from both queries after eliminating duplications
UNION ALL	Rows from both queries, including all duplications
INTERSECT	Rows that are common to both queries
MINUS	Rows in the first query that are not present in the second query

All set operators have equal precedence. If a SQL statement contains multiple set operators, the Oracle server evaluates them from left (top) to right (bottom)—if no parentheses explicitly specify another order. You should use parentheses to specify the order of evaluation explicitly in queries that use the INTERSECT operator with other set operators.

## Set Operator Guidelines

- The expressions in the `SELECT` lists must match in number.
- The data type of each column in the second query must match the data type of its corresponding column in the first query.
- Parentheses can be used to alter the sequence of execution.
- `ORDER BY` clause can appear only at the very end of the statement.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Set Operator Guidelines

- The expressions in the `SELECT` lists of the queries must match in number and data type. Queries that use `UNION`, `UNION ALL`, `INTERSECT`, and `MINUS` operators in their `WHERE` clause must have the same number and data type of columns in their `SELECT` list. The data type of the columns in `SELECT` list of the queries in the compound query may not be exactly the same. The column in second query must be in the same data type group (such as numeric or character) as the corresponding column in the first query.
- Set operators can be used in subqueries.
- You should use parentheses to specify the order of evaluation in queries that use the `INTERSECT` operator with other set operators. This ensures compliance with emerging SQL standards that will give the `INTERSECT` operator greater precedence than the other set operators.

## The Oracle Server and Set Operators

- Duplicate rows are automatically eliminated except in UNION ALL.
- Column names from the first query appear in the result.
- The output is sorted in ascending order by default except in UNION ALL.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### The Oracle Server and Set Operators

When a query uses set operators, the Oracle server eliminates duplicate rows automatically except in the case of the UNION ALL operator. The column names in the output are decided by the column list in the first SELECT statement. By default, the output is sorted in ascending order of the first column of the SELECT clause.

The corresponding expressions in the SELECT lists of the component queries of a compound query must match in number and data type. If component queries select character data, the data type of the return values is determined as follows:

- If both queries select values of CHAR data type, of equal length, then the returned values have the CHAR data type of that length. If the queries select values of CHAR with different lengths, then the returned value is VARCHAR2 with the length of the larger CHAR value.
- If either or both of the queries select values of VARCHAR2 data type, then the returned values have the VARCHAR2 data type.

If component queries select numeric data, then the data type of the return values is determined by numeric precedence. If all queries select values of the NUMBER type, then the returned values have the NUMBER data type. In queries using set operators, the Oracle server does not perform implicit conversion across data type groups. Therefore, if the corresponding expressions of component queries resolve to both character data and numeric data, the Oracle server returns an error.

## Lesson Agenda

- Set Operators: Types and guidelines
- **Tables used in this lesson**
- UNION and UNION ALL operator
- INTERSECT operator
- MINUS operator
- Matching the SELECT statements
- Using the ORDER BY clause in set operations

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Tables Used in This Lesson

The tables used in this lesson are:

- **EMPLOYEES:** Provides details regarding all current employees
- **JOB\_HISTORY:** Records the details of the start date and end date of the former job, and the job identification number and department when an employee switches jobs

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Tables Used in This Lesson

Two tables are used in this lesson. They are the **EMPLOYEES** table and the **JOB\_HISTORY** table.

You are already familiar with the **EMPLOYEES** table that stores employee details such as a unique identification number, email address, job identification (such as **ST\_CLERK**, **SA\_REP**, and so on), salary, manager and so on.

Some of the employees have been with the company for a long time and have switched to different jobs. This is monitored using the **JOB\_HISTORY** table. When an employee switches jobs, the details of the start date and end date of the former job, the **job\_id** (such as **ST\_CLERK**, **SA\_REP**, and so on), and the department are recorded in the **JOB\_HISTORY** table.

The structure and data from the **EMPLOYEES** and **JOB\_HISTORY** tables are shown on the following pages.

## Tables Used in This Lesson (continued)

There have been instances in the company, of people who have held the same position more than once during their tenure with the company. For example, consider the employee Taylor, who joined the company on 24-MAR-1998. Taylor held the job title SA\_REP for the period 24-MAR-98 to 31-DEC-98 and the job title SA\_MAN for the period 01-JAN-99 to 31-DEC-99. Taylor moved back into the job title of SA\_REP, which is his current job title.

```
DESCRIBE employees
```

DESCRIBE employees		
Name	Null	Type
EMPLOYEE_ID	NOT NULL	NUMBER(6)
FIRST_NAME		VARCHAR2(20)
LAST_NAME	NOT NULL	VARCHAR2(25)
EMAIL	NOT NULL	VARCHAR2(25)
PHONE_NUMBER		VARCHAR2(20)
HIRE_DATE	NOT NULL	DATE
JOB_ID	NOT NULL	VARCHAR2(10)
SALARY		NUMBER(8,2)
COMMISSION_PCT		NUMBER(2,2)
MANAGER_ID		NUMBER(6)
DEPARTMENT_ID		NUMBER(4)

Oracle Internal & Oracle Academy  
Use Only

## Tables Used in This Lesson (continued)

```
SELECT employee_id, last_name, job_id, hire_date, department_id
FROM employees;
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID	HIRE_DATE	DEPARTMENT_ID
1	100	King	AD_PRES	17-JUN-87	90
2	101	Kochhar	AD_VP	21-SEP-89	90
3	102	De Haan	AD_VP	13-JAN-93	90
4	103	Hunold	IT_PROG	03-JAN-90	60
5	104	Ernst	IT_PROG	21-MAY-91	60
6	107	Lorentz	IT_PROG	07-FEB-99	60
7	124	Mourgos	ST_MAN	16-NOV-99	50
8	141	Rajs	ST_CLERK	17-OCT-95	50
9	142	Davies	ST_CLERK	29-JAN-97	50
10	143	Matos	ST_CLERK	15-MAR-98	50
11	144	Vargas	ST_CLERK	09-JUL-98	50
12	149	Zlotkey	SA_MAN	29-JAN-00	80
13	174	Abel	SA_REP	11-MAY-96	80
14	176	Taylor	SA_REP	24-MAR-98	80
15	178	Grant	SA_REP	24-MAY-99	(null)
16	200	Whalen	AD_ASST	17-SEP-87	10
17	201	Hartstein	MK_MAN	17-FEB-96	20

...

```
DESCRIBE job_history
```

Name	Null	Type
EMPLOYEE_ID	NOT NULL	NUMBER(6)
START_DATE	NOT NULL	DATE
END_DATE	NOT NULL	DATE
JOB_ID	NOT NULL	VARCHAR2(10)
DEPARTMENT_ID		NUMBER(4)

### Tables Used in This Lesson (continued)

```
SELECT * FROM job_history;
```

		EMPLOYEE_ID	START_DATE	END_DATE		JOB_ID		DEPARTMENT_ID
1		102	13-JAN-93	24-JUL-98		IT_PROG		60
2		101	21-SEP-89	27-OCT-93		AC_ACCOUNT		110
3		101	28-OCT-93	15-MAR-97		AC_MGR		110
4		201	17-FEB-96	19-DEC-99		MK_REP		20
5		114	24-MAR-98	31-DEC-99		ST_CLERK		50
6		122	01-JAN-99	31-DEC-99		ST_CLERK		50
7		200	17-SEP-87	17-JUN-93		AD_ASST		90
8		176	24-MAR-98	31-DEC-98		SA_REP		80
9		176	01-JAN-99	31-DEC-99		SA_MAN		80
10		200	01-JUL-94	31-DEC-98		AC_ACCOUNT		90

Oracle Internal & Oracle Academy  
Use Only

## Lesson Agenda


- Set Operators: Types and guidelines
- Tables used in this lesson
- **UNION and UNION ALL operator**
- INTERSECT operator
- MINUS operator
- Matching the SELECT statements
- Using the ORDER BY clause in set operations

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

# UNION Operator



The UNION operator returns rows from both queries after eliminating duplications.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## UNION Operator

The UNION operator returns all rows that are selected by either query. Use the UNION operator to return all rows from multiple tables and eliminate any duplicate rows.

### Guidelines

- The number of columns being selected must be the same.
- The data types of the columns being selected must be in the same data type group (such as numeric or character).
- The names of the columns need not be identical.
- UNION operates over all of the columns being selected.
- NULL values are not ignored during duplicate checking.
- By default, the output is sorted in ascending order of the columns of the SELECT clause.

## Using the UNION Operator

Display the current and previous job details of all employees.  
Display each employee only once.

```
SELECT employee_id, job_id
FROM employees
UNION
SELECT employee_id, job_id
FROM job_history;
```

EMPLOYEE_ID	JOB_ID
1	100 AD_PRES
2	101 AC_ACCOUNT
...	...
22	200 AC_ACCOUNT
23	200 AD_ASST
24	201 MK_MAN
...	...

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the UNION Operator

The UNION operator eliminates any duplicate records. If records that occur in both the EMPLOYEES and the JOB\_HISTORY tables are identical, the records are displayed only once. Observe in the output shown in the slide that the record for the employee with the EMPLOYEE\_ID 200 appears twice because the JOB\_ID is different in each row.

Consider the following example:

```
SELECT employee_id, job_id, department_id
FROM employees
UNION
SELECT employee_id, job_id, department_id
FROM job_history;
```


EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
1	100 AD_PRES	90
2	101 AC_ACCOUNT	110
...	...	...
22	200 AC_ACCOUNT	90
23	200 AD_ASST	10
24	200 AD_ASST	90
...	...	...

## Using the UNION Operator (continued)

In the preceding output, employee 200 appears three times. Why? Note the DEPARTMENT\_ID values for employee 200. One row has a DEPARTMENT\_ID of 90, another 10, and the third 90. Because of these unique combinations of job IDs and department IDs, each row for employee 200 is unique and therefore not considered to be a duplicate. Observe that the output is sorted in ascending order of the first column of the SELECT clause (in this case, EMPLOYEE\_ID).

Oracle Internal & Oracle Academy  
Use Only

## UNION ALL Operator



The **UNION ALL** operator returns rows from both queries, including all duplications.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### UNION ALL Operator

Use the **UNION ALL** operator to return all rows from multiple queries.

#### Guidelines

The guidelines for **UNION** and **UNION ALL** are the same, with the following two exceptions that pertain to **UNION ALL**: Unlike **UNION**, duplicate rows are not eliminated and the output is not sorted by default.

## Using the UNION ALL Operator

Display the current and previous departments of all employees.

```
SELECT employee_id, job_id, department_id
FROM employees
UNION ALL
SELECT employee_id, job_id, department_id
FROM job_history
ORDER BY employee_id;
```

EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
1	100 AD_PRES	90
...		
16	144 ST_CLERK	50
17	149 SA_MAN	80
18	174 SA_REP	80
19	176 SA_REP	80
20	176 SA_MAN	80
21	176 SA_REP	80
22	178 SA_REP	(null)
...		
30	206 AC_ACCOUNT	110

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the UNION ALL Operator

In the example, 30 rows are selected. The combination of the two tables totals to 30 rows. The UNION ALL operator does not eliminate duplicate rows. UNION returns all distinct rows selected by either query. UNION ALL returns all rows selected by either query, including all duplicates. Consider the query in the slide, now written with the UNION clause:

```
SELECT employee_id, job_id, department_id
FROM employees
UNION
SELECT employee_id, job_id, department_id
FROM job_history
ORDER BY employee_id;
```

The preceding query returns 29 rows. This is because it eliminates the following row (because it is a duplicate):

176 SA_REP	80
------------	----

## Lesson Agenda


- Set Operators: Types and guidelines
- Tables used in this lesson
- UNION and UNION ALL operator
- **INTERSECT operator**
- MINUS operator
- Matching the SELECT statements
- Using ORDER BY clause in set operations

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## INTERSECT Operator



The **INTERSECT** operator returns rows that are common to both queries.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### INTERSECT Operator

Use the **INTERSECT** operator to return all rows that are common to multiple queries.

#### Guidelines

- The number of columns and the data types of the columns being selected by the **SELECT** statements in the queries must be identical in all the **SELECT** statements used in the query. The names of the columns, however, need not be identical.
- Reversing the order of the intersected tables does not alter the result.
- **INTERSECT** does not ignore **NULL** values.

## Using the INTERSECT Operator

Display the employee IDs and job IDs of those employees who currently have a job title that is the same as their previous one (that is, they changed jobs but have now gone back to doing the same job they did previously).

```
SELECT employee_id, job_id
FROM employees
INTERSECT
SELECT employee_id, job_id
FROM job_history;
```

	EMPLOYEE_ID	JOB_ID
1	176	SA_REP
2	200	AD_ASST

ORACLE

Copyright © 2009, Oracle. All rights reserved.

## Using the INTERSECT Operator

In the example in this slide, the query returns only those records that have the same values in the selected columns in both tables.

What will be the results if you add the DEPARTMENT\_ID column to the SELECT statement from the EMPLOYEES table and add the DEPARTMENT\_ID column to the SELECT statement from the JOB\_HISTORY table, and run this query? The results may be different because of the introduction of another column whose values may or may not be duplicates.

### Example:

```
SELECT employee_id, job_id, department_id
FROM employees
INTERSECT
SELECT employee_id, job_id, department_id
FROM job_history;
```

	EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
1	176	SA_REP	80

Employee 200 is no longer part of the results because the EMPLOYEES.DEPARTMENT\_ID value is different from the JOB\_HISTORY.DEPARTMENT\_ID value.

## Lesson Agenda


- Set Operators: Types and guidelines
- Tables used in this lesson
- UNION and UNION ALL operator
- INTERSECT operator
- **MINUS operator**
- Matching the SELECT statements
- Using the ORDER BY clause in set operations

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## MINUS Operator



The **MINUS** operator returns all the distinct rows selected by the first query, but not present in the second query result set.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### MINUS Operator

Use the **MINUS** operator to return all distinct rows selected by the first query, but not present in the second query result set (the first **SELECT** statement **MINUS** the second **SELECT** statement).

**Note:** The number of columns must be the same and the data types of the columns being selected by the **SELECT** statements in the queries must belong to the same data type group in all the **SELECT** statements used in the query. The names of the columns, however, need not be identical.

## Using the MINUS Operator

Display the employee IDs of those employees who have not changed their jobs even once.

```
SELECT employee_id
FROM employees
MINUS
SELECT employee_id
FROM job_history;
```

	EMPLOYEE_ID
1	100
2	103
3	104
4	107
5	124
...	
14	205
15	206

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the MINUS Operator

In the example in the slide, the employee IDs in the JOB\_HISTORY table are subtracted from those in the EMPLOYEES table. The results set displays the employees remaining after the subtraction; they are represented by rows that exist in the EMPLOYEES table, but do not exist in the JOB\_HISTORY table. These are the records of the employees who have not changed their jobs even once.

## Lesson Agenda

- Set Operators: Types and guidelines
- Tables used in this lesson
- UNION and UNION ALL operator
- INTERSECT operator
- MINUS operator
- **Matching the SELECT statements**
- Using ORDER BY clause in set operations

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Matching the SELECT Statements

- Using the UNION operator, display the location ID, department name, and the state where it is located.
- You must match the data type (using the TO\_CHAR function or any other conversion functions) when columns do not exist in one or the other table.

```
SELECT location_id, department_name "Department",  
       TO_CHAR(NULL) "Warehouse location"  
FROM departments  
UNION  
SELECT location_id, TO_CHAR(NULL) "Department",  
       state_province  
FROM locations;
```

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Matching the SELECT Statements

Because the expressions in the SELECT lists of the queries must match in number, you can use the dummy columns and the data type conversion functions to comply with this rule. In the slide, the name, Warehouse location, is given as the dummy column heading. The TO\_CHAR function is used in the first query to match the VARCHAR2 data type of the state\_province column that is retrieved by the second query. Similarly, the TO\_CHAR function in the second query is used to match the VARCHAR2 data type of the department\_name column that is retrieved by the first query.

The output of the query is shown:

	LOCATION_ID	Department	Warehouse location
1	1400	IT	(null)
2	1400	(null)	Texas
3	1500	Shipping	(null)
4	1500	(null)	California
5	1700	Accounting	(null)
6	1700	Administration	(null)
7	1700	Contracting	(null)
8	1700	Executive	(null)
9	1700	(null)	Washington

■ ■ ■

## Matching the SELECT Statement: Example

Using the UNION operator, display the employee ID, job ID, and salary of all employees.

```
SELECT employee_id, job_id, salary
FROM employees
UNION
SELECT employee_id, job_id, 0
FROM job_history;
```

EMPLOYEE_ID	JOB_ID	SALARY
1	100 AD_PRES	24000
2	101 AC_ACCOUNT	0
3	101 AC_MGR	0
4	101 AD_VP	17000
5	102 AD_VP	17000
...		
29	205 AC_MGR	12000
30	206 AC_ACCOUNT	8300

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Matching the SELECT Statement: Example

The EMPLOYEES and JOB\_HISTORY tables have several columns in common (for example, EMPLOYEE\_ID, JOB\_ID, and DEPARTMENT\_ID). But what if you want the query to display the employee ID, job ID, and salary using the UNION operator, knowing that the salary exists only in the EMPLOYEES table?

The code example in the slide matches the EMPLOYEE\_ID and JOB\_ID columns in the EMPLOYEES and JOB\_HISTORY tables. A literal value of 0 is added to the JOB\_HISTORY SELECT statement to match the numeric SALARY column in the EMPLOYEES SELECT statement.

In the results shown in the slide, each row in the output that corresponds to a record from the JOB\_HISTORY table contains a 0 in the SALARY column.

## Lesson Agenda

- Set Operators: Types and guidelines
- Tables used in this lesson
- UNION and UNION ALL operator
- INTERSECT operator
- MINUS operator
- Matching the SELECT statements
- Using the ORDER BY clause in set operations

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Oracle Internal & Oracle Academy  
Use Only

## Using the ORDER BY Clause in Set Operations

- The ORDER BY clause can appear only once at the end of the compound query.
- Component queries cannot have individual ORDER BY clauses.
- ORDER BY clause recognizes only the columns of the first SELECT query.
- By default, the first column of the first SELECT query is used to sort the output in an ascending order.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Using the ORDER BY Clause in Set Operations

The ORDER BY clause can be used only once in a compound query. If used, the ORDER BY clause must be placed at the end of the query. The ORDER BY clause accepts the column name or an alias. By default, the output is sorted in ascending order in the first column of the first SELECT query.

**Note:** The ORDER BY clause does not recognize the column names of the second SELECT query. To avoid confusion over column names, it is a common practice to ORDER BY column positions.

For example, in the following statement, the output will be shown in ascending order of the job\_id.

```
SELECT employee_id, job_id, salary
FROM   employees
UNION
SELECT employee_id, job_id, 0
FROM   job_history
ORDER BY 2;
```

If you omit the ORDER BY, then by default the output will be sorted in the ascending order of employee\_id. You cannot use the columns from the second query to sort the output.

## Quiz

Identify the set operator guidelines.

1. The expressions in the `SELECT` lists must match in number.
2. Parentheses may not be used to alter the sequence of execution.
3. The data type of each column in the second query must match the data type of its corresponding column in the first query.
4. The `ORDER BY` clause can be used only once in a compound query, unless a `UNION ALL` operator is used.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

**Answer: 1, 3**

## Summary

In this lesson, you should have learned how to use:

- UNION to return all distinct rows
- UNION ALL to return all rows, including duplicates
- INTERSECT to return all rows that are shared by both queries
- MINUS to return all distinct rows that are selected by the first query, but not by the second
- ORDER BY only at the very end of the statement

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Summary

- The UNION operator returns all the distinct rows selected by each query in the compound query. Use the UNION operator to return all rows from multiple tables and eliminate any duplicate rows.
- Use the UNION ALL operator to return all rows from multiple queries. Unlike the case with the UNION operator, duplicate rows are not eliminated and the output is not sorted by default.
- Use the INTERSECT operator to return all rows that are common to multiple queries.
- Use the MINUS operator to return rows returned by the first query that are not present in the second query.
- Remember to use the ORDER BY clause only at the very end of the compound statement.
- Make sure that the corresponding expressions in the SELECT lists match in number and data type.

## Practice 8: Overview

In this practice, you create reports by using:

- The UNION operator
- The INTERSECTION operator
- The MINUS operator

ORACLE

Copyright © 2009, Oracle. All rights reserved.

### Practice 8: Overview

In this practice, you write queries using the set operators.

## Practice 8

1. The HR department needs a list of department IDs for departments that do not contain the job ID ST\_CLERK. Use the set operators to create this report.

	DEPARTMENT_ID
1	10
2	20
3	60
4	80
5	90
6	110
7	190

2. The HR department needs a list of countries that have no departments located in them. Display the country ID and the name of the countries. Use the set operators to create this report.

	COUNTRY_ID	COUNTRY_NAME
1	DE	Germany

3. Produce a list of jobs for departments 10, 50, and 20, in that order. Display the job ID and department ID by using the set operators.

	JOB_ID	DEPARTMENT_ID
1	AD_ASST	10
2	ST_MAN	50
3	ST_CLERK	50
4	MK_MAN	20
5	MK_REP	20

4. Create a report that lists the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired by the company (that is, they changed jobs but have now gone back to doing their original job).

	EMPLOYEE_ID	JOB_ID
1	176	SA_REP
2	200	AD_ASST

### Practice 8 (continued)

5. The HR department needs a report with the following specifications:
- Last name and department ID of all employees from the EMPLOYEES table, regardless of whether or not they belong to a department
  - Department ID and department name of all departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them

Write a compound query to accomplish this.

	LAST_NAME	DEPARTMENT_ID	TO_CHAR(NULL)
1	Abel	80	(null)
2	Davies	50	(null)
3	De Haan	90	(null)
4	Ernst	60	(null)
5	Fay	20	(null)
6	Gietz	110	(null)
7	Grant	(null)	(null)
8	Hartstein	20	(null)
9	Higgins	110	(null)
10	Hunold	60	(null)
11	King	90	(null)
12	Kochhar	90	(null)
13	Lorentz	60	(null)
14	Matos	50	(null)
15	Mourgos	50	(null)
16	Rajs	50	(null)
17	Taylor	80	(null)
18	Vargas	50	(null)
19	Whalen	10	(null)
20	Zlotkey	80	(null)
21	(null)	10	Administration
22	(null)	20	Marketing
23	(null)	50	Shipping
24	(null)	60	IT
25	(null)	80	Sales
26	(null)	90	Executive
27	(null)	110	Accounting
28	(null)	190	Contracting

